

Power Transformers


Autotransformers



Case Type X



Case Type M



Case Type U

:: Description

Triad autotransformers are single winding transformers in which the primary coil is a fraction of the entire winding for voltage step-up or the secondary coil is a fraction of the entire winding for voltage step-down (see Technical Notes for an equivalent circuit diagram). In ordinary double wound power transformers, the primary and secondary are isolated and all the power is transferred by induction. In autotransformers, part of the power is transferred conductively through

the windings. Triad autotransformers come in a variety of configurations, case types and output watts (VA) ratings in excess of 2,000 watts. A universal isolation/autotransformer/voltage control model is available with up to a 4,000 output watts rating when operated as an autotransformer.

:: Specifications

See Technical Notes

:: Step-Up/Step-Down Autotransformers

Section	Part No.	VA	Primary Voltage	Secondary		Case Type	Connections	Dimensions			Mounting Dimensions		Wt. Lbs.
				Volts $\pm 5\%$	RMS Amps			H	W	D	MW	MD	
A	N-1X	50	230	115	0.435	X (1)	Leads	2 $\frac{1}{2}$ "	3 $\frac{1}{16}$ "	2"	3 $\frac{1}{8}$ "	•	1.50
B	N-3MGAA	85	230	115	0.74	M (3)	6' Cord, Plug & Socket	3 $\frac{3}{8}$ "	2 $\frac{3}{32}$ "	3 $\frac{1}{2}$ "	2 $\frac{1}{4}$ "	2 $\frac{1}{8}$ "	3.00
C	N-2X	100	230	115	0.87	X (1)	Leads	2"	4"	2 $\frac{1}{16}$ "	3 $\frac{3}{8}$ "	•	2.10
D	N-150MG	150	115	230	0.65	M (3)	6'-3 Wire Cord, Plug & Socket	3 $\frac{9}{32}$ "	2 $\frac{3}{32}$ "	3 $\frac{1}{16}$ "	2 $\frac{1}{4}$ "	2 $\frac{1}{8}$ "	4.90
	F-302U#	150	277	115	1.30	U (2)	Leads	2 $\frac{1}{16}$ "	3 $\frac{3}{8}$ "	2 $\frac{1}{4}$ "	2 $\frac{1}{8}$ "	2	2.90
	N-4MGA	150	230	115	1.30	M (3)	6' Cord, Plug & Socket	3 $\frac{9}{32}$ "	2 $\frac{3}{32}$ "	4 $\frac{1}{4}$ "	2 $\frac{1}{4}$ "	2 $\frac{1}{8}$ "	4.70
E	N-6U	200	230	115	1.70	U (2)	Leads	3"	2 $\frac{9}{16}$ "	2 $\frac{1}{8}$ "	2 $\frac{1}{4}$ "	2 $\frac{1}{8}$ "	3.60
F	N-250MGA	250	115	230	1.10	M (3)	6'-3 Wire Cord, Plug & Socket	3 $\frac{1}{4}$ "	3 $\frac{1}{4}$ "	3 $\frac{1}{16}$ "	2 $\frac{1}{2}$ "	2 $\frac{1}{8}$ "	6.60
G	N-5MGA	250	230	115	2.17	M (3)	6' Cord, Plug & Socket	3 $\frac{1}{4}$ "	3 $\frac{3}{32}$ "	4 $\frac{13}{16}$ "	2 $\frac{1}{2}$ "	3 $\frac{1}{2}$ "	7.00
H	N-500MGA	500	115	230	2.20	M (3)	6'-3 Wire Cord, Plug & Socket	4 $\frac{1}{4}$ "	3 $\frac{7}{8}$ "	4 $\frac{3}{4}$ "	3	3 $\frac{3}{8}$ "	11.20
I	N-7MGA	600	230	115	5.22	M (3)	6' Cord, Plug & Socket	4 $\frac{1}{4}$ "	3 $\frac{9}{16}$ "	5"	3	3 $\frac{3}{8}$ "	12.00
J	N-1000MGA	1,000	115	230	4.35	M (4)	6'-3 Wire Cord, Plug & Socket	5"	4 $\frac{1}{2}$ "	5 $\frac{1}{2}$ "	3 $\frac{1}{2}$ "	4 $\frac{1}{2}$ "	17.39
K	N-9MGA	1,250	230	115	10.85	M (4)	6' Cord, Plug & Socket	5 $\frac{1}{8}$ "	4 $\frac{1}{2}$ "	6"	3 $\frac{1}{2}$ "	4 $\frac{1}{2}$ "	21.00
L	N-11MGA	2,000	230	115	17.40	M (4)	6' Cord, Plug & Socket	5 $\frac{1}{8}$ "	4 $\frac{1}{2}$ "	8 $\frac{1}{4}$ "	3 $\frac{1}{2}$ "	6 $\frac{1}{8}$ "	33.25


Δ Has 3-wire plug, cord and socket # 60 Hz Mounting hole sizes: (1) = $\frac{3}{16}$ " (2) = $\frac{1}{64}$ " x $\frac{3}{16}$ " (3) = $\frac{3}{16}$ " x $\frac{3}{16}$ "

:: Outline Dimensions

Technical Notes

1. Output wattage (VA) ratings 50 to 2,000 W.
2. Wide selection of case types, including 6' line cords, plugs, sockets and lugs.
3. All transformers are 50/60 Hz line frequency, except as noted.
4. Hi-pot tested at 1,500 VRMS.

Autotransformer



(Single winding input providing input/output)

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com