

max. 222 m³/h

DC axial fans

Series 8200 J 80 x 80 x 38 mm



Highlights:



- Very rigid compression curve for high air flow at high back pressure.
- Innovative impeller with winglets for low noise.
- Optional Vario-Pro: Highly adaptable software configuration of the fan enables a tailor-made solution to the specific requirements of your applications.

General characteristics:

- Material: fibreglass-reinforced plastic. Impeller PA, housing PBT.
- Fully integrated electronic commutation. Protected against reverse polarity and locking.
- Connection via single strands AWG 24 (H3 and H4: AWG 22), TR 64. Bared and tin-plated.
- Air exhaust over struts. Direction of rotation counter-clockwise, seen on rotor.
- Mass: 160 g (H3 and H4: 200 g).

Nominal data		Air flow	Air flow	Nominal voltage	Voltage range	Sound pressure level	Sound power level	Sinter sleeve bearings	Ball bearings	Power input	Nominal speed	Temperature range	Service life L ₁₀ (40 °C)	Service life L ₁₀ (T _{max})	Life expectancy L ₁₀ Δ	Curve	Specials
Type		m³/h	CFM	VDC	VDC	dB(A)	Bel(A)	■ / ■		Watts	RPM	°C	Hours	Hours	Hours	P. 110	
8212 JN		132	77,7	12	7...13,8	55	6,6	■		10	8400	-20...+70	62 500 / 32 500	130 000	130 000	1	/2
8212 JH3	S-Force	190	111,8	12	6...13,8	66	7,3	■		25	12 000	-20...+70	55 000 / 27 500	110 000	110 000	2	/2
8212 JH4	S-Force	222	130,7	12	6...13,8	71	7,8	■		39	14 000	-20...+70	50 000 / 25 000	100 000	100 000	3	/2
8214 JN		132	77,7	24	18...26,4	55	6,6	■		10	8400	-20...+70	62 500 / 32 500	130 000	130 000	1	/2
8214 JH3	S-Force	190	111,8	24	12...27,6	66	7,3	■		25	12 000	-20...+70	55 000 / 27 500	110 000	110 000	2	/2
8214 JH4	S-Force	222	130,7	24	12...27,6	71	7,8	■		38	14 000	-20...+70	50 000 / 25 000	100 000	100 000	3	/2
8218 JN		132	77,7	48	36...53	55	6,6	■		11	8400	-20...+70	62 500 / 32 500	130 000	130 000	1	/2
8218 JH3	S-Force	190	111,8	48	20...58	66	7,3	■		25	12 000	-20...+70	55 000 / 27 500	110 000	110 000	2	/2
8218 JH4	S-Force	222	130,7	48	20...58	71	7,8	■		36	14 000	-20...+70	50 000 / 25 000	100 000	100 000	3	/2

8200 JH3 and JH4 also as standard with PWM control input and speed signal.
Speed control range from 2000 RPM up to maximum nominal speed. Stationary at 0 % PWM, maximum speed at sensor break.



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com