



SIZE :

60x60x25mm (2.36"x2.36"x0.98")

CONSTRUCTION :

Glass fiber reinforced plastic:

Impeller and housing PBT are UL 94V-0 rating

OPERATING TEMPERATURE :

Ball bearing - 30°C to + 75°C

Sleeve bearing - 10°C to + 70°C

INSULATION RESISTANCE :

10meg Ohm min. at 500 VDC

(between frame and terminal)

DIELECTRIC STRENGTH :

5mA max. at 500 VAC 60Hz one minute

(between frame and terminal)

FUNCTION :

frequency generator or rotation detection signal option

WEIGHT :


75 grams

Specifications are subject to change without notice


Specifications

MODEL NO.	BEARING	RATED VOLTAGE	OPERATING VOLTAGE RANGE	RATED CURRENT	RATED INPUT POWER	SPEED R.P.M.	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE dB-A
		VDC	V	A	W		m³/min	CFM	mmH₂O	IN H₂O	
BP602512L-03	Ball	12	10.2-13.8	0.09	1.08	2600	0.4	13.5	1.9	0.1	25.7
SP602512L-03	Sleeve										
BP602512M-03	Ball	12	10.2-13.8	0.11	1.32	3200	0.5	16.5	2.9	0.1	26.5
SP602512M-03	Sleeve										
BP602512H-03	Ball	12	10.2-13.8	0.13	1.56	3800	0.6	19.5	3.8	0.2	29.7
SP602512H-03	Sleeve										
BP602512HL-03	Ball	12	10.2-13.8	0.23	2.76	5000	0.7	25.1	6.1	0.2	36.6
SP602512HL-03	Sleeve										
BP602512HM-03	Ball	12	10.2-13.8	0.34	4.08	6000	0.9	31.0	9.3	0.4	41.1
SP602512HM-03	Sleeve										
BP602512HH-03	Ball	12	10.2-13.8	0.39	4.68	7000	1.1	37.1	11.7	0.5	47.3
SP602512HH-03	Sleeve										

Dimensions (mm)



Performance Curve



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com