# PHYSICAL INFRASTRUCTURE SOLUTIONS

B. Copper Systems

C. LISTED CER

# **Surge Suppressor Jumper Kit**

Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

Wireless

G. Outlets

H. Media Distribution

> l. Physical

Infrastructure

Management

J. Overhead &

Underfloor Routing

- Bonds power or data line surge suppressor to grounding strip or grounding busbar
- Both ends factory terminated to provide a bolt-on solution

Engineered to comply with US and International grounding requirements



| Part Number | Part Description   | Std.<br>Pkg.<br>Qty. |
|-------------|--|----------------------|
| SSGK-1      | #10 AWG (6mm²) jumper; 24" (.61m) length; factory terminated on both ends; one-hole lug on surge suppressor to two-hole lug on grounding strip/busbar side; provided with .16 oz. (5cc) of antioxidant and two each #12-24 x 1/2", M6 x 12mm, #10-32 x 1/2" and M5 x 12mm thread-forming screws. | 1                    |

# **Armored Cable Grounding Kit**

- Provides a secure bond to the armor sheath on indoor and indoor/outdoor fiber optic cables at both cassette and enclosure ends
- Worm-gear design evenly distributes forces across the armor
- Made from steel and aluminum material is compatible with common armor for long term reliability
- Black insulating cover protects and hides the connection for an aesthetically pleasing work area
- Complies with industry requirements ensuring a high level of reliability and safety



| Part Number | Part Description   | Pkg.<br>Qty. |
|-------------|--|--------------|
| ACG24K      | #6 AWG (16mm²) jumper for armored cable diameter up to 0.84" (21.3mm); 24" (609.6mm) length; factory terminated on one end with LCC6 two-hole copper compression lug and the other end with grounding terminal; provided with two each #12-24 and M6 thread-forming screws and a black polypropylene terminal cover.             | 1            |
| ACG24K-500  | #6 AWG (16mm²) jumper for armored cable diameter 0.85" (21.3mm) to 1.03" (26.2mm); 24" (609.6mm) length; factory terminated on one end with LCC6 two-hole copper compression lug and the other end with grounding terminal; provided with two each #12-24 and M6 thread-forming screws and a black polypropylene terminal cover. | 1            |
| ACGK        | Armored cable grounding kit with one grounding terminal for #6 AWG and one #10 mechanical clamp, 9/16" – 1 1/16" diameter range.   | 1            |

- K. Surface Raceway
- L. Cabinets, Racks & Cable

Management

- M. Grounding & Bonding
- N. Industrial
- 0. Labeling & Identification
- P. Cable Management Accessories
  - Q. Index

# AMEYA360 Components Supply Platform

### **Authorized Distribution Brand:**

























#### Website:

Welcome to visit www.ameya360.com

#### Contact Us:

#### Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

#### > Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

#### Customer Service :

Email service@ameya360.com

# Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com