



FEATURES:

- For continuous use up to 400°F. (200°C.)
- Adhesive back Thermocouple will bond to almost any surface
- Available in “J” & “K” calibration

MATERIALS:

“J” or “K” thermocouple mounted on a Kapton[®] surface.

RATINGS:

Temperature Range: -20° to 200°C. (-4° to 400°F.)

ORDERING INFORMATION: Model 6542X-XX

X = Calibration of Thermocouple “J” or “K” available

XX = Length in inches – Standard lengths 48” & 96”

Ordering Example: 6542K-96 is a “K” type calibration

Thermocouple with a length of 96 inches.

Kapton[®] is a registered trademark of E.I. Dupont Inc.

All dimensions are in inches. Tolerances (except noted): .xx = \pm .02” (.51 mm), .xxx = \pm .005” (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060

PomonaACCESS 90974 (800) 444-6785 or (425) 446-6010
More drawings available at www.pomonaelectronics.com

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com