

## "Compact" range with display CD20 Part number 88970052



- Green LCD with 4 lines of 18 characters and configurable backlighting
- More cost effective solution
- Industrial temperature range (-20 °C → +55 °C)
- Analogue inputs 0-10 VDC or 0-20 mA/Pt100 with converters
- Selective parameter setting : You can choose the parameters that can be adjusted on the front panel

### Part numbers

|          | Type | Inputs                            | Outputs                               | Supply  |
|----------|------|-----------------------------------|---------------------------------------|---------|
| 88970052 | CD20 | 12 digital (including 6 analogue) | 8 solid state 0.5 A (including 4 PWM) | 24 V DC |

### Specifications

#### General environment characteristics for CB, CD, XD, XB, XR and XE product types

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certifications                                                             | CE, UL, CSA, GL                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Conformity to standards (with the low voltage directive and EMC directive) | IEC/EN 61131-2 (Open equipment)<br>IEC/EN 61131-2 (Zone B)<br>IEC/EN 61000-6-2,<br>IEC/EN 61000-6-3 (*)<br>IEC/EN 61000-6-4<br>(*) Except configuration (88 970 1.1 or 88 970 1.2) + (88 970 250 or 88 970 270) + 88 970 241 class A (class B in a metal enclosure)                                                                                                                                                                                                             |
| Earthing                                                                   | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Protection rating                                                          | In accordance with IEC/EN 60529 :<br>IP40 on front panel<br>IP20 on terminal block                                                                                                                                                                                                                                                                                                                                                                                              |
| Overvoltage category                                                       | 3 in accordance with IEC/EN 60664-1                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Pollution                                                                  | Degree : 2 in accordance with IEC/EN 61131-2                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Max operating Altitude                                                     | Operation : 2000 m<br>Transport : 3,048 m                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Mechanical resistance                                                      | Immunity to vibrations IEC/EN 60068-2-6, Fc test<br>Immunity to shock IEC/EN 60068-2-27, Fa test                                                                                                                                                                                                                                                                                                                                                                                |
| Resistance to electrostatic discharge                                      | Immunity to ESD IEC/EN 61000-4-2, level 3                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Resistance to HF interference                                              | Immunity to radiated electrostatic fields<br>IEC/EN 61000-4-3,<br>Immunity to fast transients (burst immunity)<br>IEC/EN 61000-4-4, level 3<br>Immunity to shock waves<br>IEC/EN 61000-4-5<br>Radio frequency in common mode<br>IEC/EN 61000-4-6, level 3<br>Voltage dips and breaks (AC)<br>IEC/EN 61000-4-11<br>Immunity to damped oscillatory waves<br>IEC/EN 61000-4-12                                                                                                     |
| Conducted and radiated emissions                                           | Class B (*) in accordance with EN 55022, EN 55011 (CISPR22, CISPR11) group 1<br>(*) Except configuration (88 970 1.1 or 88 970 1.2) + (88 970 250 or 88 970 270) + 88 970 241 class A (class B in metallic cabinet)                                                                                                                                                                                                                                                             |
| Operating temperature                                                      | -20 → +55 °C (+40 °C in a non-ventilated enclosure) in accordance with IEC/EN 60068-2-1 and IEC/EN 60068-2-2                                                                                                                                                                                                                                                                                                                                                                    |
| Storage temperature                                                        | -40 → +70 °C in accordance with IEC/EN 60068-2-1 and IEC/EN 60068-2-2                                                                                                                                                                                                                                                                                                                                                                                                           |
| Relative humidity                                                          | 95 % max. (no condensation or dripping water) in accordance with IEC/EN 60068-2-30                                                                                                                                                                                                                                                                                                                                                                                              |
| Mounting                                                                   | On symmetrical DIN profile, 35 x 7.5 mm and 35 mm x 15 or panel (2 x 4 mm Ø)                                                                                                                                                                                                                                                                                                                                                                                                    |
| Screw terminals connection capacity                                        | Flexible wire with ferrule =<br>1 conductor : 0.25 to 2.5 mm <sup>2</sup> (AWG 24...AWG 14)<br>2 conductors 0.25 to 0.75 mm <sup>2</sup> (AWG 24...AWG 18)<br>Semi-rigid wire =<br>1 conductor : 0.2 to 2.5 mm <sup>2</sup> (AWG 25...AWG 14)<br>Rigid wire =<br>1 conductor : 0.2 to 2.5 mm <sup>2</sup> (AWG 25...AWG 14)<br>2 conductors 0.2 to 1.5 mm <sup>2</sup> (AWG 25...AWG 16)<br>Tightening torque =<br>0.5 N.m (4.5 lb-in) (tighten using screwdriver diam. 3.5 mm) |

|                                                             |                                                                                                          |
|-------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Processing characteristics of CB, CD, XD & XB product types |                                                                                                          |
| LCD display                                                 | CD, XD : Display with 4 lines of 18 characters                                                           |
| Programming method                                          | Function blocks / SCF (Grafset) or Ladder                                                                |
| Program size                                                | For CB, CD :<br>4 Ko : 64 macros max.<br>256 blocks max. per macro<br>180 typical blocks<br>For XB, XD : |

|                                            |                                                                                                                                      |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
|                                            | 8 Ko : 64 macro max.<br>256 blocks max. per macro<br>350 typical blocks<br>Or for CB, CD, XB, XD : 120 lines in Ladder               |
| Program memory                             | Flash EEPROM                                                                                                                         |
| Removable memory                           | EEPROM                                                                                                                               |
| Data memory                                | 368 bit/200 words                                                                                                                    |
| Back-up time in the event of power failure | Program and settings in the controller : 10 years<br>Program and settings in the plug-in memory : 10 years<br>Data memory : 10 years |
| Cycle time                                 | Function blocks : 6 →90 ms (typically 20 ms)<br>Ladder : typically 20 ms                                                             |
| Response time                              | Input acquisition time : 1 to 2 cycle times                                                                                          |
| Clock data retention                       | 10 years (lithium battery) at 25 °C                                                                                                  |
| Clock drift                                | Drift < 12 min/year (at 25 °C)<br>6 s/month (at 25 °C with user-definable correction of drift)                                       |
| Timer block accuracy                       | 1 % ± 2 cycle times                                                                                                                  |
| Start up time on power up                  | < 1,2 s                                                                                                                              |

#### Characteristics of products with AC power supplied

|                                                |                                                                                                                                               |                                                                                                                                              |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Supply                                         | 24 V AC<br>(88970..4)                                                                                                                         | 100 →240 V AC<br>(88970..3)                                                                                                                  |
| Nominal voltage                                | 24 V AC                                                                                                                                       | 100 →240 V AC                                                                                                                                |
| Operating limits                               | -15 % / +20 %<br>or 20.4 VAC→28.8 VAC                                                                                                         | -15 % / +10 %<br>or 85 VAC→264 VAC                                                                                                           |
| Supply frequency range                         | 50/60 Hz (+4 % / -6 %)<br>or 47→53 Hz/57 < 63 Hz                                                                                              | 50/60 Hz (+4 % / -6 %) or 47 →53 Hz/57 < 63 Hz                                                                                               |
| Immunity from micro power cuts                 | 10 ms (repetition 20 times)                                                                                                                   | 10 ms (repetition 20 times)                                                                                                                  |
| Max. absorbed power                            | CB12-CD12-XD10-XB10 : 4 VA<br>CB20-CD20 : 6 VA<br>XD10-XB10 with extension : 7.5 VA<br>XD26-XB26 : 7.5 VA<br>XD26-XB26 with extension : 10 VA | CB12-CD12-XD10-XB10 : 7 VA<br>CB20-CD20 : 11 VA<br>XD10-XB10 with extension : 12 VA<br>XD26-XB26 : 12 VA<br>XD26-XB26 with extension : 17 VA |
| Isolation voltage                              | 1780 V AC                                                                                                                                     | 1780 V AC                                                                                                                                    |
| Inputs                                         | 24 V AC<br>(88970..4)                                                                                                                         | 100 →240 V AC<br>(88970..3)                                                                                                                  |
| Input voltage                                  | 24 V AC (-15 % / +20 %)                                                                                                                       | 100 →240 V AC (-15 % / +10 %)                                                                                                                |
| Input current                                  | 4,4 mA @ 20,4 V AC<br>5,2 mA @ 24,0 V AC<br>6,3 mA @ 28,8 V AC                                                                                | 0,24 mA @ 85 V AC<br>0,75 mA @ 264 V AC                                                                                                      |
| Input impedance                                | 4.6 kΩ                                                                                                                                        | 350 kΩ                                                                                                                                       |
| Logic 1 voltage threshold                      | ≥ 14 V AC                                                                                                                                     | ≥ 79 V AC                                                                                                                                    |
| Making current at logic state 1                | >2 mA                                                                                                                                         | >0.17 mA                                                                                                                                     |
| Logic 0 voltage threshold                      | ≤ 5 V AC                                                                                                                                      | ≤ 20 V AC (≤ 28 V AC : XE10, XR06, XR10, XR14)                                                                                               |
| Release current at logic state 0               | <0.5 mA                                                                                                                                       | <0.5 mA                                                                                                                                      |
| Response time with LADDER programming          | 50 ms<br>State 0 →1 (50/60 Hz)                                                                                                                | 50 ms<br>State 0 < 1 (50/60 Hz)                                                                                                              |
| Response time with function blocks programming | Configurable in increments of 10 ms<br>50 ms min. up to 255 ms<br>State 0 →1 (50/60 Hz)                                                       | Configurable in increments of 10 ms<br>50 ms min. up to 255 ms<br>State 0 →1 (50/60 Hz)                                                      |
| Maximum counting frequency                     | In accordance with cycle time (Tc) and input response time (Tr) :<br>1/ ( (2 x Tc) + Tr)                                                      | In accordance with cycle time (Tc) and input response time (Tr) :<br>1/ ( (2 x Tc) + Tr)                                                     |
| Sensor type                                    | Contact or 3-wire PNP                                                                                                                         | Contact or 3-wire PNP                                                                                                                        |
| Input type                                     | Resistive                                                                                                                                     | Resistive                                                                                                                                    |
| Isolation between power supply and inputs      | None                                                                                                                                          | None                                                                                                                                         |
| Isolation between inputs                       | None                                                                                                                                          | None                                                                                                                                         |
| Protection against polarity inversions         | Yes                                                                                                                                           | Yes                                                                                                                                          |
| Status indicator                               | On LCD screen for CD and XD                                                                                                                   | On LCD screen for CD and XD                                                                                                                  |

#### Characteristics of relay outputs common to the entire range

|                                                    |                                                                                                                                                                      |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max. breaking voltage                              | 5 →30 V DC<br>24 →250 V AC                                                                                                                                           |
| Breaking current                                   | CB-CD-XB10-XD10-XR06-XR10 : 8 A<br>XD26-XB26 : 8 x 8 A relays, 2 x 5 A relays<br>XE10 : 4 x 5 A relays<br>XR14 : 4 x 8 A relays, 2 x 5 A relays                      |
| Electrical durability for 500 000 operating cycles | Usage category DC-12 : 24 V, 1.5 A<br>Usage category DC-13 : 24 V (L/R = 10 ms), 0.6 A<br>Usage category AC-12 : 230 V, 1.5 A<br>Usage category AC-15 : 230 V, 0.9 A |
| Max. Output Common Current                         | 12A for O8,O9,OA                                                                                                                                                     |
| Minimum switching capacity                         | 10 mA (at minimum voltage of 12 V)                                                                                                                                   |
| Minimum load                                       | 12 V, 10 mA                                                                                                                                                          |
| Maximum rate                                       | Off load : 10 Hz<br>At operating current : 0.1 Hz                                                                                                                    |
| Mechanical life                                    | 10,000,000 operations (cycles)                                                                                                                                       |
| Voltage for withstanding shocks                    | In accordance with IEC/EN 60947-1 and IEC/EN 60664-1 : 4 kV                                                                                                          |
| Off-cycle response time                            | Make 10 ms<br>Release 5 ms                                                                                                                                           |
| Built-in protections                               | Against short-circuits : None<br>Against overvoltages and overloads : None                                                                                           |
| Status indicator                                   | On LCD screen for CD and XD                                                                                                                                          |

#### Characteristics of product with DC power supplied

|                                                             |                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply                                                      | 12 V DC<br>(88970..5 & 8970814 & 88970840)                                                                                                                          | 24 V DC<br>(88970..1 et 88970..2)                                                                                                                                                                                                                                                                                |
| Nominal voltage                                             | 12 V DC                                                                                                                                                             | 24 V DC                                                                                                                                                                                                                                                                                                          |
| Operating limits                                            | -13 % / +20 %<br>or 10.4 V DC < 14.4 V DC (including ripple)                                                                                                        | -20 % / +25 %<br>or 19.2 V DC < 30 V DC (including ripple)                                                                                                                                                                                                                                                       |
| Immunity from micro power cuts                              | ≤ 1 ms (repetition 20 times)                                                                                                                                        | ≤ 1 ms (repetition 20 times)                                                                                                                                                                                                                                                                                     |
| Max. absorbed power                                         | CB12 with solid state outputs : 1.5 W<br>CD12 : 1.5 W<br>CD20 : 2.5 W<br>XD26-XB26 : 3 W<br>XD26-XB26 with extension : 5 W<br>XD26 with solid state outputs : 2.5 W | CB12-CD12-CD20 with solid state outputs - XD10-XB10 with solid state outputs : 3 W<br>XD10-XB10 with relay outputs : 4 W<br>XD26-XB26 with solid state outputs : 5 W<br>CB20-CD20 with relay outputs : 6 W<br>XD26 with relay outputs : 6 W<br>XD10-XB10 with extension : 8 W<br>XD26-XB26 with extension : 10 W |
| Protection against polarity inversions                      | Yes                                                                                                                                                                 | Yes                                                                                                                                                                                                                                                                                                              |
| Digital inputs (I1 to IA and IH to IY)                      | 12 V DC<br>(88970..5 & 88970814 & 88970840)                                                                                                                         | 24 V DC<br>(88970..1 and 88970..2)                                                                                                                                                                                                                                                                               |
| Input voltage                                               | 12 V DC (-13 % / +20 %)                                                                                                                                             | 24 V DC (-20 % / +25 %)                                                                                                                                                                                                                                                                                          |
| Input current                                               | 3,9 mA @ 10,44 V DC<br>4,4 mA @ 12,0 V DC<br>5,3 mA @ 14,4 VDC                                                                                                      | 2,6 mA @ 19,2 V DC<br>3,2 mA @ 24 V DC<br>4,0 mA @ 30,0 VDC                                                                                                                                                                                                                                                      |
| Input impedance                                             | 2.7 kΩ                                                                                                                                                              | 7.4 kΩ                                                                                                                                                                                                                                                                                                           |
| Logic 1 voltage threshold                                   | ≥ 7 V DC                                                                                                                                                            | ≥ 15 V DC                                                                                                                                                                                                                                                                                                        |
| Making current at logic state 1                             | ≥2 mA                                                                                                                                                               | ≥2.2 mA                                                                                                                                                                                                                                                                                                          |
| Logic 0 voltage threshold                                   | ≤ 3 V DC                                                                                                                                                            | ≤ 5 V DC                                                                                                                                                                                                                                                                                                         |
| Release current at logic state 0                            | <0.9 mA                                                                                                                                                             | <0.75 mA                                                                                                                                                                                                                                                                                                         |
| Response time                                               | 1 →2 cycle times + 6 ms                                                                                                                                             | 1 →2 cycle times + 6 ms                                                                                                                                                                                                                                                                                          |
| Maximum counting frequency                                  | I1 & I2 : FBD (Up to 6 k Hz) & Ladder (1 k Hz)<br>I3 to IA & IH to IY : in accordance with cycle time (Tc) and input response time (Tr) : 1/ ( (2 x Tc) + Tr)       | I1 & I2 : FBD (Up to 6 k Hz) & Ladder (1 k Hz)<br>I3 to IA & IH to IY : in accordance with cycle time (Tc) and input response time (Tr) : 1/ ( (2 x Tc) + Tr)                                                                                                                                                    |
| Sensor type                                                 | Contact or 3-wire PNP                                                                                                                                               | Contact or 3-wire PNP                                                                                                                                                                                                                                                                                            |
| Conforming to IEC/EN 61131-2                                | Type 1                                                                                                                                                              | Type 1                                                                                                                                                                                                                                                                                                           |
| Input type                                                  | Resistive                                                                                                                                                           | Resistive                                                                                                                                                                                                                                                                                                        |
| Isolation between power supply and inputs                   | None                                                                                                                                                                | None                                                                                                                                                                                                                                                                                                             |
| Isolation between inputs                                    | None                                                                                                                                                                | None                                                                                                                                                                                                                                                                                                             |
| Protection against polarity inversions                      | Yes                                                                                                                                                                 | Yes                                                                                                                                                                                                                                                                                                              |
| Status indicator                                            | On LCD screen for CD and XD                                                                                                                                         | On LCD screen for CD and XD                                                                                                                                                                                                                                                                                      |
| Analogue or digital inputs (IB to IG)                       | 12 V DC<br>(88970..5 & 88970814 & 88970840)                                                                                                                         | 24 V DC<br>(88970..1 and 88970..2)                                                                                                                                                                                                                                                                               |
| CB12-CD12-XD10-XB10                                         | 4 inputs IB →IE                                                                                                                                                     | 4 inputs IB →IE                                                                                                                                                                                                                                                                                                  |
| CB20-CD20-XB26-XD26                                         | 6 inputs IB →IG                                                                                                                                                     | 6 inputs IB →IG                                                                                                                                                                                                                                                                                                  |
| Inputs used as analogue input only in FBD                   |                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                  |
| Measurement range                                           | (0 →10 V) or (0 →V power supply)                                                                                                                                    | (0 →10 V) or (0 →V power supply)                                                                                                                                                                                                                                                                                 |
| Input impedance                                             | 14 kΩ                                                                                                                                                               | 12 kΩ                                                                                                                                                                                                                                                                                                            |
| Input voltage                                               | 14.4 V DC max                                                                                                                                                       | 30 V DC max                                                                                                                                                                                                                                                                                                      |
| Value of LSB                                                | 14 mV                                                                                                                                                               | 29 mV                                                                                                                                                                                                                                                                                                            |
| Input type                                                  | Common mode                                                                                                                                                         | Common mode                                                                                                                                                                                                                                                                                                      |
| Resolution                                                  | 10 bit at maximum input voltage                                                                                                                                     | 10 bit at maximum input voltage                                                                                                                                                                                                                                                                                  |
| Conversion time                                             | Controller cycle time                                                                                                                                               | Controller cycle time                                                                                                                                                                                                                                                                                            |
| Accuracy at 25 °C                                           | ± 5 %                                                                                                                                                               | ± 5 %                                                                                                                                                                                                                                                                                                            |
| Accuracy at 55 °C                                           | ± 6.2 %                                                                                                                                                             | ± 6.2 %                                                                                                                                                                                                                                                                                                          |
| Repeat accuracy at 55 °C                                    | ± 2 %                                                                                                                                                               | ± 2 %                                                                                                                                                                                                                                                                                                            |
| Isolation between analogue channel and power supply         | None                                                                                                                                                                | None                                                                                                                                                                                                                                                                                                             |
| Cable length                                                | 10 m maximum, with shielded cable (sensor not isolated)                                                                                                             | 10 m maximum, with shielded cable (sensor not isolated)                                                                                                                                                                                                                                                          |
| Protection against polarity inversions                      | Yes                                                                                                                                                                 | Yes                                                                                                                                                                                                                                                                                                              |
| Potentiometer control                                       | 2.2 kΩ/0.5 W (recommended)<br>10 kΩ max.                                                                                                                            | 2.2 kΩ/0.5 W (recommended)<br>10 kΩ max.                                                                                                                                                                                                                                                                         |
| Inputs used as digital inputs                               |                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                  |
| Input voltage                                               | 12 V DC (-13 % / +20 %)                                                                                                                                             | 24 V DC (-20 % / +25 %)                                                                                                                                                                                                                                                                                          |
| Input current                                               | 0,7 mA @ 10,44 VDC<br>0,9 mA @ 12,0 VDC<br>1,0 mA @ 14,4VDC                                                                                                         | 1,6 mA @ 19,2 VDC<br>2,0 mA @ 24,0 V DC<br>2,5 mA @ 30,0 VDC                                                                                                                                                                                                                                                     |
| Input impedance                                             | 14 kΩ                                                                                                                                                               | 12 kΩ                                                                                                                                                                                                                                                                                                            |
| Logic 1 voltage threshold                                   | ≥ 7 V DC                                                                                                                                                            | ≥ 15 VDC                                                                                                                                                                                                                                                                                                         |
| Making current at logic state 1                             | ≥0.5 mA                                                                                                                                                             | ≥1.2 mA                                                                                                                                                                                                                                                                                                          |
| Logic 0 voltage threshold                                   | ≤ 3 V DC                                                                                                                                                            | ≤ 5 V DC                                                                                                                                                                                                                                                                                                         |
| Release current at logic state 0                            | ≤0.2 mA                                                                                                                                                             | ≤0.5 mA                                                                                                                                                                                                                                                                                                          |
| Response time                                               | 1 →2 cycle times                                                                                                                                                    | 1 →2 cycle times                                                                                                                                                                                                                                                                                                 |
| Maximum counting frequency in FBD                           | In accordance with cycle time (Tc) and input response time (Tr) :<br>1/ ( (2 x Tc) + Tr)                                                                            | In accordance with cycle time (Tc) and input response time (Tr) :<br>1/ ( (2 x Tc) + Tr)                                                                                                                                                                                                                         |
| Sensor type                                                 | Contact or 3-wire PNP                                                                                                                                               | Contact or 3-wire PNP                                                                                                                                                                                                                                                                                            |
| Conforming to IEC/EN 61131-2                                | Type 1                                                                                                                                                              | Type 1                                                                                                                                                                                                                                                                                                           |
| Input type                                                  | Resistive                                                                                                                                                           | Resistive                                                                                                                                                                                                                                                                                                        |
| Isolation between power supply and inputs                   | None                                                                                                                                                                | None                                                                                                                                                                                                                                                                                                             |
| Isolation between inputs                                    | None                                                                                                                                                                | None                                                                                                                                                                                                                                                                                                             |
| Protection against polarity inversions                      | Yes                                                                                                                                                                 | Yes                                                                                                                                                                                                                                                                                                              |
| Status indicator                                            | On LCD screen for CD and XD                                                                                                                                         | On LCD screen for CD and XD                                                                                                                                                                                                                                                                                      |
| Characteristics of relay outputs common to the entire range |                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                  |
| Max. breaking voltage                                       | 5 →30 V DC<br>24 →250 V AC                                                                                                                                          |                                                                                                                                                                                                                                                                                                                  |
| Max. Output Common Current                                  | 12A (10A UL) for O8,O9,OA                                                                                                                                           |                                                                                                                                                                                                                                                                                                                  |

|                                                    |                                                                                                                                                                                                                               |                                                                                                                                                                                                                               |
|----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Breaking current                                   | CB-CD-XD10-XB10-XR06-XR10 : 8 A<br>XD26-XB26 : 8 x 8 A relays, 2 x 5 A relays<br>XE10 : 4 x 5 A relays<br>XR14 : 4 x 8 A relays, 2 x 5 A relays                                                                               |                                                                                                                                                                                                                               |
| Electrical durability for 500 000 operating cycles | Usage category DC-12 : 24 V, 1.5 A<br>Usage category DC-13 : 24 V (L/R = 10 ms), 0.6 A<br>Usage category AC-12 : 230 V, 1.5 A<br>Usage category AC-15 : 230 V, 0.9 A                                                          |                                                                                                                                                                                                                               |
| Minimum switching capacity                         | 10 mA (at minimum voltage of 12 V)                                                                                                                                                                                            |                                                                                                                                                                                                                               |
| Minimum load                                       | 12 V, 10 mA                                                                                                                                                                                                                   |                                                                                                                                                                                                                               |
| Maximum rate                                       | Off load : 10 Hz<br>At operating current : 0.1 Hz                                                                                                                                                                             |                                                                                                                                                                                                                               |
| Mechanical life                                    | 10,000,000 operations (cycles)                                                                                                                                                                                                |                                                                                                                                                                                                                               |
| Voltage for withstanding shocks                    | In accordance with IEC/EN 60947-1 and IEC/EN 60664-1 : 4 kV                                                                                                                                                                   |                                                                                                                                                                                                                               |
| Off-cycle response time                            | Make 10 ms<br>Release 5 ms                                                                                                                                                                                                    |                                                                                                                                                                                                                               |
| Built-in protections                               | Against short-circuits : None<br>Against overvoltages and overloads : None                                                                                                                                                    |                                                                                                                                                                                                                               |
| Status indicator                                   | On LCD screen for CD and XD                                                                                                                                                                                                   |                                                                                                                                                                                                                               |
| Digital / PWM solid state output                   | 12 V DC<br>(88970814 & 88970840)                                                                                                                                                                                              | 24 V DC<br>(88970..2)                                                                                                                                                                                                         |
| PWM solid state output*                            | CB12 : O4<br>XD26 : O4 →O7                                                                                                                                                                                                    | CD12-XD10-XB10 : O4<br>CD20-XD26-XB26 : O4 →O7                                                                                                                                                                                |
| * Only available with "FBD" programming language   | * Only available with "FBD" programming language                                                                                                                                                                              |                                                                                                                                                                                                                               |
| Breaking voltage                                   | 10.4 →30 VDC                                                                                                                                                                                                                  | 19.2 →30 VDC                                                                                                                                                                                                                  |
| Nominal voltage                                    | 12-24 V DC                                                                                                                                                                                                                    | 24 V DC                                                                                                                                                                                                                       |
| Nominal current                                    | 0.5 A                                                                                                                                                                                                                         | 0.5 A                                                                                                                                                                                                                         |
| Max. breaking current                              | 0,625 A                                                                                                                                                                                                                       | 0,625 A                                                                                                                                                                                                                       |
| Voltage drop                                       | ≤ 2 V for I = 0.5 A (at state 1)                                                                                                                                                                                              | ≤ 2 V for I = 0.5 A (at state 1)                                                                                                                                                                                              |
| Response time                                      | Make ≤ 1 ms<br>Release ≤ 1 ms                                                                                                                                                                                                 | Make ≤ 1 ms<br>Release ≤ 1 ms                                                                                                                                                                                                 |
| Operating frequency                                | 1 Maximum on inductive load                                                                                                                                                                                                   | 1 Maximum on inductive load                                                                                                                                                                                                   |
| Built-in protections                               | Against overloads and short-circuits : Yes<br>Against overvoltages (*) : Yes<br>Against inversions of power supply : Yes<br>(*) In the absence of a volt-free contact between the output of the logic controller and the load | Against overloads and short-circuits : Yes<br>Against overvoltages (*) : Yes<br>Against inversions of power supply : Yes<br>(*) In the absence of a volt-free contact between the output of the logic controller and the load |
| Min. load                                          | 1 mA                                                                                                                                                                                                                          | 1 mA                                                                                                                                                                                                                          |
| Maximum incandescent load                          | 0,2 A / 12 V DC<br>0,1 A / 24 V DC                                                                                                                                                                                            | 0,1 A / 24 V DC                                                                                                                                                                                                               |
| Galvanic isolation                                 | No                                                                                                                                                                                                                            | No                                                                                                                                                                                                                            |
| PWM frequency                                      | 14.11 Hz<br>56.45 Hz<br>112.90 Hz<br>225.80 Hz<br>451.59 Hz<br>1806.37 Hz                                                                                                                                                     | 14.11 Hz<br>56.45 Hz<br>112.90 Hz<br>225.80 Hz<br>451.59 Hz<br>1806.37 Hz                                                                                                                                                     |
| PWM cyclic ratio                                   | 0 →100 % (256 steps for CD, XD and 1024 for XA)                                                                                                                                                                               | 0 →100 % (256 steps for CD, XD and 1024 for XA)                                                                                                                                                                               |
| PWM accuracy at 120 Hz                             | < 5 % (20 % →80 %) load at 10 mA                                                                                                                                                                                              | < 5 % (20 % →80 %) load at 10 mA                                                                                                                                                                                              |
| Max. Breaking current PWM                          | 50 mA                                                                                                                                                                                                                         | 50 mA                                                                                                                                                                                                                         |
| Max. cable length PWM                              | 20 m                                                                                                                                                                                                                          | 20 m                                                                                                                                                                                                                          |
| PWM accuracy at 500 Hz                             | < 10 % (20 % →80 %) load at 10 mA                                                                                                                                                                                             | < 10 % (20 % →80 %) load at 10 mA                                                                                                                                                                                             |
| Status indicator                                   | On LCD screen for CD and XD                                                                                                                                                                                                   | On LCD screen for CD and XD                                                                                                                                                                                                   |

## Accessories


| Type    | Description                                                                      | Code     |
|---------|----------------------------------------------------------------------------------|----------|
| M3 Soft | Multilingual programming software containing specific library functions (CD-ROM) | 88970111 |
| PA      | EEPROM memory cartridge                                                          | 88970108 |
| PA      | 3 m serial link cable : PC →Millenium 3                                          | 88970102 |
| PA      | USB cable 3 m : PC →Millenium 3                                                  | 88970109 |
| PA      | Millenium 3 interface →Bluetooth® (class A 10 m)                                 | 88970104 |

## Comments

\* to be marketed 1<sup>st</sup> quarter 2006

## Dimensions (mm)

### CD20



# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct    +86 (21) 6401-6692  
Email     amall@ameya360.com  
QQ        800077892  
Skype     ameyasales1 ameyasales2

➤ Customer Service :

Email     service@ameya360.com

➤ Partnership :

Tel        +86 (21) 64016692-8333  
Email     mkt@ameya360.com