



### FEATURES

- Efficiency up to 81%
- SIP Package with Industry Standard Pinout
- Package Dimension:  
5V&12V Models:  
19.5 x 10.2 x 6.1 mm (0.77"x 0.4"x 0.24")  
15V&24V Models  
19.5 x 10.2 x 7.1 mm (0.77"x 0.4"x 0.28")
- Isolation Voltage 1000 VDC
- OperatingTemp. Range -40°C to +85°C
- Lead free , RoSH Compliant
- Single and Dual Outputs
- >2 MHours MTBF
- 3 Years Product Warranty

The PB01S/D series are miniature, SIP Package, isolated 1W DC/DC converters with 1,000VDC isolation. It offers single and dual output models, short circuit protection, and allows a wide operating temperature range of -40°C to +85°C. These isolated DC/DC converters are the latest offering from a world leader in power systems technology and manufacturing — Delta Electronics, Inc

### Model List

| Model Number | Input Voltage (Range) | Output Voltage | Output Current |      | Input Current |          | Load Regulation | Max capacitive Load | Efficiency (typ.) |
|--------------|-----------------------|----------------|----------------|------|---------------|----------|-----------------|---------------------|-------------------|
|              |                       |                | Max.           | Min. | @Max. Load    | @No Load |                 |                     |                   |
|              |                       |                | mA             | mA   | mA(typ.)      | mA(typ.) |                 | uF                  | %                 |
| PB01S0503A   | 5<br>(4.5 ~ 5.5)      | 3.3            | 260            | 5    | 235           | 30       | 10              | 220                 | 73                |
| PB01S0505A   |                       | 5              | 200            | 4    | 281           |          | 10              |                     | 71                |
| PB01S0509A   |                       | 9              | 110            | 2    | 260           |          | 8               |                     | 76                |
| PB01S0512A   |                       | 12             | 84             | 1.5  | 258           |          | 7               |                     | 78                |
| PB01S0515A   |                       | 15             | 67             | 1    | 258           |          | 7               | 100*                | 78                |
| PB01D0505A   |                       | ±5             | ±100           | ±2   | 278           |          | 10              |                     | 72                |
| PB01D0509A   |                       | ±9             | ±56            | ±1   | 262           |          | 8               |                     | 77                |
| PB01D0512A   |                       | ±12            | ±42            | ±0.8 | 258           |          | 7               |                     | 78                |
| PB01D0515A   |                       | ±15            | ±34            | ±0.7 | 258           |          | 7               |                     | 79                |
| PB01S1203A   | 12<br>(10.8 ~ 13.2)   | 3.3            | 260            | 5    | 96            | 12       | 8               | 220                 | 74                |
| PB01S1205A   |                       | 5              | 200            | 4    | 114           |          | 8               |                     | 73                |
| PB01S1209A   |                       | 9              | 110            | 2    | 106           |          | 5               |                     | 78                |
| PB01S1212A   |                       | 12             | 84             | 1.5  | 105           |          | 5               | 100*                | 80                |
| PB01S1215A   |                       | 15             | 67             | 1    | 104           |          | 5               |                     | 80                |
| PB01D1205A   |                       | ±5             | ±100           | ±2   | 113           |          | 8               |                     | 74                |
| PB01D1209A   |                       | ±9             | ±56            | ±1   | 106           |          | 5               |                     | 79                |
| PB01D1212A   |                       | ±12            | ±42            | ±0.8 | 104           |          | 5               |                     | 81                |
| PB01D1215A   |                       | ±15            | ±34            | ±0.7 | 105           |          | 5               |                     | 81                |
| PB01S1505A   | 15<br>(13.5 ~ 16.5)   | 5              | 200            | 4    | 93            | 11       | 8               | 220                 | 72                |
| PB01S1512A   |                       | 12             | 84             | 1.5  | 85            |          | 5               |                     | 79                |
| PB01S1515A   |                       | 15             | 67             | 1    | 85            |          | 5               |                     | 79                |
| PB01D1505A   |                       | ±5             | ±100           | ±2   | 93            |          | 8               | 100*                | 72                |
| PB01D1512A   |                       | ±12            | ±42            | ±0.8 | 85            |          | 5               |                     | 80                |
| PB01D1515A   |                       | ±15            | ±34            | ±0.7 | 85            |          | 5               |                     | 80                |
| PB01S2403A   | 24<br>(21.6 ~ 26.4)   | 3.3            | 260            | 5    | 49            | 7        | 8               | 220                 | 73                |
| PB01S2405A   |                       | 5              | 200            | 4    | 59            |          | 8               |                     | 71                |
| PB01S2409A   |                       | 9              | 110            | 2    | 54            |          | 5               |                     | 76                |

## Model List

| Model Number | Input Voltage (Range) | Output Voltage | Output Current |      | Input Current |          | Load Regulation | Maxcapacitive Load | Efficiency (typ.) |
|--------------|-----------------------|----------------|----------------|------|---------------|----------|-----------------|--------------------|-------------------|
|              |                       |                | Max.           | Min. | @Max. Load    | @No Load |                 |                    | @Max. Load        |
|              | VDC                   | VDC            | mA             | mA   | mA(typ.)      | mA(typ.) | % (max.)        | uF                 | %                 |
| PB01S2412A   | 24<br>(21.6 ~ 26.4)   | 12             | 84             | 1.5  | 54            | 7        | 5               | 100*               | 78                |
| PB01S2415A   |                       | 15             | 67             | 1    | 53            |          | 5               |                    | 79                |
| PB01D2405A   |                       | ±5             | ±100           | ±2   | 58            |          | 8               |                    | 72                |
| PB01D2409A   |                       | ±9             | ±56            | ±1   | 55            |          | 5               |                    | 76                |
| PB01D2412A   |                       | ±12            | ±42            | ±0.8 | 53            |          | 5               |                    | 79                |
| PB01D2415A   |                       | ±15            | ±34            | ±0.7 | 53            |          | 5               |                    | 80                |

\* For each output

## Input Characteristics

| Parameter                         | Model            | Min.               | Typ. | Max. | Unit |
|-----------------------------------|------------------|--------------------|------|------|------|
| Input Voltage Range               | 5V Input Models  | 4.5                | 5    | 5.5  | VDC  |
|                                   | 12V Input Models | 10.8               | 12   | 13.2 |      |
|                                   | 15V Input Models | 13.5               | 15   | 16.5 |      |
|                                   | 24V Input Models | 21.6               | 24   | 26.4 |      |
| Input Surge Voltage (1 sec. max.) | 5V Input Models  | -0.7               | ---  | 9    |      |
|                                   | 12V Input Models | -0.7               | ---  | 18   |      |
|                                   | 15V Input Models | -0.7               | ---  | 18   |      |
|                                   | 24V Input Models | -0.7               | ---  | 30   |      |
| Reverse Polarity Input Current    | All Models       | ---                | ---  | 0.3  | A    |
| Input Filter                      |                  | Internal Capacitor |      |      |      |
| Internal Power Dissipation        |                  | ---                | ---  | 450  | mW   |

## Output Characteristics

| Parameter                | Conditions                  | Min.                      | Typ.  | Max.  | Unit              |
|--------------------------|-----------------------------|---------------------------|-------|-------|-------------------|
| Output Voltage Accuracy  |                             | ---                       | ±1.0  | ±3.0  | %                 |
| Output Voltage Balance   | Dual Output, Balanced Loads | ---                       | ±0.1  | ±1.0  | %                 |
| Line Regulation          | For Vin Change of 1%        | ---                       | ±1.2  | ±1.5  | %                 |
| Load Regulation          | Io=20% to 100%              | See Model Selection Guide |       |       |                   |
| Ripple & Noise (20MHz)   |                             | ---                       | 50    | 75    | mV <sub>P-P</sub> |
| Ripple & Noise (20MHz)   | Over Line, Load & Temp.     | ---                       | ---   | 150   | mV <sub>P-P</sub> |
| Ripple & Noise (20MHz)   |                             | ---                       | ---   | 15    | mV rms            |
| Temperature Coefficient  |                             | ---                       | ±0.01 | ±0.02 | %/°C              |
| Short Circuit Protection |                             | 0.5 Second Max.           |       |       |                   |

## General Characteristics

| Parameter                     | Conditions                        | Min.      | Typ. | Max. | Unit  |
|-------------------------------|-----------------------------------|-----------|------|------|-------|
| I/O Isolation Voltage (rated) | 60 Seconds                        | 1000      | ---  | ---  | VDC   |
| I/O Isolation Resistance      | 500 VDC                           | 1000      | ---  | ---  | MΩ    |
| I/O Isolation Capacitance     | 100KHz, 1V                        | ---       | 60   | 100  | pF    |
| Switching Frequency           |                                   | 70        | 100  | 120  | KHz   |
| MTBF (calculated)             | MIL-HDBK-217F@25°C, Ground Benign | 2,000,000 | ---  | ---  | Hours |


## Recommended Input Fuse

| 5V Input Models      | 12V Input Models     | 15V Input Models     | 24V Input Models     |
|----------------------|----------------------|----------------------|----------------------|
| 500mA Slow-Blow Type | 200mA Slow-Blow Type | 150mA Slow-Blow Type | 100mA Slow-Blow Type |

## Environmental Specifications

| Parameter                                     | Conditions          | Min. | Max. | Unit     |
|-----------------------------------------------|---------------------|------|------|----------|
| Operating Temperature Range (with Derating)   | Ambient             | -40  | +85  | °C       |
| Case Temperature                              |                     | ---  | +90  | °C       |
| Storage Temperature Range                     |                     | -50  | +125 | °C       |
| Humidity (non condensing)                     |                     | ---  | 95   | % rel. H |
| Cooling                                       | Free-Air convection |      |      |          |
| Lead Temperature (1.5mm from case for 10Sec.) |                     | ---  | 260  | °C       |

## Power Derating Curve




## Notes

- 1 Specifications typical at  $T_a = +25^\circ\text{C}$ , resistive load, nominal input voltage and rated output current unless otherwise noted.
- 2 Ripple & Noise measurement bandwidth is 0-20MHz.
- 3 These power converters require a minimum output loading to maintain specified regulation, operation under no-load conditions will not damage these modules; however they may not meet all specifications listed.
- 4 All DC/DC converters should be externally fused at the front end for protection.
- 5 Specifications subject to change without notice.

## Mechanical Drawing

### Mechanical Dimensions



### Pin Connections

| Pin | Single Output | Dual Output |
|-----|---------------|-------------|
| 1   | +Vin          | +Vin        |
| 2   | -Vin          | -Vin        |
| 4   | -Vout         | -Vout       |
| 5   | No Pin        | Common      |
| 6   | +Vout         | +Vout       |

5V&12V Input:

T: 6.1mm(0.24 inch)

15V&24V Input:

T: 7.1mm(0.28 inch) for Models

► All dimensions in mm (inches)

► Tolerance:  $X.X \pm 0.25$  ( $X.XX \pm 0.01$ )  
 $X.XX \pm 0.13$  ( $X.XXX \pm 0.005$ )

► Pins  $\pm 0.05$  ( $\pm 0.002$ )

## Physical Outline

Case Size (5V&12V Input) : 19.5x6.1x10.2mm (0.77x0.24x0.40 Inches)

Case Size : 19.5x7.1x10.2mm (0.77x0.28x0.40 Inches)  
 (15V&24V Input)

Case Material : Non-Conductive Black Plastic  
 (flammability to UL 94V-0 rated)

Weight (5V&12V Input) : 2.2g

Weight (15V&24V Input) : 2.6g

| Part Numbering System |               |       |                   |               |                |                    |
|-----------------------|---------------|-------|-------------------|---------------|----------------|--------------------|
| P                     | B             | 01    | S                 | 05            | 05             | A                  |
| Form factor           | Family series | Watt  | Number of Outputs | Input Voltage | Output Voltage | Option Code        |
| D-DIP                 | A~Z           | 01:1W | S - Single        | 03:3.3V       | 03:3.3V        | A - Std. Functions |
| P-SIP                 |               | 02:2W | D- Dual           | 05: 5V        | 05: 5V         |                    |
| S-SMD                 |               | 03:3W |                   | 12:12V        | 12:12V         |                    |
|                       |               | 04:4W |                   | 24: 24V       | 15: 15V        |                    |
|                       |               | 06:6W |                   | 48:48V        | 24: 24V        |                    |

## WARRANTY

Delta offers a three(3) years limited warranty. Complete warranty information is listed on our web site or is available upon request from Delta.

Information furnished by Delta is believed to be accurate and reliable. However, no responsibility is assumed by Delta for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Delta. Delta reserves the right to revise these specifications at any time, without notice.

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)