

## Platinum Resistance Temperature Detector


## PCB 1325 (0805)

This platinum temperature sensor on a printed circuit board has been specially designed for use in calorimetry. When designing these sensors, the stringent requirements of this sector with regard to precision, long-term stability, cost minimisation as well as the option for fully automatic further processing were of prime concern.

The temperature sensor in an SMD model forms the measurement active element on a PCB. The chip is connected with terminal faces with a thin conductive path in order to reduce heat dissipation and to prevent corruption of the measuring results. As a cable set sensor, it is suitable for a wide range of applications within a temperature range of 0°C to 150°C.

Nominal Resistance $R_0$	Tolerance DIN EN 60751 1996-07	Tolerance DIN EN 60751 2009-05	Ordner No.	Dimensions in mm			FC Type
				L1	L2 +1 -2	B -0,2	
1000	B	F 0.3	30 201 102	13	15	2,5	0805
500	B	F 0.3	30 201 103	13	15	2,5	0805

Specification	DIN EN 60751
Tolerance classes	Class B
Temperature range	0°C to 150°C
Temperature coefficient	TC = 3850 ppm/K
Long-term stability	≤ 0.1 K after 1000 h at 150°C energized with: Pt 1000: 0.3 mA Pt 500: 0.7 mA
Measuring current	1000Ω: 0.1 to 0.3mA 500Ω: 0.1 to 0.7mA
Self-heating	0.15 K/mW in ice water
Temperature change resistance	≤ 0.1 K after 1000 change 0°C/150°C in air
Contact	Cu connection pad with chem. Sn surface
Soldering	1) Chip is soldered lead free 2) Connection pads are ready for lead free soldering
Ambient conditions	Use unprotected only in dry environments
Response time	water (v= 0.4m/s): $t_{0,5} = 0.05s$ $t_{0,9} = 0.10s$ air (v=2m/s): $t_{0,5} = 1.5s$ $t_{0,9} = 5.0s$
Packaging	Supplied in plastic container
Storage life	12 months
Note	Other tolerances and values of resistance are available on request.



We reserve the right to make alterations and technical data printed. All technical data serves as a guideline and does not guarantee particular properties to any products.

## Heraeus Sensor Technology USA

1901 Route 130  
North Brunswick, NJ 08902  
Phone 732-940-4400 Fax 732-940-4445  
Email [info.hst-us@heraeus.com](mailto:info.hst-us@heraeus.com)  
[www.hst-us.com](http://www.hst-us.com)

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email        amall@ameya360.com  
  
QQ            800077892  
  
Skype        ameyasales1 ameyasales2

➤ Customer Service :

Email        service@ameya360.com

➤ Partnership :

Tel            +86 (21) 64016692-8333  
  
Email        mkt@ameya360.com