

Touch panel - TP 06S - 2985178

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 14.5 cm/5.7" C-STN-Display (Resistive industrial touch screen), 320 x 240 Pixel (QVGA), 125 colors, ARM9™, 200 MHz, 2x USB Host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Windows CE 5.0 and User software: Visu+ / AX OPC Server. (Bus system: without)

Product Features

- Short startup time
- Easy installation, low installation depth, and compact design
- Display available in sizes from 8.9 cm (3.8") to 38.1 cm (15")
- Visu+ RT and AX OPC server integrated as standard in all devices

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	1633.8 g
Custom tariff number	84714100
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

External dimension, width	203 mm
External dimension, height	147 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	195 mm
Installation dimension, height	139 mm
Installation dimension, depth	54 mm

Display

Display	14.5 cm/5.7" C-STN
---------	--------------------

Touch panel - TP 06S - 2985178

Technical data

Display

Screen resolution	320 x 240 Pixel(s) (QVGA)
Backlighting	CCFL
Touch technology	Resistive industrial touch screen
Colors	125 colors

Computer data

Processor	ARM9™, 200 MHz
Operating systems	Windows® CE 5.0
User software	Visu+
	AX OPC Server
RAM	64 MB SDRAM
Mass storage	32 MByte flash memory
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x USB Host 2.0
Bus system	without

General

Mounting type	Front installation
---------------	--------------------

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Device supply

Power supply unit	24 V DC ±20 %
-------------------	---------------

Standards and Regulations

Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Classifications

eCl@ss

eCl@ss 4.0	27330202
eCl@ss 4.1	27330202

Touch panel - TP 06S - 2985178

Classifications

eCl@ss

eCl@ss 5.0	27242215
eCl@ss 5.1	27242301
eCl@ss 6.0	27242301
eCl@ss 7.0	27242301
eCl@ss 8.0	27242302

ETIM

ETIM 2.0	EC001426
ETIM 3.0	EC001426
ETIM 4.0	EC001426
ETIM 5.0	EC001412

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43211903
UNSPSC 13.2	43201404

Approvals

Approvals


Approvals

UL Listed / cUL Listed / LR / GL / BV / DNV / ABS / GL-SW / EAC / LR / ABS / RINA / GL / cULus Listed

Ex Approvals



Approvals submitted

Approval details

UL Listed 

Touch panel - TP 06S - 2985178

Approvals

cUL Listed 
LR
GL
BV
DNV
ABS
GL-SW
EAC
LR
ABS
RINA
GL
cULus Listed 

Accessories

Accessories

Battery module

Touch panel - TP 06S - 2985178

Accessories

Battery / accumulator - HMI BATTERY - 2701383

Lithium battery



Mounting material

Mounting material - HMI WALL MOUNTING KIT - 2701380



HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.

Mounting material - HMI SCB MOUNTING KIT 4 - 2701384



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

Mounting material - HMI SCB MOUNTING KIT 6 - 2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

Mounting material - HMI SCB MOUNTING KIT 8 - 2701387



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

Touch panel - TP 06S - 2985178

Accessories

Operating stylus

Touch pen - TOUCH PEN - 2701379



Touch pen for HMIs, silver coated. Delivery includes self-adhesive pen holder.

Protective foil

Protective foil - 5,7" DISPLAY PROTECTIVE FOIL - 2701371



Protective film set comprising 10 pieces of film for a 5.7" display. Including a squeegee to apply film and instructions.

Storage medium

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com