

LMax SMD Power Inductor

LMXN Series – Non-Shielded Style B



FEATURES

- Miniature surface mount design
- High power, High saturation inductors
- Very low resistance
- Maximum power density
- Ideal inductors for DC-DC converters
- Available on tape and reel for auto surface mounting

APPLICATIONS

- Notebook Computers
- Handheld Communications
- LCD Televisions
- Power Supply For VTRs
- DC/DC Converters, etc.

CHARACTERISTICS




- Saturation Rated Current: The current when the inductance becomes 30% lower than its initial value. (Ta=25°C)
- Operating temperature range: -40 ~ 85°C

INDUCTANCE AND RATED CURRENT RANGES

- 0705 0.47μH ~ 22.0μH 7.7 ~ 0.70A
- 0906 0.56μH ~ 100μH 7.7 ~ 0.53A
- 1310 0.47μH ~ 100μH 11.4 ~ 0.95A
- 1913 0.47μH ~ 100μH 25.1 ~ 1.80A
- 2216 0.78μH ~ 470μH 30.0 ~ 0.8A
- Electrical specifications at 25°C



DIMENSIONS



mm (inches)

Type	A max.	B max.	C max.	D	E	H	I	J
0705	7.50 (0.295)	5.20 (0.205)	3.20 (0.126)	4.60 (0.181)	2.50 (0.098)	4.00 (0.157)	2.00 (0.079)	4.00 (0.157)
0906	8.89 (0.350)	6.40 (0.252)	5.00 (0.197)	5.84 (0.230)	2.60 (0.103)	4.06 (0.160)	2.00 (0.079)	5.08 (0.200)
1310	13.20 (0.560)	9.90 (0.390)	6.35 (0.250)	9.50 (0.374)	4.50 (0.177)	6.50 (0.256)	2.30 (0.091)	9.00 (0.344)
1913	19.40 (0.764)	13.30 (0.524)	6.80 (0.268)	12.7 (0.500)	6.60 (0.260)	8.00 (0.315)	3.80 (0.150)	11.7 (0.460)
2216	22.35 (0.880)	16.26 (0.604)	8.00 (0.315)	16.0 (0.630)	8.00 (0.315)	8.64 (0.340)	4.30 (0.169)	14.35 (0.565)

HOW TO ORDER

LM	XN	0705	M	R04	B	T	A	S
Family	Series	Size	Tolerance	Inductance	Style	Termination	Special	Packaging
LM = Power Inductor	XN = Non-Shielded	0705 = 7x5xh (h = see catalog)	M = ±20% P = +40% -20%	R04 = 0.039μH R39 = 0.390μH 3R9 = 3.900μH 390 = 39.00μH 391 = 390.0μH 392 = 3900μH		T = Sn Plate	A = Standard	S = 13" Reel



LMax SMD Power Inductor



LMXN Series – Non-Shielded Style B

ELECTRICAL CHARACTERISTICS

0705/0906/1310/1913/2216

Codes	L (μ H)	Tolerance			Test Condition	DCR (Ω) max.					I sat (A) max*				
		705	0906 2216	1310 1913		0705	0906	1310	1913	2216	0705	0906	1310	1913	2216
R47	0.47	P	–	P	100KHz, 0.1V	0.025	–	0.005	0.003	–	7.7	–	11.4	25.1	–
R56	0.56	–	M	–	100KHz, 0.1V	–	0.010	–	–	–	–	7.7	–	–	–
R78	0.78	–	M	–	100KHz, 0.1V	–	–	–	–	0.003	–	–	–	–	30
1R0	1.0	M	–	P	100KHz, 0.1V	0.050	–	0.006	0.004	–	2.9	–	9.9	15.3	–
1R5	1.5	M	M	P	100KHz, 0.1V	0.050	–	0.008	0.006	0.004	2.6	–	7.9	12	25
2R2	2.2	M	M	M	100KHz, 0.1V	0.070	0.035	0.011	0.008	0.006	2.3	3.5	6.1	10.2	20
3R3	3.3	M	M	M	100KHz, 0.1V	0.080	0.040	0.014	0.009	0.009	2	3	5.1	9.3	17
3R9	3.9	–	M	–	100KHz, 0.1V	–	–	–	–	0.010	–	–	–	–	15
4R7	4.7	M	M	M	100KHz, 0.1V	0.090	0.054	0.018	0.012	0.014	1.5	2.6	4.2	7.7	13
6R0	6.0	–	M	–	100KHz, 0.1V	–	–	–	–	0.017	–	–	–	–	12
6R8	6.8	M	M	M	100KHz, 0.1V	0.130	0.08	0.027	0.019	–	1.2	2.2	3.6	6.2	–
7R8	7.8	–	M	–	100KHz, 0.1V	–	–	–	–	0.018	–	–	–	–	11
100	10	M	M	M	100KHz, 0.1V	0.160	0.111	0.038	0.027	0.026	1.1	1.9	3.3	5.2	10
150	15	M	M	M	100KHz, 0.1V	0.230	0.170	0.045	0.032	0.032	0.9	1.5	2.4	4.3	8
220	22	M	M	M	100KHz, 0.1V	0.370	0.250	0.070	0.050	0.043	0.7	1.2	2	3.7	7
330	33	–	M	M	100KHz, 0.1V	–	0.350	0.100	0.069	0.066	–	0.99	1.7	3	6
470	47	–	M	M	100KHz, 0.1V	–	0.470	0.150	0.109	0.096	–	0.87	1.4	2.4	5
680	68	–	M	M	100KHz, 0.1V	–	0.730	0.220	0.156	0.115	–	0.68	1.2	2	4
101	100	–	M	M	100KHz, 0.1V	–	1.110	0.280	0.206	0.165	–	0.53	0.95	1.8	3
221	220	–	M	–	100KHz, 0.1V	–	–	–	–	0.396	–	–	–	–	2.4
331	330	–	M	–	100KHz, 0.1V	–	–	–	–	0.588	–	–	–	–	1
471	470	–	M	–	100KHz, 0.1V	–	–	–	–	0.950	–	–	–	–	0.8

*Saturation Current: The current when the inductance becomes 30% lower than its initial value. (Ta=25°C)

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com