









RoHS Compliant



Dimensions (In.)



SPECIFICATIONS

- Impedance variation: $\pm 10\%$ @ 1KHz
- DC Resistance tolerance: $\pm 15\%$
- Insulation: $>10M\Omega$ @ 100VDC
- Core type / size: EI-14
- Breakdown voltage: 100VAC Hipot for 1 minute
- Waxing: Vacuum treatment can be water washed with water temperature less than 20°C
- Max output: 75mW
- Freq. response: $\pm 3\text{dB}$, 300Hz-3.5 KHz @ 1KHZ 0dB
- Can be water washed with water temperature less than 20°C
- RoHS Compliant

Mouser Stock No.	Impedance		Resistance	
	PRI	SEC	PRI	SEC
42XL001-RC	500 Ω	8 Ω	35 Ω	1 Ω
42XL002-RC	10K Ω	2K Ω	580 Ω	200 Ω
42XL003-RC	1.2K Ω	8 Ω	80 Ω	1 Ω
42XL009-RC	500 Ω	500 Ω	40 Ω	38 Ω
42XL016-RC	600 Ω	600 Ω	65 Ω	55 Ω
42XL031-RC	600 Ω	100 Ω	74 Ω	28 Ω

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com