

# MMBD2835LT1G, MMBD2836LT1G, SMMBD2835LT1G

## Monolithic Dual Switching Diodes

### Features

- AEC-Q101 Qualified and PPAP Capable
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant\*

### MAXIMUM RATINGS (EACH DIODE)

| Rating   | Symbol | Value    | Unit  |
|--|--------|----------|-------|
| Reverse Voltage<br>MMBD2835LT1G, SMMBD2835LT1G<br>MMBD2836LT1G | $V_R$  | 35<br>75 | Vdc   |
| Forward Current  | $I_F$  | 100      | mA dc |

### THERMAL CHARACTERISTICS

|  |                 |                |                            |
|--|-----------------|----------------|----------------------------|
| Total Device Dissipation FR-5 Board<br>(Note 1)<br>$T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$         | $P_D$           | 225<br>1.8     | mW<br>mW/ $^\circ\text{C}$ |
| Thermal Resistance, Junction-to-Ambient  | $R_{\theta JA}$ | 556            | $^\circ\text{C/W}$         |
| Total Device Dissipation Alumina<br>Substrate, (Note 2)<br>$T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$           | 300<br>2.4     | mW<br>mW/ $^\circ\text{C}$ |
| Thermal Resistance, Junction-to-Ambient  | $R_{\theta JA}$ | 417            | $^\circ\text{C/W}$         |
| Junction and Storage Temperature   | $T_J, T_{stg}$  | -55 to<br>+150 | $^\circ\text{C}$           |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1. FR-5 =  $1.0 \times 0.75 \times 0.062$  in.
2. Alumina =  $0.4 \times 0.3 \times 0.024$  in. 99.5% alumina.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.




ON Semiconductor®


<http://onsemi.com>



SOT-23 (TO-236AB)  
CASE 318-08  
STYLE 12



### MARKING DIAGRAM



xxx = Specific Device Code  
A3X = MMBD2835LT1G  
SMMBD2835LT1G  
A2X = MMBD2836LT1G  
M = Date Code  
■ = Pb-Free Package  
(Note: Microdot may be in either location)

\*Date Code orientation and/or overbar may vary depending upon manufacturing location.

### ORDERING INFORMATION

| Device        | Package             | Shipping†              |
|---------------|---------------------|------------------------|
| MMBD2835LT1G  | SOT-23<br>(Pb-Free) | 3,000 /<br>Tape & Reel |
| SMMBD2835LT1G | SOT-23<br>(Pb-Free) | 3,000 /<br>Tape & Reel |
| MMBD2836LT1G  | SOT-23<br>(Pb-Free) | 3,000 /<br>Tape & Reel |


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MMBD2835LT1G, MMBD2836LT1G, SMMBD2835LT1G

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted) (EACH DIODE)

| Characteristic  | Symbol     | Min         | Max               | Unit |
|---|------------|-------------|-------------------|------|
| <b>OFF CHARACTERISTICS</b>  |            |             |                   |      |
| Reverse Breakdown Voltage ( $I_R = 100\ \mu\text{A}$ )<br>MMBD2835LT1G, SMMBD2835LT1G<br>MMBD2836LT1G   | $V_{(BR)}$ | 35<br>75    | –<br>–            | Vdc  |
| Reverse Voltage Leakage Current (Note 3)<br>( $V_R = 30\ \text{Vdc}$ )<br>MMBD2835LT1G, SMMBD2835LT1G<br>( $V_R = 50\ \text{Vdc}$ )<br>MMBD2836LT1G | $I_R$      | –<br>–      | 100<br>100        | nAdc |
| Diode Capacitance ( $V_R = 0\ \text{V}$ , $f = 1.0\ \text{MHz}$ )   | $C_T$      | –           | 4.0               | pF   |
| Forward Voltage<br>( $I_F = 10\ \text{mA}$ )<br>( $I_F = 50\ \text{mA}$ )<br>( $I_F = 100\ \text{mA}$ )   | $V_F$      | –<br>–<br>– | 1.0<br>1.0<br>1.2 | Vdc  |
| Reverse Recovery Time ( $I_F = I_R = 10\ \text{mA}$ , $I_{R(REC)} = 1.0\ \text{mA}$ ) (Figure 1)  | $t_{rr}$   | –           | 4.0               | ns   |

3. For each individual diode while the second diode is unbiased.



- Notes: 1. A 2.0 kΩ variable resistor adjusted for a Forward Current ( $I_F$ ) of 10 mA.  
2. Input pulse is adjusted so  $I_{R(\text{peak})}$  is equal to 10 mA.  
3.  $t_p \gg t_{rr}$

**Figure 1. Recovery Time Equivalent Test Circuit**

CURVES APPLICABLE TO EACH CATHODE




Figure 2. Forward Voltage




Figure 3. Leakage Current




Figure 4. Capacitance


# MMBD2835LT1G, MMBD2836LT1G, SMMBD2835LT1G

## PACKAGE DIMENSIONS

### SOT-23 (TO-236)

CASE 318-08

ISSUE AP



#### NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 0.89        | 1.00 | 1.11 | 0.035  | 0.040 | 0.044 |
| A1  | 0.01        | 0.06 | 0.10 | 0.001  | 0.002 | 0.004 |
| b   | 0.37        | 0.44 | 0.50 | 0.015  | 0.018 | 0.020 |
| c   | 0.09        | 0.13 | 0.18 | 0.003  | 0.005 | 0.007 |
| D   | 2.80        | 2.90 | 3.04 | 0.110  | 0.114 | 0.120 |
| E   | 1.20        | 1.30 | 1.40 | 0.047  | 0.051 | 0.055 |
| e   | 1.78        | 1.90 | 2.04 | 0.070  | 0.075 | 0.081 |
| L   | 0.10        | 0.20 | 0.30 | 0.004  | 0.008 | 0.012 |
| L1  | 0.35        | 0.54 | 0.69 | 0.014  | 0.021 | 0.029 |
| H_E | 2.10        | 2.40 | 2.64 | 0.083  | 0.094 | 0.104 |
| θ   | 0°          | ---  | 10°  | 0°     | ---   | 10°   |

#### STYLE 12:

1. CATHODE
2. CATHODE
3. ANODE

## SOLDERING FOOTPRINT



**ON Semiconductor** and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

**MMBD2835LT1/D**

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
Email       amall@ameya360.com  
QQ         800077892  
Skype       ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
Email       mkt@ameya360.com