




File: E209153



ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	8.0	± Max
T:	4.0	± Max
Lead Diameter	0.5	± Nom
S:	5.1	± Nom
L:	38.0	± Nom
Coating Lead Run Down (straight Leads)	5.0	± Max
B:	6.30	± Nom
C:	1.50	± Nom



Electrical Specifications

Resistance:	4.0	Ω	± 20 %
Max Steady State Current upto 65°C:	3.00	A	
Max Rec. Energy Rating:	10	J	
Actual Failure Instantaneous Energy:	20	J	
Resistance @ 100% Max Current:	0.23	Ω	
Resistance @ 50% Max Current:	0.32	Ω	
Body Temperature at 100% Max Current:	122.00	°C	
Dissipation Constant:	9.0	mw/°C	
Thermal Time Constant:	20	Sec.	
Material Type (for Beta and Curve):	A		

SL08 4R003	
Date: 02/14/2012	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision:

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com