

Customer Information Sheet

DRAWING No.:C90-3102RXXSX-XXSHEET 2 OF 2

IF IN DOUBT - ASK




C

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

CONTACT LAYOUT (SHOWN LOOKING AT THE MATING FACE
IS FOR ILLUSTRATION ONLY)



ORDER CODE:
C90-3102RXXXX-XX

SHELL SIZE (CONTACT LAYOUT):
10SL-3, 10SL-4, 12S-3, 14S-2
14S-6

CONTACT GENDER:
P - MALE
S - FEMALE

SPECIFICATIONS:

MATERIAL:

- SHELL: ALUMINIUM ALLOY
- INSULATOR: SYNTHETIC RUBBER
- GASKET: SYNTHETIC RUBBER
- CONTACT COPPER ALLOY

FINISH:

- SHELL: ZINC WITH BLACK CHROMATE COATING
- CONTACT: SILVER

ENVIRONMENTAL:

- OPERATING TEMPERATURE: -55°C TO +125°C


MECHANICAL:

- VIBRATION SENSITIVITY: 10Hz TO 500Hz, 98mm/s² (10G)
- SHOCK SEVERITY: 490m/s² (50G) FOR 11ms
- WATER RESISTANCE (SEALING): 1.8m FOR 48HRS, EXCEEDS IP67

ELECTRICAL:

- CURRENT RATING: 13A
- VOLTAGE RATING: 10SL & 12S SHELL SIZES: 500V AC, 700V DC
14S SHELL SIZE: 200V AC, 250V DC
- VOLTAGE PROOF: 10SL & 12S: 2,000V AC
14S: 1,000V AC
- INSULATION RESISTANCE: 5,000MΩ MIN.

FOR MECHANICAL/ELECTRICAL REQUIREMENTS, SEE COMPONENT SPECIFICATION C045XX (LATEST ISSUE)



SHELL SIZE	DIM 'A'	DIM 'B'	THREAD 'C'	DIM 'D'	DIM 'E' +0.4 -0.0	DIM 'F' +0.4 -0.0
10SL	Ø 15.75	18.25	5/8-24UNEF	25.65	25.40	Ø 15.87
12S	Ø 17.17	20.62	3/4-20UNEF	28.02	27.80	Ø 19.05
14S	Ø 18.92	23.02	7/8-20UNEF	30.40	30.17	Ø 22.22

SB	6	25.06.13	12118
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.BENNETT	
CHECKED:		S.FLOWER	
DRAWN:		R.ADDE	
CUSTOMER REF.:			
ASSEMBLY DRG:			

- NOTES:
- PRODUCT IS RoHS COMPLIANT.
 - CONNECTOR PACKED IN BAGS, ONE CONNECTOR AND GASKET PER BAG.
 - RECOMMENDED WIRE SIZE 16-22 AWG.
 - RECOMMENDED PANEL CUT-OUT FOR SHELL SIZE 10SL & 12S = Ø 20.62 AND FOR SHELL SIZE 14S = Ø 23.83.
 - RECOMMENDED WIRE STRIP LENGTH = 7.5mm.

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm

ANGLES = ±5°
UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH: SEE ABOVE

S/AREA: mm²

TITLE:

PANEL MOUNT CONNECTOR

DRAWING NUMBER:

C90-3102RXXSX-XX

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com