

The diagram shows a circular structure composed of several concentric rings. A central crosshair, consisting of a vertical and a horizontal line, is superimposed on the rings. The rings are centered on the intersection of the crosshair. The outermost ring is the largest, and the innermost ring is the smallest. The crosshair lines extend beyond the outermost ring.

Specifications			Notes	Revision History					
Description	Value	Unit		Version	Description		Date	Approved	
Shape	Round		1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS	1	Released from Engineering		2/8/2014	J.S.	
Resonant Frequency	600	(Hz)							
Frequency Range	600 ~ 7,000	(Hz)							
SPL @ 10cm	90	(dBA)							
Impedance	8	(Ohm)							
Cone Material	Mylar								
Nominal Power	0.5	(W)							
Max Power	1.0	(W)							
Mount Type	Flush Mount								
Operating Temperature	-20 ~ +60	°C		Drawn by	Date	Checked by	Date	Approved by	Date
Storage Temperature	-30 ~ +70	°C		G.W.	1/27/2014	C.E.	2/4/2014	J.S.	2/5/2014
Weight	8	(g)							
			DB UNLIMITED	Dynamic Speaker			SM320608-1		

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com