


APPLICABLE FFC LAYOUT
(THICKNESS: 0.29 to 0.34)



RECOMMENDED PCB LAYOUT - COMPONENT VIEW

MATERIAL:
HOUSING MATERIAL: PPS
COLOR: BEIGE
ACTUATOR MATERIAL: PPS
COLOR: BLACK
CONTACT MATERIAL: PHOSPOR BRONZE
CONTACT PLATING: 100μ" TIN OVER 50μ" NI
QUALITY CLASS: 25 MATING CYCLES*







ENVIRONMENTAL:
OPERATING TEMPERATURE: -25°C UP TO 85°C
FLAMABILITY RATING: UL94-V0
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL:
CURRENT RATING: 1A
WORKING VOLTAGE: 125V
INSULATION RESISTANCE: >100MOHM
DIELECTRIC WITHSTANDING VOLT.: 500VAC/MN
CONTACT RESISTANCE: 20mOHM MAX

STANDARD
CERTIFIED: E323964 / MODEL NUMBER 686
FOLLOWED BY 1, FOLLOWED BY 03 THRU 30, FOLLOWED
BY 141 OR 144, FOLLOWED BY NUMERIC DIGITS


SOLDERING:
REFLOW PROCESS ONLY

DIMENSION:
A = B + 8.00
B = 1.00 x (NB PINS - 1)
C = B + 2.1
D = B + 6.00




SECT. A-A


RoHS Compliant				*NOTE: theoretical value related to the Tin plating; however, due to the sensitive actuator, we recommend not to make more than 1 or 2 cycles in order to maintain acceptable mechanical & electrical conditions				
N	05-JUN-15	TPK REVIEW	AK	PROJECTION: 	GENERAL TOLERANCE .X = +/_ 0.2 .XX = +/_ 0.15	 WÜRTH ELEKTRONIK		
M	13-DEC-13	TPK UPDATE	QL					
L	10-APR-13	ACTUATOR	AR					
K	23-JAN-13	UNIT μ => μ"	QL					
J	18-SEP-12	MC NOTE	GG	APPROVAL: GMo	UNIT: MM	DESCRIPTION: 1.0MM ZIF FPC HORIZONTAL BOTTOM CONTACT TYPE - TAPE & REEL PACKAGING	SIZE A4	
I	28-JUN-12	COLOR	GG		SCALE:			
H	26-JUN-12	DIM	GG		SHEET: 1/2			WERI PART NO: 686 1xx 144 22
REV	DATE	FILE	BY		DRAW: PEARL			




PART-NO.	4-9PIN	10-14PIN	15-26PIN	27-30PIN
W	24.00	32.00	44.00	56.00
F	11.50	14.20	20.20	26.20
S0	— —	28.40	40.40	52.40

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15	 WÜRTH ELEKTRONIK	DESCRIPTION: 1.0MM ZIF FPC HORIZONTAL BOTTOM CONTACT TYPE - TAPE & REEL PACKAGING	SIZE A4
G								
F								
E								
D				APPROVAL: GMo	UNIT: MM	WERI PART NO: 686 1xx 144 22		
C								
B								
A								
REV	DATE	FILE	BY		DRAW: AK			

①




②




Pull the actuator upwards in the open position

Ⓐ

①



②




Insert the FFC cable vertically until the conductor almost disappears

Ⓑ




Press actuator in the middle to make there is no gap and the actuator is locked


①





②




Press both ends of the actuator



A



B



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com