




ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	6.0	± max
T:	2.7	± max
Lead Diameter	0.5	± nom
S:	5.1	± nom
L:	38.0	± nom
Coating Lead Run Down (straight Leads)		± max
B:	4.50	± nom
C:	1.80	± nom



Electrical Specifications

Resistance:	30.0 Ω	± 5 %
Max Steady State Current upto 65°C:	0.25	A
Max Rec. Energy Rating:	3	J
Actual Failure Instantaneous Energy:		J
Maximum Capacitance @ 120 VAC:	200	μ f
Resistance @ 100% Max Current:		Ω
Resistance @ 50% Max Current:		Ω
Body Temperature at 100% Max Current:		°C
Dissipation Constant:	4.0	mw/°C
Thermal Time Constant:	20	Sec.
Material Type (for Beta and Curve):		

SL05 30001	
Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com