


FED. MFR. CODE 91929

105 ML1-E1



1- ROLLER ASSEMBLY MAY BE RE-ASSEMBLED 90° FROM POSITION SHOWN.
2- IT IS ESSENTIAL THAT THE CONDUIT OPENING BE PROPERLY SEALED IN ORDER TO MAINTAIN THE EXPLOSION PROOF PROPERTIES.
3- SWITCH WILL PERFORM SATISFACTORILY IN TEMPERATURES TO MINUS 30°F.
-LISTED BY UNDERWRITERS LABORATORY, INC. FOR USE IN CLASS I GROUPS C AND D VAPOR-AIR
4- ATMOSPHERES, AND CLASS 2 GROUPS E, F AND G DUST-AIR ATMOSPHERES

CHARACTERISTICS	ELECTRICAL DATA		SCALE 1/2 TO 1
OPERATING FORCE — — — 6 LBS. APPROX.	CONTACT ARRANGEMENT TWO CIRCUIT DOUBLE THROW DOUBLE BREAK		DO NOT SCALE PRINT
RELEASE FORCE — — — — 4 LBS. APPROX.	10 A-120, 240, OR 480 VAC; 1/2 HP-120 VAC 1 HP-240 VAC; 0.8 A-115 VDC; 0.4 A-230 VDC PILOT DUTY; 720VA-HEAVY DUTY 600 VAC MAX		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:
DIFFERENTIAL TRAVEL — — — .020 MAX.	(A)	(UL)	ONE PLACE (.0) ±.030
OVERTRAVEL — — — — .475 MIN.	(B)	(SA)	TWO PLACE (.00) ±.015
SWITCH-BASIC REPLACEMENT — — — — 1 MN1	(C)		THREE PLACE (.000) ±.008
			ANGLES ±
			WEIGHT 1 LB. 13 OZ.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com