

NHD-5.7-640480WF-CTXL#-T

TFT (Thin-Film-Transistor) Color Liquid Crystal Display Module

NHD-	Newhaven Display
5.7-	5.7" Diagonal
640480-	640xRGBx480 pixels
WF-	Model
C-	Built-in driver+Controller
T-	White LED backlight
X-	TFT
L-	12:00 view, Wide Temp
#	RoHS Compliant
T-	Touch Panel

Newhaven Display International, Inc.

2511 Technology Drive, Suite 101

Elgin IL, 60124

Ph: 847-844-8795

Fax: 847-844-8796

www.newhavendisplay.com

nhtech@newhavendisplay.com

nhsales@newhavendisplay.com


Document Revision History


Revision	Date	Description	Changed by
0	3/9/2009	Initial Release	CL
1	3/3/2011	Drawing and TP content updated	BE
2	6/18/2012	Pin description updated	AK

Functions and Features

- 640xRGBx480 resolution
- LED backlight
- 8-bit parallel interface
- SSD1963 Controller
- 4-Wire resistive Touch Panel

Mechanical Drawing





Pin Description

Note: CON2 has a 20-pin, 1.0mm pitch, Top-Contact FFC Connector. Pins 21 and 22 are not connected.

CON2:


Pin No.	Symbol	External Connection	Function Description
1	GND	Power Supply	Ground
2	VCC	Power Supply	Power supply for LCD and logic (3.3V)
3	NC	-	No Connect
4	D/C#	MPU	Register Select signal – 0: Command, 1: Data
5	WR#	MPU	Active LOW Write signal, 8080 MPU interface
6	RD#	MPU	Active LOW Read signal, 8080 MPU interface
7-14	[DB0-DB7]	MPU	Bi-directional data bus lines
15	CS#	MPU	Active LOW Chip Select signal
16	U/D	MPU	Scan direction 1: Up, 0: Down
17	R/L	MPU	Scan direction 1: Right, 0: Left
18	RES#	MPU	Active LOW Reset signal
19	NC	-	No Connect
20	NC	-	No Connect

Recommended LCD connector: 1.0mm pitch 20-Conductor FFC. Molex p/n 52746-2070

Backlight:

Pin No.	Symbol	External Connection	Function Description
1	VCC	Power Supply	LED Anode (60mA @ 23.1V)
2	VCC	Power Supply	LED Cathode

Backlight connector: JST p/n: BHSR-02VS-1 **Mates with:** JST p/n: SM 02B-BHSS-1



Touch Panel Pin Description

Pin No.	Symbol	External Connection	Function Description
1	X1	Touch Controller	DOWN
2	Y1	Touch Controller	LEFT
3	X2	Touch Controller	UP
4	Y2	Touch Controller	RIGHT

Recommended Touch panel connector: 1.0mm pitch FFC

Controller Information

Built-in SSD1963 controller.

Please download specification at http://www.newhavendisplay.com/app_notes/SSD1963.pdf

8080 Mode Interface:

The 8080 mode MPU interface consists of CS#, D/C, RD#, WR#, and DB[7:0]. This interface uses WR# to define a write cycle and RD# to define a read cycle. If the WR# goes LOW when the CS# signal is LOW, the data or command will be latched into the system at the rising edge of WR#. Similarly, the read cycle will start when RD# goes LOW and end at the rising edge of RD#. See the SSD1963 datasheet for detailed timing diagrams.

Command Instructions:

See the SSD1963 datasheet for the Instruction Table and Command Descriptions.

Pixel Data Format:

Interface	Cycle	D[7]	D[6]	D[5]	D[4]	D[3]	D[2]	D[1]	D[0]
8 bits	1 st	R7	R6	R5	R4	R3	R2	R1	R0
	2 nd	G7	G6	G5	G4	G3	G2	G1	G0
	3 rd	B7	B6	B5	B4	B3	B2	B1	B0

Electrical Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Operating Temperature Range	Top	Absolute Max	-20	-	+70	°C
Storage Temperature Range	Tst	Absolute Max	-30	-	+80	°C
Supply Voltage	VCC	-	3.0	3.3	3.6	V
Supply Current	ICC	VCC=3.3	-	190	250	mA
Backlight Supply Current	IB	-	-	60	-	mA
Backlight Supply Voltage	VBL	-	-	23.1	24.5	V
Backlight Lifetime		-	10,000	25,000	-	Hr

Optical Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Viewing Angle – Top		Cr ≥ 10	-	60	-	°
Viewing Angle – Bottom		Cr ≥ 10	-	40	-	°
Viewing Angle – Left		Cr ≥ 10	-	60	-	°
Viewing Angle – Right		Cr ≥ 10	-	60	-	°
Contrast Ratio	Cr	-	150	250	-	
Luminance	YL	-	250	300	-	cd/m ²
Response Time (rise)	Tr	-	-	25	40	ms
Response Time (fall)	Tr	-	-	25	40	ms

Quality Information

Test Item	Content of Test	Test Condition	Note
High Temperature storage	Endurance test applying the high storage temperature for a long time.	+80°C , 200hrs	2
Low Temperature storage	Endurance test applying the low storage temperature for a long time.	-30°C , 200hrs	1,2
High Temperature Operation	Endurance test applying the electric stress (voltage & current) and the high thermal stress for a long time.	+70°C 200hrs	2
Low Temperature Operation	Endurance test applying the electric stress (voltage & current) and the low thermal stress for a long time.	-20°C , 200hrs	1,2
High Temperature / Humidity Operation	Endurance test applying the electric stress (voltage & current) and the high thermal with high humidity stress for a long time.	+60°C , 90% RH , 96hrs	1,2
Thermal Shock resistance	Endurance test applying the electric stress (voltage & current) during a cycle of low and high thermal stress.	-20°C,30min -> 25°C,5min -> 70°C,30min = 1 cycle 10 cycles	
Vibration test	Endurance test applying vibration to simulate transportation and use.	10-55Hz , 15mm amplitude. 60 sec in each of 3 directions X,Y,Z For 15 minutes	3
Static electricity test	Endurance test applying electric static discharge.	VS=800V, RS=1.5kΩ, CS=100pF One time	

Note 1: No condensation to be observed.

Note 2: Conducted after 4 hours of storage at 25°C, 0%RH.

Note 3: Test performed on product itself, not inside a container.

Precautions for using LCDs/LCMs

See Precautions at www.newhavendisplay.com/specs/precautions.pdf

Warranty Information and Terms & Conditions

http://www.newhavendisplay.com/index.php?main_page=terms

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com