## **AMPROBE®**

**Data Sheet** 

# TIC 300 PRO High Energy Tic Tracer – Non Contact AC Voltage Detector

Rugged and reliable for utility, industrial and mine safety applications, The TIC 300 PRO warns against dangerous voltages in low and medium voltage applications up to 122 KV without contacting the energized conductor.

- Utility tool for checking transmission lines, power distribution equipment, down power lines, fuses, and load break connectors
- Lower voltage setting for checking voltage presence in breaker panels, breakers, power outlets and wiring
- Verifies presence of Voltage from 30 VAC to 122,000 VAC (122kV)
- Non-contact AC voltage detection
- Visual and audible voltage indication
- Self-test verifies that tester works properly
- Ergonomic design with a convenient handle
- Drop-proof to 6-FT
- Used with Hot Stick Tic 410A for voltage higher than 1500 VAC



### No hassle warranty

No waiting.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



#### **TIC 300 PRO High Energy Tic Tracer – Non Contact AC Voltage Detector**

**Data Sheet** 

#### **Specifications**

Non-Contact Voltage Detection 30-1500 VAC

1500- 122,000 VAC (with Hot Stick TIC 410A)

#### **Self-Test Verification**

Line voltage (kV)	Phase to ground		Phase to phase	
phase to phase	(ft-in)	(m)	(ft-in)	(m)
0.03 to 1.0	note 1	note 1	note 1	note 1
1.1 to 15.0	2-1	0.64	2-2	.66
15.1 to 36.0	2-4	0.72	2-7	0.77
36.1 to 46.0	2-7	0.77	2-10	0.85
46.1 to 72.5	3-0	0.90	3-6	1.05
72.6 to 121	3-2	0.95	4-3	1.29

Sensitivity Typical

#### Low Voltage

Voltage (Phase to Ground)	Detection Range	
	Average	
30 V	2.7"	
75 V	9.7"	
100 V	1′ 1″	
120 V	1′ 6″	
220 V	2′ 4″	
500 V	4′ 2″	
1000 V	6′ 3″	
1500 V	7′ 9″	

#### High Voltage

Voltage	Detection Range	
(Phase to Ground)	Average	
1.5 kV	1′ 2″	
2.0 kV	2′ 5″	
4.0 kV	3″	
10.0 kV	6′ 3″	
25.0 kV	9′ 4″	
50.0 kV	13′ 0″	
75.0 kV	14′ 8″	
100.0 kV	19′ 8″	
122.0 kV	22′ 0″	

#### **Optional Accessories**

TIC 410A Hot Stick, CC-300PRO Carrying Case

#### **Amprobe® Test Tools**

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203

Tel: 877-AMPROBE

#### **Amprobe® Test Tools Europe**

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved. 12/2009 3612797 Rev A

## AMEYA360 Components Supply Platform

#### **Authorized Distribution Brand:**

























#### Website:

Welcome to visit www.ameya360.com

#### Contact Us:

#### Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

#### > Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

#### Customer Service :

Email service@ameya360.com

#### Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com