


## SPECIFICATION

Model #	:	<b>ISPC.915.A</b>
Part No.	:	<b>ISPC.91A.09.0092E</b>
Product Name	:	5dBi ISM Band 915MHz Embedded Ceramic Patch Antenna with Cable and Connector
Features	:	High antenna efficiency 902MHz to 928MHz ISM Band 5dBi Peak (when placed on 30cm x30cm ground plane) - Broadside to Zenith Radiation Pattern 1dBi Peak Gain in free-space 47.5*47.5*6.5 mm (Ceramic Antenna) 49.5*49.5*7.5 mm (Antenna with EVB) RG178 92mm cable length MMCX male Right Angle Connector RoHS Compliant

Photo:



## 1. Introduction

The 5dBi ISPC.915.A embedded ceramic patch antenna with cable and connector is designed primarily for ISM band 915MHz compact fixed wireless applications where it can be mounted to a metal panel to function as ground underneath the antenna.

When placed on a reference 30cm square ground-plane, the antenna has excellent directional hemispherical radiation pattern up to 5dBi on the zenith, and an efficiency of 71%.

Even without a ground-plane underneath the antenna achieves 1dBi and an efficiency of 50~60%, with an omni-directional pattern.

Coming as standard with a RG178 cable and MMCX male right angle connector it is a great solution for the following typical applications

- RFID Readers
- Short range 915MHz mesh networks

Cable type, length and connector can be customized. Mechanical customization of the antenna can also be done for a minimum order quantity. Please contact your regional Taoglas office for more details.

## 2. Specification

ELECTRICAL		
Measurement Environment	Free Space	On 30x30(cm) ground plane
Operation Frequency (MHz)	915MHz	
Return Loss (dB)	-7.4	-9.7
Peak Gain(dbi)	1.19	5.21
Efficiency (%)	58.20	71.25
Average Gain (dB)	-2.35	-1.47
Polarization	Linear	
Impedance	50 Ohms	
Radiation Properties	Broadside Toward Zenith	
Max Input Power	5 W	
MECHANICAL		
Dimension (mm)	47.5*47.5*6.5	
Material	Ceramic	
Product Dimension (mm)	49.5*49.5*7.5	
Coaxial Cable	RG178	
Coaxial Length (mm)	92	
Connector	MMCX Male Right Angle	
ENVIRONMENTAL RATINGS		
Operation Temperature	-40°C to 85°C	
Storage Temperature	-40°C to 105°C	
Relative Humidity	40% to 95%	
RoHS Compliant	Yes	


## 3. Antenna Characteristics

### 3.1 Testing setup

ISPC.915.A antenna was tested with R&S ZNB-8 network analyzer.




Free Space




On 30x30(cm) ground plane


### 3.2 Return Loss




### 3.3 Peak Gain



### 3.4 Efficiency




### 3.5 Average Gain




## 4. Antenna Radiation Patterns

### 4.1 Antenna setup

The antenna radiation pattern measured setup as shown the below,



**Free Space**




**On 30x30(cm) ground plane**


## 4.2 Antenna radiation patterns

### On 30x30(cm) Ground plane

#### XY Plane




#### XZ Plane







## YZ Plane



## Free Space XY Plane




## XZ Plane




## YZ Plane

Z



## 5. DRAWING



	Name	P/N	Material	Finish	QTY
1	915MHz Patch	001513H010007A	Ceramic	Clear	1
2	RG-178	301013A000007A	FEP	Brown	1
3	MMCX(M) RA	202713D010007A	Brass	Gold	1
4	PCB	100213H000007A	FR4 1t	N/A	1

## 6. APPLICATION NOTE

Taoglas considers the application here of the ISPC.91A antenna in different typical environments. Some environments the antenna will be close to ground plane (or general metal objects) and at different orientations. The distance to ground-plane will also differ. Following this rationale, we compiled the antenna S11 variation charts as below to evaluate the typical effects on performance. A degraded return loss would generally to relatively decreased efficiency, peak gain, and deformed radiation patterns. \*\*Note - while it may appear from the return loss on the ground above antenna that the antenna may work in this orientation, it is likely the gain and efficiency are very poor we would not recommend it under any circumstance\*\*

There are three general situations of a ground plane orientation to antenna, the setup is as below.



Ground under antenna




Ground above antenna





Ground side of antenna



## Ground under antenna



## Ground above antenna



## Ground side of antenna







## 7. Packaging

8 pieces per Tray

5 Trays per Inside Box: 40 pieces

4 Inside Box's per Outer Box: 160 pieces





# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)