REV. Status A. Electrical Specifications (@25°C) ISSUE 1 1. Rated Voltage; 250 V AC 50/60 Hz 2. Rated Current; 3A AC 04/08/96 TS 3. Common Mode Inductance (@ 1 KHz); 1 mH MIN 4. DC Resistance; (each winding) 0.1Ω MAX 6. Insulation Resistance; 100 M Ω MIN at 500 VDC Winding to Winding, Winding to Core 7. HiPot test; AC 2.0 KV 1 minute Winding to Winding, Winding to Core Country of origin-B. Schematic Diagram; WINDING 2 WINDING 1 C. Mechanical Specifications; **-**12.5(0.49) MAX 28(1.1) MAX $20\pm5(0.787\pm0.197)$ 1.5(0.059) MAX WIRE INSULATION SOLDER COATED TYP 4 PLACES -Ø 0.7(0.027) 4 PLACES-START WINDING 1 START WINDING 2

Brennan ENGINEER: DWG CONTROL NO. REV COIL P-A4-11621 CMT-01301 COMMON MODE T. Shiozawa QUALITY CONTROL: ACAD\MISCX\A41116211.DWG CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE TAMURA CORPORATION OF AMERICA MODEL SPECIFICATION 43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624 (909) 699-1270 FAX 9096769482 DIM: mm(In) SCL: 1/1 PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.

FINISH WINDING 1

FINISH WINDING 2

PREPARED BY:

M. Ong

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com