

Fast-Acting Indicating Telecom Fuse

60Vdc/125Vac



Catalog Symbol: GMT

Fast-acting indicating fuse for telecom circuits.

Ratings:

Volts: 60Vdc/125Vac Amps: 18/100 – 15A IR: 450A @ 60Vdc 300A @ 125Vac Agency Information:

UL Recognized, Guide JFHR2, File E56412

Materials:

Body: Thermoplastic (flammability rating: UL94V0)

Terminals: Tin-plated beryllium copper Carton Quantity & Weight: 100 fuses per carton, 0.33 lbs. (150g.)

Fuse Holders: Catalog Nos. HLS, HLT and PCT


General Information:

- · For telecom, computer, or control circuits.
- · Visual spring indicating and alarm circuit indicating.
- Color coded flags designate amp rating.
- · Fuses easily replaced without use of insulated tools.
- Fuses can be removed with wire hook when mounted on minimum centers.
- GMT-X fuse cover available.
- GMT-Y fuse cover (with pull-tab) available.


Catalog Symbol and Color Codes

5 9		l	
Catalog Symbol	Color Code	Catalog Symbol	Color Code
Symbol	Code	Symbol	Coue
GMT-18/100A	Yellow	GMT-3 1/2A	White/Blue
GMT-1/4A	Violet	GMT-4A	White/Brown
GMT-3/8A	White/Gray	GMT-5A	Green
GMT-1/2A	Red	GMT-7 1/2A	Black/White
GMT-65/100A	Black	GMT-10A	Red/White
GMT-3/4A	Brown	GMT-12A	Yellow/Green
GMT-1A	Gray	GMT-15A	Red/Blue
GMT-1 1/3A	White	GMT-Dummy	Gray
GMT-1 1/2A	White/Yellow	GMT-A (alarm)*	Yellow
GMT-2A	Orange	GMT-X (cover)	Clear
GMT-3A	Blue		


^{*}Designed specifically for use in the Telpower® Series 15800 fused disconnect switch.



Covers — in (mm)



GMT-X Fuse Cover




GMT-Y Fuse Cover

COOPER Bussmann

0708 BU-SB08204 Page 1 of 2 Data Sheet 5008

Time-Current Characteristic Curves-Average Melt



Test Specifications

rost opcomoations		
Percent	Opening	
Overload	Time	
100%	10 min. (minimum)	
150%	5 min. (maximum)	

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

0708 BU-SB08204 Page 2 of 2



Data Sheet 5008

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com