1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



### **Datasheet for 76650-0029**

**General Information** 

**Part Number:** 76650-0029

Manufacturer: Molex / Waldom

Title: Solderless Terminal Kit

Assorted Non-Insulated Quick Disconnect, Ring, Spade and Butt Splice Solderless

**Description:** Terminals. Nylon Insulated Closed-End Solderless Terminals, with Universal

Crimping Tool

**Product Family:** Solderless Terminals

Certificates: (Molex Parts within this kit) - EU RoHS Compliant and UL

Country of Origin: Kit assembled in U.S.A.

**Specifications** 

Design

**Configuration:** Wire-to-Wire, Wire-to-Board / Solderless Terminals

**Size(s):** .250", # 6 and # 10

Current Rating: Per (Proper) Wire Specification

Voltage: Per (Proper) Wire Specification

Wire size: (22-18) and (16-14)

### **Product Highlights**

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade.

Spades have the open tongue end used for rapid insertion on the mounting screw. The spade is usually used on free standing studs.

Butt Splices allow two stripped wires to be inserted into each end and "butt" in the center, with the crimp securing both wires together.

1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



### **Datasheet for 76650-0029**

### **Features and Benefits**

- Terminals employ the full barrel length that eliminates costly and time consuming location when crimping
- Finest quality electrolytic copper
- One-piece design, butted seam
- The Spade's open tongue end is for rapid insertion on the mounting screw / stud
- The basic Ring Tongue type is the safest and most reliable because it cannot be disconnected unless the screw is completely removed.
- Block Spades are designed for use in terminal blocks

# **Applications**

- MRO (Maintenance Repair and Operations)
- Consumer applications
- Power applications
- Motor applications
- Powertrains
- Transportation
- Construction / Mining
- Energy / Power
- Production Equipment
- Instrumentation
- Environmental Equipment and Controls
- Blower Motors



# **Datasheet for 76650-0029**

Bill of Materials for Part No. 76650-0029			
Molex Part No.	Country of Origin	Description	Quantity in Kit
19016-0111	USA	Non-insulated .250" Female Quick Disconnects,16-14 AWG	40
19022-0018	USA	Non-insulated .250" Male Quick Disconnects, 16-14 AWG	40
19044-0032	USA	Non-insulated #10 Ring Tongue Terminals, 16-14 AWG	30
19044-0068	USA	Non-insulated #6 Ring Tongue Terminals, 22-18 AWG	30
19044-0072	USA	Non-insulated #10 Ring Tongue Terminals, 22-18 AWG	30
19044-0152	USA	Non-insulated #6 Ring Tongue Terminals, 16-14 AWG	30
19118-0021	USA	Non-insulated #6 Flanged Block Spade Terminals, 22-18 AWG	40
19128-0021	USA	Non-insulated #6 Block Spade Terminals, 16-14 AWG	30
19146-0037	USA	Non-insulated #10 Block Spade Terminals, 16-14 AWG	30
19160-0002	USA	Insulated Nylon Closed-end Connectors, 16-14 AWG	20
19189-0002	USA	Non-insulated Butt Splice Connectors, 22-18 AWG	40
19189-0008	USA	Non-insulated Butt Splice Connectors, 16-14 AWG	40
CT-4071-1R^	Taiwan	Universal Hand Crimping Tool, 22-10 AWG	1

^=Tool Provided by Waldom

## Recommended Molex Tool(s) for Part No. 76650-0029\*

Country

Molex Part No.	of Origin	Description
64001-0600 *	USA	Hand Crimp Tool (RHT-7000)
64003-0100 *	USA	Hand Crimp Tool (RHT-1992)
64003-1200 *	USA	Hand Crimp Tool (RHT-1752)

<sup>\*</sup>Tool(s) not included in kit. Tool(s) ordered separately.

# AMEYA360 Components Supply Platform

# **Authorized Distribution Brand:**

























# Website:

Welcome to visit www.ameya360.com

# Contact Us:

# Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

# > Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

# Customer Service :

Email service@ameya360.com

# Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com