

N Specifications

Materials

Connector Part	Material	Finish
Bodies	Brass	Nickel or Gold
Center contact	Male: Brass	Gold
	Female: Brass, Phosphor Bronze or Beryllium Copper	
Insulator	PTFE	N/A
Crimp ferrule	Annealed Copper	Nickel or Gold

Electrical

Electrical Data	Detail	
Impedance	50 ohm	75 ohm
Frequency range	0~11GHz	0~6GHz
Working voltage	500volts rms max.	
Insulation resistance	5,000 megaohms min.	
Dielectric withstanding voltage	2,500 volts rms min.	
Contact resistance	Center contact: 3.0 milliohms max.	
	Outer contact: 2.0 milliohms max.	
VSWR: f(GHz)	Straight: 1.3 max.	
	Right angle: 1.5 max.	
Insertion loss	0.3dB max. at 10GHz	

Mechanical

Mechanical Data	Detail
Engagement force	6 inch-pounds max.
Disengagement force	6 inch-pounds max.
Connector durability	500 cycles min.
Cable retention force	RG58, 141, 142, 223/U » 40lbs min.
	RG174, 188, 316/U » 20lbs min.

Environmental

Environmental Data	Detail
Corrosion (salt spray)	MIL-STD-202 METHOD 101 TEST CONDITION B
Thermal shock	MIL-STD-202 METHOD 107 TEST CONDITION B
Vibration	MIL-STD-202 METHOD 204 TEST CONDITION B
Mechanical shock	MIL-STD-202 METHOD 213 TEST CONDITION I
Temperature Range	-65°C to 165°C (PTFE)

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com