

POWER TRANSFORMER **CHASSIS MOUNT: OUICK-CONNECT WORLD SERIES TM**

VPS16-11000

Electrical Specifications (@25C)

- 1. Maximum Power: 175.0VA
- 2. Primary Series: 230VAC, 50/60Hz; Parallel: 115VAC, 50/60Hz
- 3. Secondary Series: 16.0V CT@ 11.0A; Parallel: 8.0V @ 22.0A
- 4. Voltage Regulation: 25% TYP @ full load to no load
- 5. Temperature Rise: 30C TYP (45C MAX allowed)
- Insulation Resistance: 100MΩ

Construction:

Dual bobbin construction with an insulated shroud, both made of a high temperature material that exceeds UL flammability requirements.

Safety:

These units are designed with 4000VAC isolation between the primary and secondary, and also, between each winding and the core. Since the dual bobbin construction effectively reduces capacitance, electrostatic shielding is not required. World Series Transformers are designed and manufactured to meet the following agency approvals:

Agency File:

UL: File E53148, UL 5085-1 and 2 (formerly UL 506), General Purpose. CSA: File LR 221330. C22.2 NO. 66, General Purpose. TUV Certificate No.: R72103639, EN60950, Information Technology



A. Dimensions:

A. Dimensions:						ι	Unit: In inches		
н	W	D	А	В	С	Т	MW	ML	
3-3/4	3-1/8	2-13/16	-	1-5/8	3/8	1/4	2-1/2	2-1/2	

B. Mounting Hole Size: 13/64"X3/8"

C. WT Lbs. : 5.5

Connections¹:

Input: Series – 6 and 1, Jumper 5 to 2 Parallel - 6 and 1, Jumper 6 to 2 and 5 to 1 Output: Series – 12 and 7, Jumper 11 to 8

Parallel - 12 and 7, Jumper 12 to 8 and 11 to 7


RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.


* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.


Primary and secondary windings are designed to be connected in series or parallel. Winding are not intended to be used independently.

22520B Temescal Canyon Road Corona, California 92883









Publish Date: September 13, 2012



Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

- > Sales :
 - Direct +86 (21) 6401-6692
 - Email amall@ameya360.com
 - QQ 800077892
 - Skype ameyasales1 ameyasales2

> Customer Service :

Email service@ameya360.com

> Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com