

- Multiple sizes, strengths, and mounting options anchor Nytyes® securely.
- Three Types:
 - 1) Flat - Adhesive-Back and Screw Mounts
 - 2) Dart - Arrowhead and Blind Mounts
 - 3) Saddle - Screw Mount only
- Rubber based adhesive effective up to 126°F (52°C).
- Apply Adhesive-Backed parts to a clean, dry surface.

Heyco® Cable Tie Tensioning Tool



Part No. 0998 fits all standard duty Nytyes. Metal construction, has three tension settings, and automatically trims excess.


Heyco® Nytye® Mounting Platforms

NYTYE MAX. TENSILE STRENGTH		SCREW SIZE *		MAX. PANEL THICKNESS **		NYTYE INSERT POINTS	PART NO. Natural	DESCRIPTION	FOOTPRINT	
lbs.	N	no.	M	in.	mm.				in.	mm.
Flat Type		Adhesive-Back Mount								
40	178	-	-	-	-	4	3594	MP 4A-S	.80 x .80	20,3 x 20,3
50	222	8	4,0	-	-	2	3590	MP 2A	1.10 x 1.10	27,9 x 27,9
		6	3,5	-	-	4	3593	MP 4A	1.15 x 1.15	29,2 x 29,2
Screw Mount										
40	178	6	3,5	-	-	4	4264	MP 4-S	.75 x .75	19,1 x 19,1 
50	222	8	4,0	-	-	4	4265	MP 34	.38 x .75	9,5 x 19,0 
						2	3590	MP 2A †	1.10 x 1.10	27,9 x 27,9
		6	3,5	-	-	4	3593	MP 4A †	1.15 x 1.15	29,2 x 29,2
Dart Type		Arrowhead Mount *								
50	222	.19	4,8	.05	1,2	2	4266	MP PM-19	.56 x .31	6,0 x 14,3 
		.25	6,4	.11	2,8	2	3762	MP PM-25	.31 x .56	7,9 x 14,3
		.26	6,7	.35	9,0	2	4267	MP PM-26	.31 x .80	7,9 x 20,2 
Blind Mount **										
40	178	.31	7,9	.25	6,4	2	4268	MP PMB-31	.33 x .43	8,3 x 11,0 
Saddle Type		Screw Mount								
18	80	4	3,0	-	-	2	4269	MP S-4	.33 x .51	8,3 x 13,0 
50	222	8	4,0	-	-	2	3759	MP S-8	.38 x .63	9,5 x 15,9
120	534	10	5,0	-	-	2	3753	MP S-10	.63 x .88	15,9 x 22,2
consult Heyco				-	-	2	3754	MP S-5/8	1.25 x 2.31	31,8 x 58,7


* Data = Mounting Hole Diameter, for all **Dart Type** Mount Platforms.

** Data = **Minimum** Panel Thickness for **Blind Mount** Platforms.


† These screw-mountable parts are also Adhesive-Backed.
Standard color natural.




MP 4A-S




MP 2A




MP 4A



MP 4S




MP 34




Dart Type
4266




Dart Type
3762, 4267



Blind Mount
4268



Saddle
Type



MP S-5/8

Quick
Specs

Material	Nylon 6/6
Flammability Rating	94V-2
Temperature Range	32°F (0°C) to 185°F (85°C)

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com