

VOLTAGE CONTROLLED TEMPERATURE COMPENSATED CRYSTAL OSCILLATOR

ASVTX-09



RoHS
Compliant



5.0 X 3.2 X 1.5mm

FEATURES:

- Compact and low in height.
- Low current consumption.
- Suitable for high-density SMT.
- Vc function corresponds to PLL circuits.
- IR reflow possible.

APPLICATIONS:

- Cellular and cordless phones.
- Standard OSC for exact equipment.
- Mobile communication equipment.
- Portable radio equipment and music player.

STANDARD SPECIFICATIONS:

PARAMETERS

ABRACON P/N	ASVTX-09
Frequency	10.000MHz to 44.545MHz
Standard Frequencies	12.8MHz, 13.0MHz, 14.4MHz, 15.36MHz, 16.000MHz, 16.384MHz, 16.8MHz, 19.2MHz, 19.440MHz, 19.680MHz, 19.8MHz, 26.0MHz
Operating Temperature	- 30° C to + 75° C (See Table 1 for options)
Storage Temperature	- 40° C to + 85° C
Freq. Stability vs. +25°C	± 0.5ppm standard (See option)
vs. Operating Temp.	±2.5ppm standard (See Table1 for options)
vs. Aging	± 1ppm/1st year
vs. Supply Voltage	±0.2ppm (± 5% change)
vs. Load	±0.2ppm (± 10% change)
Voltage Control Range (Vcc)	1.5V ±1.0V standard (See options)
Supply Voltage (Vdd)	3.0V ± 5% Standard (See options)
Supply Current	2mA max
Output Type	Clipped Sine
Output Voltage	0.8Vp-p min
Output Load	10 kohm // 10 pF
Pullability	± 8ppm min
Transfer Function	Positive
Phase Noise	-110dBc/Hz @ 100KHz offset; -130dBc/Hz @ 1KHz offset

OPTIONS & PART IDENTIFICATION:

(Left blank if standard)

ASVTX - 09 - ☐ - Frequency - ☐ - ☐☐ - ☐

	Supply Voltage (Vdd)	Control Voltage (Vcc)	Frequency Stability vs +25°C	
A	2.5V±5%	1.25V±1.0V	Blank*	±0.5ppm
Blank*	3.0V±5%	1.5V±1.0	J	±1.5ppm
B	3.3V±5%	1.65V± 1.5V		
C	5.0V±5%	2.5V± 2.0V		

*3.0V±5% : Standard

* Standard

Packaging	
Blank	Bulk
T	Tape and Reel

(1,000 or 2,000pcs/reel)

Table 1: Frequency Stability vs Operating Temp.

	±1ppm	±1.5ppm	±2ppm	±2.5ppm	±3ppm	±4ppm	±5ppm
0°C-50°C	D10	D15	D20	D25	D30	D40	D50
-10°C to 60°C	E10	E15	E20	E25	E30	E40	E50
0°C to 70°C		F15	F20	F25	F30	F40	F50
-20°C to +75°C			G20	G25	G30	G40	G50
-30°C to 75°C				STD	H30	H40	H50
-40°C to 85°C					I30	I40	I50



VOLTAGE CONTROLLED TEMPERATURE COMPENSATED CRYSTAL OSCILLATOR

ASVTX-09




RoHS
Compliant




5.0 X 3.2 X 1.5mm

OUTLINE DRAWING:



Dimensions: Inches (mm)


Recommended land pattern



Note: It is recommended to use an approximately 0.01uF bypass capacitor between PIN 2 and 4.

PIN	FUNCTION
1	Vcc
2	GND
3	Output
4	Vdd

TAPE & REEL:



Dimensions: mm



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com