

Switch Mode Power Supplies Encapsulated Constant Current

TLD1040-36-C1050

Description:

The TLD1040-36-C1050 is a compact and lightweight Constant Current Switch Mode Power Supply. Waterproof design within a 2x4 J box, IP66, NEMA 4 suitable for dry and damp locations. Convection cooled plastic housing. Designed for outdoor and indoor applications. Some typical applications include LED's, Lighting, etc.

Specifications (@25C)

Electrical Specifications:

Input Voltage: Input Frequency Range: Max Input Current: Max Inrush Current: **Power Factor:** Output: Crest Factor (lpk): Leakage Current: Efficiency: **Current Accuracy:** Load Regulation: Hold up time: Protection:

100-304Vac1 47-63Hz 0.5A @ 115Vac; 0.25A @ 230Vac <5A@115Vac, 10A@230Vac >0.9 at full load, 115Vac 1.050Adc±5%, 18-36Vdc 1.5 Max. 300µA Typical 84% Typical at full load ±1% (when applicable) ±3% Half cycle minimum at 120 VAC and 80% of rated voltage Over-voltage, Over current and Short circuit protection: Auto-recovery

Environmental Specifications:

Operating Temperature: -30 to 60°C (De-rating: 1%/°C from 60-70°C) Storage Temperature: -40 to 85°C Operating Humidity: 5 to 95% RH (non-Condensing) Convection cooling 5 to 50Hz >100,000 Hours at full load and 25°C ambient conditions Compliant to 47CFR, Part 2, Part 15 and Cispr PUB, 22 Class B

General Specifications:

Connections: Dimensions (WxLxH): Weight: Warranty:

5in leads - Input: 18 AWG; Output: 18 AWG 70.0x95.0x32.0mm 220g 3 years @ 40°C, 100% Load

Safety Standards:

Cooling:

MTBF:

EMC:

Vibration:

Standards:

UL (cUL) 1310, UL48




RoHS Compliance: This power supply meets the requirements 2002/95/EC, know as the RoHS initiative.


Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.


¹ Parts manufactured before November, 2010 have an input voltage range of 90 – 264VAC.

Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757

22520B Temescal Canyon Road Corona, California 92883







Publish Date: May 1, 2012

AMEYA360 Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

> Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales :

- Direct +86 (21) 6401-6692
- Email amall@ameya360.com
- QQ 800077892
- Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

> Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com