3M[™] D Sub EMI Junction Shell

Metal



- Provides EMI/ESD protection similar to aluminium die cast
- Easy assembly reduces time and labor to ensure low applied cost
- Optional thumbscrew kit
- Provides option in grounding for discrete wire applications
- Light weight, compact design
- See the Regulatory Information Appendix (RIA) in the "RoHS compliance" section of www.3mconnectors.com for compliance information

Date Modified: July 30, 2013

TS-0036-F Sheet 1 of 2

Physical


Shell and Hardware:

Material: Steel Plating: Nickel

Cover Nut:

Material: Unfilled Thermoplastic (ABS)


Flammability: UL 94V-0 Color: Black




3M[™] D Sub EMI Junction Shell

Metal

| Connector Size | Dimensions | | | | | | |
|-------------------|---------------|---------------|---------------|---------------|---------------|---------------|--------------------------------|
| | Α | В | C Ref | D | E [± .03] | F | Recommended Cable size OD ±.01 |
| 09 | 1.18 [30.0] | 0.76 [19.4] | 1.65 [41.9] | 0.54 [13.6] | 0.29 [7.3] | 0.75 [18.9] | 0.28 [7.0] |
| 15 | 1.50 [38.0] | 1.09 [27.6] | 1.85 [46.9] | 0.54 [13.6] | 0.34 [8.7] | 0.75 [18.9] | 0.33 [8.5] |
| 25 | 2.05 [52.0] | 1.63 [41.4] | 2.24 [57.0] | 0.65 [16.4] | 0.43 [10.8] | 0.98 [24.9] | 0.42 [10.6] |
| 37 | 2.68 [68.0] | 2.28 [57.8] | 2.78 [70.6] | 0.74 [18.8] | 0.48 [12.2] | 1.10 [28.0] | 0.47 [12.0] |







NO.4-40UNC

NO.4-40UNC

188
178
2.0
4.78

Bottom Shell





Note: The $3M^{\text{TM}}$ 3341-7 Thumb Screw contains lead in the base material, therefore RIA E5 & C3 apply when using this hardware.

Ordering Information

Junction Shell (RIA E1 & C1 Apply) 3357 - 92XX

09 = 9 Position 15 = 15 Position 25 = 25 Position 37 = 37 Position

Connector Size

Thumb Screw Kit (RIA E5 & C3 Apply)
3341-7
Retainer Ring (RIA E1 & C1 Apply)
3808-ER

TS-0036-F Sheet 2 of 2

Important Notice All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M. Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the

warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of

the legal theory asserted.

6801 River Place Blvd. Austin, TX 78726-9000

www.3Mconnectors.com

1-800-225-5373

U.S.A.

3M Electronics Solutions Division

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com