


## Enhanced isoCink+™ Bridge Rectifiers



Case Style PB

\*Tested to UL standard for safety electrically isolated semiconductor devices. UL 1557 4th edition. Dielectric tested to maximum case, storage and junction temperature to 150 °C to withstand 1500 V. Epoxy meets UL 94 V-0 flammability rating.

### PRIMARY CHARACTERISTICS

|                       |                      |
|-----------------------|----------------------|
| Package               | PB                   |
| $I_{F(AV)}$           | 40 A                 |
| $V_{RRM}$             | 600 V, 800 V, 1000 V |
| $I_{FSM}$             | 400 A                |
| $I_R$                 | 10 $\mu$ A           |
| $V_F$ at $I_F = 20$ A | 0.94 V               |
| $T_J$ max.            | 150 °C               |
| Diode variations      | In-Line              |

### FEATURES

- UL recognition file number E312394 (QQX2) UL 1557 (see \*)
- Enhanced high-current density single in-line package
- Superior thermal conductivity
- Solder dip 275 °C max. 10 s, per JESD 22-B106
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances and white-goods applications.

### MECHANICAL DATA

#### Case: PB

Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS-compliant, commercial grade

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test

**Polarity:** As marked on body

**Mounting Torque:** 10 cm-kg (8.8 inches-lbs) max.

**Recommended Torque:** 5.7 cm-kg (5 inches-lbs)

### MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)

| PARAMETER  | SYMBOL  | PB4006         | PB4008 | PB4010 | UNIT             |
|--|---|----------------|--------|--------|------------------|
| Maximum repetitive peak reverse voltage  | V <sub>RRM</sub>  | 600            | 800    | 1000   | V                |
| Average rectified forward current (Fig. 1, 2)  | $\frac{T_C = 87\text{ }^{\circ}\text{C}^{(1)}}{T_A = 25\text{ }^{\circ}\text{C}^{(2)}}$ | I <sub>O</sub> | 40     |        | A                |
|  |   |                | 4.4    |        |                  |
| Non-repetitive peak forward surge current<br>8.3 ms single sine-wave, T <sub>J</sub> = 25 °C | I <sub>FSM</sub>  | 400            |        |        | A                |
| Rating for fusing (t < 8.3 ms) T <sub>J</sub> = 25 °C  | I <sup>2</sup> t  | 664            |        |        | A <sup>2</sup> s |
| Operating junction and storage temperature range   | T <sub>J</sub> , T <sub>STG</sub>   | - 55 to + 150  |        |        | °C               |

#### Notes

<sup>(1)</sup> With heatsink

<sup>(2)</sup> Without heatsink, free air

| ELECTRICAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                       |                         |                |      |      |      |
|--|-----------------------|-------------------------|----------------|------|------|------|
| PARAMETER  | TEST CONDITIONS       |                         | SYMBOL         | TYP. | MAX. | UNIT |
| Maximum instantaneous forward voltage per diode <sup>(1)</sup>             | I <sub>F</sub> = 20 A | T <sub>A</sub> = 25 °C  | V <sub>F</sub> | 1.01 | 1.10 | V    |
|  |                       | T <sub>A</sub> = 125 °C |                | 0.94 | 1.00 |      |
| Reverse current per diode <sup>(2)</sup>                                   | rated V <sub>R</sub>  | T <sub>A</sub> = 25 °C  | I <sub>R</sub> | -    | 10   | μA   |
|  |                       | T <sub>A</sub> = 125 °C |                | 130  | 500  |      |
| Typical junction capacitance per diode                                     | 4.0 V, 1 MHz          |                         | C <sub>J</sub> | 120  | -    | pF   |

**Notes**
<sup>(1)</sup> Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle

<sup>(2)</sup> Pulse test: 10 ms pulse width

| THERMAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                                 |        |        |        |      |
|---|---------------------------------|--------|--------|--------|------|
| PARAMETER   | SYMBOL                          | PB4006 | PB4008 | PB4010 | UNIT |
| Typical thermal resistance  | R <sub>θJC</sub> <sup>(1)</sup> | 0.75   |        |        | °C/W |
|   | R <sub>θJA</sub> <sup>(2)</sup> | 18     |        |        |      |

**Notes**
<sup>(1)</sup> With 60 W air cooled heatsink

<sup>(2)</sup> Without heatsink, free air

| <b>ORDERING INFORMATION</b> (Example) |                 |                        |               |               |
|---------------------------------------|-----------------|------------------------|---------------|---------------|
| PREFERRED P/N                         | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| PB4006-E3/45                          | 7.53            | 45                     | 20            | Tube          |


**RATINGS AND CHARACTERISTICS CURVES** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)


Fig. 1 - Derating Curve Output Rectified Current




Fig. 2 - Forward Current Derating Curve




Fig. 3 - Forward Power Dissipation




Fig. 5 - Typical Reverse Characteristics Per Diode




Fig. 4 - Typical Forward Characteristics Per Diode





Fig. 6 - Typical Junction Capacitance Per Diode



PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

Case Type PB





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email       amall@ameya360.com  
  
QQ         800077892  
  
Skype      ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
  
Email      mkt@ameya360.com