

4-Port Rugged Industrial USB 2.0 Hi-Speed Hub w 15KV ESD Immunity and metal case, Mountable

MODEL NUMBER: **U223-004-IND**



Description

Tripp Lite's U223-004-IND is a rugged, all metal constructed USB 4-Port hub for use in data centers, work areas, and Industrial applications. Can be mounted on a wall or din-rail with included mounting hardware. Supports Hi-Speed USB 2.0 transfer rates at 480mbps, but is also backward compatible to USB 1.1 (12mbps). Hub is bus-powered through the computer connection, or can self power with an external adapter (not included) or via the included 3-wire terminal block connector (9-36V).

Features

- Industrial-grade, rugged all metal 4-port USB hub
- Supports USB 1.1 and 2.0 transfer speeds (12 - 480mbps)
- Wall or Din Rail mountable - hardware included
- Bus Powered or optional 3-Wire DC Terminal Block
- Over-current detection and protection circuit design
- ESD protected to $\pm 15\text{kV}$
- Automatic link and speed detection
- Plug-and-Play; no software or drivers
- Compatible with all major operating systems

Specifications

OVERVIEW	
Over Current Protection	Yes
Model Type	Hubs

Highlights

- Industrial-grade, rugged metal enclosure
- ESD Protected to $\pm 15\text{ kV}$
- USB 2.0 Compliant - 480Mbps
- Compatible with all major operating systems

Applications

- Use in areas where hub needs to be securely fastened to a surface, such as din rail or wall
- Use in locations where environment is extreme or possible damage could occur

System Requirements



- Compatible with all major operating systems

Package Includes

- U223-004-IND
- USB cable x 1
- 3-pin power terminal block
- DIN rail mounting hardware
- Wallmount hardware



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

PHYSICAL	
Unit Dimensions (HWD/in)	1 x 2.5 x 5.6
Unit Dimensions (HWD/cm)	2.5 x 6.4 x 14.2
Material of construction	Metal
Mounting accessories included	Yes
Color	Black
ENVIRONMENTAL	
Relative Humidity	5 to 95% RH
Operating Temperature	0C to 60C (32F to 140F)
CONNECTIONS	
Connector A	 USB B (FEMALE)
Connector B	 (X4) USB A (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

Related Items

Optional Products

Model Number	Description	Qty.
U022-006	6-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	1
U022-010	10-ft. USB 2.0 A/B Gold Device Cable (A Male to B Male)	1
U022-015	15-ft. USB 2.0 A/B Gold Device Cable (A Male to B Male)	1
U023-003	3-ft. USB2.0 A/B Gold Device Cable with Ferrite Chokes (A Male to B Male)	1
U023-006	6-ft. USB2.0 A/B Gold Device Cable with Ferrite Chokes (A Male to B Male)	1
U223-007-IND	7-Port Industrial USB 2.0 Hub with 15kV ESD Immunity	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at:
<http://www.tripplite.com/sku/U223-004-IND>.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com