

## MM74HC244 Octal 3-STATE Buffer

### General Description

The MM74HC244 is a non-inverting buffer and has two active low enables (1G and 2G); each enable independently controls 4 buffers. This device does not have Schmitt trigger inputs.

These 3-STATE buffers utilize advanced silicon-gate CMOS technology and are general purpose high speed non-inverting buffers. They possess high drive current outputs which enable high speed operation even when driving large bus capacitances. These circuits achieve speeds comparable to low power Schottky devices, while retaining the advantage of CMOS circuitry, i.e., high noise immunity, and low power consumption. All three devices have a fanout of 15 LS-TTL equivalent inputs.

All inputs are protected from damage due to static discharge by diodes to  $V_{CC}$  and ground.

### Features


- Typical propagation delay: 14 ns
- 3-STATE outputs for connection to system buses
- Wide power supply range: 2–6V
- Low quiescent supply current: 80  $\mu$ A
- Output current: 6 mA

### Ordering Code:

| Order Number | Package Number | Package Description   |
|--------------|----------------|---|
| MM74HC244WM  | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| MM74HC244SJ  | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| MM74HC244MTC | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| MM74HC244N   | N20A           | 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide      |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

### Connection Diagram




### Truth Table

| $\overline{1G}$ | 1A | 1Y | $\overline{2G}$ | 2A | 2Y |
|-----------------|----|----|-----------------|----|----|
| L               | L  | L  | L               | L  | L  |
| L               | H  | H  | L               | H  | H  |
| H               | L  | Z  | H               | L  | Z  |
| H               | H  | Z  | H               | H  | Z  |

H = HIGH Level  
L = LOW Level  
Z = High Impedance

Logic Diagram



| Absolute Maximum Ratings (Note 1)                |                                     | Recommended Operating Conditions      |            |            |              |
|--|-------------------------------------|---------------------------------------|------------|------------|--------------|
| (Note 2)   |                                     |                                       | <b>Min</b> | <b>Max</b> | <b>Units</b> |
| Supply Voltage ( $V_{CC}$ )                      | -0.5 to +7.0V                       | Supply Voltage ( $V_{CC}$ )           | 2          | 6          | V            |
| DC Input Voltage ( $V_{IN}$ )                    | -1.5 to $V_{CC} + 1.5V$             | DC Input or Output Voltage            |            |            |              |
| DC Output Voltage ( $V_{OUT}$ )                  | -0.5 to $V_{CC} + 0.5V$             | ( $V_{IN}, V_{OUT}$ )                 | 0          | $V_{CC}$   | V            |
| Clamp Diode Current ( $I_{IK}, I_{OK}$ )         | $\pm 20$ mA                         | Operating Temperature Range ( $T_A$ ) | -40        | +85        | $^{\circ}C$  |
| DC Output Current, per pin ( $I_{OUT}$ )         | $\pm 35$ mA                         | Input Rise or Fall Times              |            |            |              |
| DC $V_{CC}$ or GND Current, per pin ( $I_{CC}$ ) | $\pm 70$ mA                         | ( $t_r, t_f$ ) $V_{CC} = 2.0V$        |            | 1000       | ns           |
| Storage Temperature Range ( $T_{STG}$ )          | -65 $^{\circ}C$ to +150 $^{\circ}C$ | $V_{CC} = 4.5V$                       |            | 500        | ns           |
| Power Dissipation ( $P_D$ )                      |                                     | $V_{CC} = 6.0V$                       |            | 400        | ns           |
| (Note 3)   | 600 mW                              |                                       |            |            |              |
| S.O. Package only                                | 500 mW                              |                                       |            |            |              |
| Lead Temperature ( $T_L$ )                       |                                     |                                       |            |            |              |
| (Soldering 10 seconds)                           | 260 $^{\circ}C$                     |                                       |            |            |              |

**Note 1:** Absolute Maximum Ratings are those values beyond which damage to the device may occur.

**Note 2:** Unless otherwise specified all voltages are referenced to ground.

**Note 3:** Power Dissipation temperature derating — plastic "N" package: — 12 mW/ $^{\circ}C$  from 65 $^{\circ}C$  to 85 $^{\circ}C$ .


### DC Electrical Characteristics (Note 4)

| Symbol   | Parameter                              | Conditions  | $V_{CC}$ | $T_A = 25^{\circ}C$ |                   |           | Units     |         |
|----------|--|---|----------|---------------------|-------------------|-----------|-----------|---------|
|          |  |   |          | Typ                 | Guaranteed Limits |           |           |         |
| $V_{IH}$ | Minimum HIGH Level Input Voltage       |   | 2.0V     |                     | 1.5               | 1.5       | 1.5       | V       |
|          |  |   | 4.5V     |                     | 3.15              | 3.15      | 3.15      | V       |
|          |  |   | 6.0V     |                     | 4.2               | 4.2       | 4.2       | V       |
| $V_{IL}$ | Maximum LOW Level Input Voltage        |   | 2.0V     |                     | 0.5               | 0.5       | 0.5       | V       |
|          |  |   | 4.5V     |                     | 1.35              | 1.35      | 1.35      | V       |
|          |  |   | 6.0V     |                     | 1.8               | 1.8       | 1.8       | V       |
| $V_{OH}$ | Minimum HIGH Level Output Voltage      | $V_{IN} = V_{IH}$ or $V_{IL}$<br>$ I_{OUT}  \leq 20 \mu A$                          | 2.0V     | 2.0                 | 1.9               | 1.9       | 1.9       | V       |
|          |  |   | 4.5V     | 4.5                 | 4.4               | 4.4       | 4.4       | V       |
|          |  |   | 6.0V     | 6.0                 | 5.9               | 5.9       | 5.9       | V       |
|          |  | $V_{IN} = V_{IH}$ or $V_{IL}$<br>$ I_{OUT}  \leq 6.0$ mA<br>$ I_{OUT}  \leq 7.8$ mA | 4.5V     | 4.2                 | 3.98              | 3.84      | 3.7       | V       |
|          |  |   | 6.0V     | 5.7                 | 5.4               | 5.34      | 5.2       | V       |
|          |  |   |          |                     |                   |           |           |         |
| $V_{OL}$ | Maximum LOW Level Output Voltage       | $V_{IN} = V_{IH}$ or $V_{IL}$<br>$ I_{OUT}  \leq 20 \mu A$                          | 2.0V     | 0                   | 0.1               | 0.1       | 0.1       | V       |
|          |  |   | 4.5V     | 0                   | 0.1               | 0.1       | 0.1       | V       |
|          |  |   | 6.0V     | 0                   | 0.1               | 0.1       | 0.1       | V       |
|          |  | $V_{IN} = V_{IH}$ or $V_{IL}$<br>$ I_{OUT}  \leq 6.0$ mA<br>$ I_{OUT}  \leq 7.8$ mA | 4.5V     | 0.2                 | 0.26              | 0.33      | 0.4       | V       |
|          |  |   | 6.0V     | 0.2                 | 0.26              | 0.33      | 0.4       | V       |
|          |  |   |          |                     |                   |           |           |         |
| $I_{IN}$ | Maximum Input Current                  | $V_{IN} = V_{CC}$ or GND  | 6.0V     |                     | $\pm 0.1$         | $\pm 1.0$ | $\pm 1.0$ | $\mu A$ |
| $I_{OZ}$ | Maximum 3-STATE Output Leakage Current | $V_{IN} = V_{IH}$ , or $V_{IL}$<br>$V_{OUT} = V_{CC}$ or GND<br>$\bar{G} = V_{IH}$  | 6.0V     |                     | $\pm 0.5$         | $\pm 5$   | $\pm 10$  | $\mu A$ |
| $I_{CC}$ | Maximum Quiescent Supply Current       | $V_{IN} = V_{CC}$ or GND<br>$I_{OUT} = 0 \mu A$                                     | 6.0V     |                     | 8.0               | 80        | 160       | $\mu A$ |

**Note 4:** For a power supply of  $5V \pm 10\%$  the worst case output voltages ( $V_{OH}$ , and  $V_{OL}$ ) occur for HC at 4.5V. Thus the 4.5V values should be used when designing with this supply. Worst case  $V_{IH}$  and  $V_{IL}$  occur at  $V_{CC} = 5.5V$  and 4.5V respectively. (The  $V_{IH}$  value at 5.5V is 3.85V.) The worst case leakage current ( $I_{IN}$ ,  $I_{CC}$ , and  $I_{OZ}$ ) occur for CMOS at the higher voltage and so the 6.0V values should be used.



| AC Electrical Characteristics   |  |  |          |                    |                   |                                    |                                     |          |
|---|--|--|----------|--------------------|-------------------|------------------------------------|-------------------------------------|----------|
| $V_{CC} = 5V, T_A = 25^\circ C, t_r = t_f = 6 \text{ ns}$   |  |  |          |                    |                   |                                    |                                     |          |
| Symbol  | Parameter                                | Conditions   | Typ      | Guaranteed Limit   | Units             |                                    |                                     |          |
| $t_{PHL}, t_{PLH}$  | Maximum Propagation Delay                | $C_L = 45 \text{ pF}$  | 14       | 20                 | ns                |                                    |                                     |          |
| $t_{PZH}, t_{PZL}$  | Maximum Enable Delay to Active Output    | $R_L = 1 \text{ k}\Omega$<br>$C_L = 45 \text{ pF}$                 | 17       | 28                 | ns                |                                    |                                     |          |
| $t_{PHZ}, t_{PLZ}$  | Maximum Disable Delay from Active Output | $R_L = 1 \text{ k}\Omega$<br>$C_L = 5 \text{ pF}$                  | 15       | 25                 | ns                |                                    |                                     |          |
| AC Electrical Characteristics   |  |  |          |                    |                   |                                    |                                     |          |
| $V_{CC} = 2.0V-6.0V, C_L = 50 \text{ pF}, t_r = t_f = 6 \text{ ns}$ (unless otherwise specified)  |  |  |          |                    |                   |                                    |                                     |          |
| Symbol  | Parameter                                | Conditions   | $V_{CC}$ | $T_A = 25^\circ C$ |                   | $T_A = -40 \text{ to } 85^\circ C$ | $T_A = -55 \text{ to } 125^\circ C$ | Units    |
|   |  |  |          | Typ                | Guaranteed Limits |                                    |                                     |          |
| $t_{PHL}, t_{PLH}$  | Maximum Propagation Delay                | $C_L = 50 \text{ pF}$  | 2.0V     | 58                 | 115               | 145                                | 171                                 | ns       |
|   |  |  | 2.0V     | 83                 | 165               | 208                                | 246                                 | ns       |
|   |  | $C_L = 150 \text{ pF}$   | 4.5V     | 14                 | 23                | 29                                 | 34                                  | ns       |
|   |  |  | 4.5V     | 17                 | 33                | 42                                 | 49                                  | ns       |
|   |  | 6.0V   | 10       | 20                 | 25                | 29                                 | ns                                  |          |
| $t_{PZH}, t_{PZL}$  | Maximum Output Enable Time               | $R_L = 1 \text{ k}\Omega$  | 2.0V     | 75                 | 150               | 189                                | 224                                 | ns       |
|   |  |  |          |                    |                   |                                    |                                     |          |
|   |  | $C_L = 150 \text{ pF}$   | 4.5V     | 15                 | 30                | 38                                 | 45                                  | ns       |
|   |  |  | 4.5V     | 30                 | 40                | 50                                 | 60                                  | ns       |
|   |  | 6.0V   | 13       | 26                 | 32                | 38                                 | ns                                  |          |
| 6.0V  | 17                                       | 34   | 43       | 51                 | ns                |                                    |                                     |          |
| $t_{PHZ}, t_{PLZ}$  | Maximum Output Disable Time              | $R_L = 1 \text{ k}\Omega$<br>$C_L = 50 \text{ pF}$                 | 2.0V     | 75                 | 150               | 189                                | 224                                 | ns       |
|   |  |  | 4.5V     | 15                 | 30                | 38                                 | 45                                  | ns       |
|   |  |  | 6.0V     | 13                 | 26                | 32                                 | 38                                  | ns       |
| $t_{TLH}, t_{THL}$  | Maximum Output Rise and Fall Time        |  | 2.0V     |                    | 60                | 75                                 | 90                                  | ns       |
|   |  |  | 4.5V     |                    | 12                | 15                                 | 18                                  | ns       |
|   |  |  | 6.0V     |                    | 10                | 13                                 | 15                                  | ns       |
| $C_{PD}$  | Power Dissipation Capacitance (Note 5)   | (per buffer)<br>$\overline{G} = V_{IH}$<br>$\overline{G} = V_{IL}$ |          | 12<br>50           |                   |                                    |                                     | pF<br>pF |
| $C_{IN}$  | Maximum Input Capacitance                |  |          | 5                  | 10                | 10                                 | 10                                  | pF       |
| $C_{OUT}$   | Maximum Output Capacitance               |  |          | 10                 | 20                | 20                                 | 20                                  | pF       |
| <p><b>Note 5:</b> <math>C_{PD}</math> determines the no load dynamic power consumption, <math>P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}</math>, and the no load dynamic current consumption, <math>I_S = C_{PD} V_{CC} f + I_{CC}</math>.</p> |  |  |          |                    |                   |                                    |                                     |          |

**Physical Dimensions** inches (millimeters) unless otherwise noted




**20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  
Package Number M20B**



**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



LAND PATTERN RECOMMENDATION



DIMENSIONS ARE IN MILLIMETERS



DETAIL A


NOTES:

- A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M20DRevB1



**20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M20D**

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)




PIN #1 IDENT.

LAND PATTERN RECOMMENDATION



DIMENSIONS ARE IN MILLIMETERS



DETAIL A


NOTES:

- A. CONFORMS TO JEDEC REGISTRATION MO-153, VARIATION AC, REF NOTE 6, DATE 7/93.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLDS FLASH, AND TIE BAR EXTRUSIONS.
- D. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.

MTC20REVD1

**20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide  
Package Number MTC20**

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



N20A (REV G)

**20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide  
Package Number N20A**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)