



TMD-53W Thermocouple Thermometer K/ J With Wireless

Amprobe TMD-53W thermometer with wireless download capability is a professional choice for HVAC/R technicians, electricians, research, industrial process, and quality control. The dual inputs allow easy super-heat and sub-cool temperature measurement as well as cut-out and in temperature measurements.

Choose between models with 0.1% and 0.05% basic accuracy, single and triple displays or memory. Wireless communication is invaluable for applications requiring remote access to the instruments data.

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

- Wireless two ways transmission
- K/J-type thermocouple selection
- Dual input
- MAX/MIN with elapsed time, AVG, REL, HOLD functions
- TIME setting, REL setting
- Warning beeper with Hi/Lo setting
- Resolution 0.1°C to 0.2°F
- User selectable °C/°F

TMD-53W Thermocouple Thermometer K/ J With Wireless

Data Sheet

General Specifications

Display	5 digit liquid crystal display (LCD).
Polarity	Automatic, positive implied, negative polarity indication.
Low Battery Indication	The "⚡" is displayed when the battery voltage drops below the operating level.
Auto Power Off	30 minutes
Measurement Rate	1 time/second
Operating Environment	0°C to 50°C (32°F to 122°F) <80% R.H.
Storage Environment	-20°C to 60°C (-4°F to 140°F) <70% R.H. with battery removed from meter
Accuracy	Stated accuracy at 23°C ±5°C, <75% R.H.
Battery	1.5V x 4pcs AAA size
Battery Life	200 hours typical
Dimensions	L241.3 X W157.98 XH76.2mm (9.5 X 6.22 X3 in)
Weight	Approx. 304g (0.67 lb) including batteries and packaging box.

WIRELESS Features

Frequency Range	910~920MHz. Low current consumption less than 1mA. The transmitting distance can reach 25M without magnetic interference.
-----------------	---

Electrical Specification

Feature	Range
Thermocouple Type	K/J
Wireless Transmission	YES
Temperature	K-TYPE: -200°C-1370°C, -328°F-2498°F J-TYPE: -200°C-1050°C, -328°F-1922°F
Accuracy	±(0.05%rdg + 0.3°C) on -50°C to 1370°C ±(0.05%rdg + 0.7°C) on -50°C to -200°C ±(0.05%rdg + 0.6°F) on -58°F to 2498°F ±(0.05%rdg + 1.4°F) on -58°F to -328°F
Number Of Parameters On The Display	3
Included Accessories	Users Manual, Battery (4), Software CD, USB wireless Antenna, K type thermocouple (2)



Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com