www.tripplite.com



6 outlet, 6ft cord, 2850 joules, 2-line coaxial, 1-line tel/modem, All-metal housing Isobar Surge Suppressor

MODEL NUMBER: ISOBAR6DBS



Description

Tripp Lite's ISOBAR6DBS Isobar Home/Business Theater Surge Suppressor provides premium protection--2850 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. Exclusive Isolated Filter Banks eliminate noise interference between components. 6

Highlights

- . 6 outlets / 6-ft. cord
- 2850 joule rating
- Isolated Filter Banks / all-metal housing
- 2-line 2.2 GHz gold coaxial protection
- 1-line tel/modem surge protection
- \$250,000 Ultimate Lifetime
 Insurance (USA and Canada only)

Applications

 Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

Package Includes

- ISOBAR6DBS Home/Business
 Theater Surge Suppressor
- 6 ft. gold coaxial cable
- 6 ft. phone cord
- Instruction manual with warranty information

outlets (with transformer spacing and plug-in safety covers), 2-line 2.2 GHz gold coaxial protection and 1-line tel/modem protection safeguard an entire home/business theater system. \$250,000 Ultimate Lifetime Insurance coverage (USA and Canada only). Includes all-metal housing, three diagnostic LEDs, 6-ft. cord with a right-angle plug, 6-ft. coaxial cable and 6-ft. phone cord.

Features

- 2850 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$250,000 Ultimate Lifetime Insurance (USA and Canada only) covers connected components against surge damage...for life!
- Isolated Filter Banks eliminate interference between connected components
- All-metal housing safely withstands the strongest surges
- 6 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- · Widely spaced outlets accommodate up to 3 transformers
- Four plug-in safety covers protect against accidental contact
- 2 sets of 2.2GHz gold coaxial protection to safeguard components on cable, satellite or antenna line (includes 6-ft gold coax cable)
- 1-line tel/modem surge protection (with included 6-ft. phone cord) safeguards personal video recorders (PVRs) on a single dial-up line.
- 6-ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 3 diagnostic LEDs alert user to protection, line power and fault status
- Keyhole slots provide convenient wall or cabinet mounting
- Illuminated master switch provides one-touch power control over all components. Circuit breaker protects against dangerous system overload



- All-metal housing (black) stands up to the most demanding environments
- UL and cUL listed

Specifications

OVERVIEW		
Intended Application	Home/Office, Computer Networks, Audio/Video	
ОПТРИТ		
Frequency compatibility	50 / 60 Hz	
Output watts	1440	
Circuit Breaker (amps)	12	
Outlet quantity / type	6 NEMA 5-15R	
Transformer accommodation	Accommodates 3 transformers	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P	
Input plug features	Space-saving right angle input plug	
Input cord length (ft.)	6	
Input cord length (m)	1.8	
Input cord gauge, type	14 gauge, SJT	
Voltage compatibility (VAC)	120	
Maximum Surge Amps	135000	
UPC ASSIGNMENT		
Unit Carton UPC#	037332011213	
LEDS ALARMS & SWITCHES		
Switches	Combination AC circuit breaker and two position red illuminated on/off power switch	
Diagnostic LEDs	PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	2850	
AC suppression response time	NM = 0 ns. CM = <1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	





Clamping voltage (RMS)	140V	
UL1449 let through rating	330V - UL verified	
EMI / RFI filtering	Up to 40 dB40-80 dB	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	Yes	
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	Yes	
Cable (Coax) Protection Details	2 line	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (HWD/in)	3 x 11.5 x 7	
Shipping Dimensions (HWD/cm)	7.62 x 29.2 x 17.8	
Shipping weight (lbs)	3.6	
Shipping weight (kg)	1.6	
Unit Dimensions (HWD/in)	2.5 x 9 x 3.5	
Unit Dimensions (HWD/cm)	6.35 x 22.9 x 8.9	
Unit weight (lbs)	2.8	
Unit weight (kg)	1.27	
Material of construction	Metal	
Integrated keyhole mounting tabs	Keyhole mounting slots allow desk or wall mounting	
Housing Color	Black	
Receptacle Color	Black	
AC line cord color	Black	
Style	Strip	
Outlets center to center measurement	Distance between horizontal outlets = 39.45mm; Distance between vertical outlets = 39.30mm	
Keyhole slot center to center measurement	Distance between horizontal tabs = 210.79mm; Distance between vertical tabs = 58.17mm	
SPECIAL FEATURES		
Appearance	Rugged all-metal corded strip format with high quality duplex receptacles	
Right-Angle Plug	Yes	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449	
	3/4	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

UL1363 (Power Tap)	UL1363UL1363	
UL497A (Communications)	UL497A	
FCC Part 68 (Communications)	FCC PFCC Part 68art 68	
cUL / CSA (Canada)	cULcUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 Ultimate Lifetime Insurance	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

> Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com