

**ZXMP6A16DN8**
**DUAL P-CHANNEL 60V ENHANCEMENT MODE MOSFET**
**Product Summary**

$V_{(BR)DSS}$	$R_{DS(ON)} \text{ Max}$	Package	$I_D$ $T_A = +25^\circ\text{C}$ (Notes 4 & 6)
-60V	85mΩ @ $V_{GS} = -10\text{V}$	SO-8	-3.9A
	125mΩ @ $V_{GS} = -4.5\text{V}$		-3.2A

**Description**

This MOSFET has been designed to minimize the on-state resistance and yet maintain superior switching performance, making it ideal for high efficiency power management applications.

**Applications**


- DC-DC Converters
- Power Management Functions
- Disconnect Switches
- Motor Control

**Features**


- Low On-Resistance
- Fast Switching Speed
- Low Threshold
- Low Gate Drive
- Low Profile SOIC Package
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**

**Mechanical Data**


- Case: SO-8
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish; Solderable per MIL-STD-202, Method 208 **Ⓔ3**
- Weight: 0.074 grams (approximate)



Top View



Top View




Equivalent Circuit

**Ordering Information**

Part Number	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
ZXMP6A16DN8TA	ZXMP6A16D	7	12	500

- Notes:
1. EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant. All applicable RoHS exemptions applied.
  2. See <http://www.diodes.com> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

**Marking Information**


ZXMP6A16D = Product Type Marking Code  
 YYWW = Date Code Marking  
 YY = Year (ex: 11 = 2011)  
 WW = Week (01 - 53)

**ZXMP6A16DN8**
**Maximum Ratings** (@T<sub>A</sub> = +25°C, unless otherwise specified.)





Characteristic			Symbol	Value	Unit
Drain-Source voltage			V <sub>DSS</sub>	-60	V
Gate-Source voltage		(Note 4)	V <sub>GS</sub>	±20	V
Continuous Drain current	V <sub>GS</sub> = 10V	(Notes 6 & 8)	I <sub>D</sub>	-3.9	A
		T <sub>A</sub> = +70°C (Notes 6 & 8)		-3.1	
		(Notes 5 & 8)		-2.9	
Pulsed Drain current		(Notes 7 & 8)	I <sub>DM</sub>	-18.3	A
Continuous Source current (Body diode)		(Notes 6 & 8)	I <sub>S</sub>	-3.2	A
Pulsed Source current (Body diode)		(Notes 7 & 8)	I <sub>SM</sub>	-18.3	A

**Thermal Characteristics**

Characteristic		Symbol	Value	Unit
Power dissipation Linear derating factor	(Notes 5 & 8)	P <sub>D</sub>	1.25	W mW/°C
			10.0	
	(Notes 5 & 9)		1.81	
			14.5	
Thermal Resistance, Junction to Ambient	(Notes 6 & 8)	R <sub>θJA</sub>	2.15	°C/W
			17	
	(Notes 5 & 8)		100	
	(Notes 5 & 9)		70	
Thermal Resistance, Junction to Lead	(Notes 6 & 8)	R <sub>θJL</sub>	60	
	(Notes 8 & 10)		48.85	
Operating and storage temperature range		T <sub>J</sub> , T <sub>STG</sub>	-55 to 150	°C

- Notes:
- AEC-Q101 V<sub>GS</sub> maximum is ±16V.
  - For a device surface mounted on 25mm x 25mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
  - Same as note (5), except the device is measured at t ≤ 10 sec.
  - Same as note (5), except the device is pulsed with D = 0.02 and pulse width 300μs.
  - For a dual device with one active die.
  - For a device with two active die running at equal power.
  - Thermal resistance from junction to solder-point.

## Thermal Characteristics




**ZXMP6A16DN8**
**Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
<b>OFF CHARACTERISTICS</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	-60	—	—	V	I <sub>D</sub> = -250μA, V <sub>GS</sub> = 0V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	—	—	-1.0	μA	V <sub>DS</sub> = -60V, V <sub>GS</sub> = 0V
Gate-Source Leakage	I <sub>GSS</sub>	—	—	±100	nA	V <sub>GS</sub> = ±20V, V <sub>DS</sub> = 0V
<b>ON CHARACTERISTICS</b>						
Gate Threshold Voltage	V <sub>GS(th)</sub>	-1.0	—	—	V	I <sub>D</sub> = -250μA, V <sub>DS</sub> = V <sub>GS</sub>
Static Drain-Source On-Resistance (Note 11)	R <sub>DS(on)</sub>	—	—	85	mΩ	V <sub>GS</sub> = -10V, I <sub>D</sub> = -2.9A
			—	125		V <sub>GS</sub> = -4.5V, I <sub>D</sub> = -2.4A
Forward Transconductance (Notes 11 & 12)	g <sub>fs</sub>	—	7.2	—	S	V <sub>DS</sub> = -15V, I <sub>D</sub> = -2.9A
Diode Forward Voltage (Note 11)	V <sub>SD</sub>	—	-0.85	-0.95	V	I <sub>S</sub> = -3.4A, V <sub>GS</sub> = 0V, T <sub>J</sub> = +25°C
Reverse recovery time (Note 12)	t <sub>rr</sub>	—	29.2	—	ns	I <sub>S</sub> = -2A, di/dt = 100A/μs,
Reverse recovery charge (Note 12)	Q <sub>rr</sub>	—	39.6	—	nC	T <sub>J</sub> = +25°C
<b>DYNAMIC CHARACTERISTICS (Note 12)</b>						
Input Capacitance	C <sub>iss</sub>	—	1021	—	pF	V <sub>DS</sub> = -30V, V <sub>GS</sub> = 0V, f = 1MHz
Output Capacitance	C <sub>oss</sub>	—	83.1	—	pF	
Reverse Transfer Capacitance	C <sub>rss</sub>	—	56.4	—	pF	
Total Gate Charge (Note 13)	Q <sub>g</sub>	—	12.1	—	nC	V <sub>GS</sub> = -5V
Total Gate Charge (Note 13)	Q <sub>g</sub>	—	24.2	—	nC	V <sub>GS</sub> = -10V
Gate-Source Charge (Note 13)	Q <sub>gs</sub>	—	2.5	—	nC	
Gate-Drain Charge (Note 13)	Q <sub>gd</sub>	—	3.7	—	nC	
Turn-On Delay Time (Note 13)	t <sub>D(on)</sub>	—	3.5	—	ns	V <sub>DD</sub> = -30V, V <sub>GS</sub> = -10V, I <sub>D</sub> = -1A, R <sub>G</sub> = 6.0Ω
Turn-On Rise Time (Note 13)	t <sub>r</sub>	—	4.1	—	ns	
Turn-Off Delay Time (Note 13)	t <sub>D(off)</sub>	—	35	—	ns	
Turn-Off Fall Time (Note 13)	t <sub>f</sub>	—	10	—	ns	

Notes: 11. Measured under pulsed conditions. Pulse width ≤ 300μs; duty cycle ≤ 2%  
12. For design aid only, not subject to production testing.  
13. Switching characteristics are independent of operating junction temperatures.


## Typical Characteristics




**Output Characteristics**




**Output Characteristics**




**Typical Transfer Characteristics**



**Normalised Curves v Temperature**





**On-Resistance v Drain Current**







**Source-Drain Diode Forward Voltage**

## Typical Characteristics (cont.)




## Test Circuits




**ZXMP6A16DN8**

**Package Outline Dimensions**



SO-8		
Dim	Min	Max
A	-	1.75
A1	0.10	0.20
A2	1.30	1.50
A3	0.15	0.25
b	0.3	0.5
D	4.85	4.95
E	5.90	6.10
E1	3.85	3.95
e	1.27 Typ	
h	-	0.35
L	0.62	0.82
θ	0°	8°
All Dimensions in mm		

**Suggested Pad Layout**



Dimensions	Value (in mm)
X	0.60
Y	1.55
C1	5.4
C2	1.27

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)



# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct    +86 (21) 6401-6692  
Email     amall@ameya360.com  
QQ        800077892  
Skype     ameyasales1 ameyasales2

➤ Customer Service :

Email     service@ameya360.com

➤ Partnership :

Tel        +86 (21) 64016692-8333  
Email     mkt@ameya360.com