


4302T-5V Sub Miniature 1.65mm Integrated Resistor-5 Volts

Description and Features



Sub-Miniature High Brite LED

- Integral current limiting resistor.
- TTL compatible-requires no external current limiter.
- Wide viewing angle 90° .
- High brightness-5mcd.

Electro-Optical Characteristics and Ratings

PART NUMBER	4302T1-5V	4302T3-5V	4302T5-5V
Output Color	Red	Ambr	Green
Diffusion	Diffused	Diffused	Diffused
Package Color	Red	Ambr	Green
Rated Current (mA)	10	10	10
Forward Voltage Typ. (V)	5	5	5
Forward Voltage Max. (V)	6	6	6
Luminous Intensity Min. (mcd)	1.3	0.9	1.6
Luminous Intensity Typ. (mcd)	5.0	5.0	5.0
Peak Wavelength (nm)	635	583	565
Viewing Angle 2θ 1/2 (degrees)	90	90	90
Continuous Forward Current Max. (mA)	13	13	13
Reverse Breakdown Voltage Min. (V)	5	5	5
Peak Forward Current Max. (1ms-300pps) (mA)	13	13	13

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com