
# 3M<sup>™</sup> Textool<sup>™</sup> Staggered ZIP Strip Sockets

.050" (1.27 mm) x .100" (2.54 mm)

### 32 Position



- For devices with .050" (1.27 mm) lead centers formed in staggered rows with .100" (2.54 mm) between centers and rows
- Socket with top-plate cover requires vertical insertion of leads
- Frequently used in pairs to handle devices with standard leads on opposite sides of the package
- Order left and right hand strips separately to obtain a complete pair
- Lever actuated zero insertion force mechanism

Date Modified: September 17, 2012

TS-0363-B Sheet 1 of 2

### **Physical**

#### **Insulation**

Material: Glass Filled Polysulfone

Flammability: UL 94V-0

Color: Green

Marking: 3M Logo & Part Number Identifier

**Contact:** 

Material: Beryllium Copper

Plating:  $30 \,\mu$ " (0.76  $\mu$ vm) Gold – MIL-G-45204, Type II, Grade C, over  $50 \,\mu$ " (1.27  $\mu$ m)

Nickel – QQ-N-290A, Class 2

### **Electrical**

**Current Rating:** 1 Amp

Insulation Resistance: > 1 \forall 109 W at 500 V dc Withstanding Voltage: 1000 V rms at Sea Level


### **Environmental**

**Operating Temperature Rating:** - 55 °C to +125 °C

# $3M^{\text{\tiny TM}}$ Textool $^{\text{\tiny TM}}$ Staggered ZIP Strip Sockets

.050" (1.27 mm) x .100" (2.54 mm)

### 32 Position



## **Ordering Information**

Socket Part Number	Contact Quantity
232-1270-01-0602J	32
232-1270-02-0602J	32

Contact Pattern

TS-0363-B Sheet 2 of 2

# **Important Notice** All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M. Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the

warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of

the legal theory asserted.

6801 River Place Blvd. Austin, TX 78726-9000

www.3Mconnectors.com

U.S.A. 1-800-225-5373

**3M Electronics Solutions Division** 

# AMEYA360 Components Supply Platform

## **Authorized Distribution Brand:**

























### Website:

Welcome to visit www.ameya360.com

### Contact Us:

### Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

### > Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

### Customer Service :

Email service@ameya360.com

# Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com