



ATP613

N-Channel Power MOSFET 500V, 5.5A, 2Ω, ATPAK

ON Semiconductor®

<http://onsemi.com>

Features

- Reverse recovery time $t_{rr}=60\text{ns}(\text{typ.})$
- Input Capacitance $C_{iss}=350\text{pF}(\text{typ.})$
- Halogen free compliance
- ON-resistance $R_{DS(on)}=1.55\Omega(\text{typ.})$
- 10V drive

Specifications

Absolute Maximum Ratings at $T_a=25^\circ\text{C}$

Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V_{DS}		500	V
Gate-to-Source Voltage	V_{GS}		± 30	V
Drain Current (DC)	I_D		5.5	A
Drain Current (Pulse)	I_{DP}	$PW \leq 10\mu\text{s}$, duty cycle $\leq 1\%$	19	A
Source-to-Drain Diode Forward Current (DC)	I_S		5.5	A
Source-to-Drain Diode Forward Current (Pulse)	I_{SP}	$PW \leq 10\mu\text{s}$, duty cycle $\leq 1\%$	19	A
Allowable Power Dissipation	P_D	$T_c=25^\circ\text{C}$	70	W
Channel Temperature	T_{ch}		150	$^\circ\text{C}$
Storage Temperature	T_{stg}		-55 to +150	$^\circ\text{C}$
Avalanche Energy (Single Pulse) *1	E_{AS}		93	mJ
Avalanche Current *2	I_{AV}		5.5	A


Note : *1 $V_{DD}=99\text{V}$, $L=5\text{mH}$, $I_{AV}=5.5\text{A}$ (Fig.1)*2 $L \leq 5\text{mH}$, Single pulse

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions

unit : mm (typ)


7057-001




Product & Package Information

- Package : ATPAK
- JEITA, JEDEC : -
- Minimum Packing Quantity : 3,000 pcs./reel


Packing Type: TL



Marking



Electrical Connection



ATP613

Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=10mA, V_{GS}=0V$	500			V
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS}=400V, V_{GS}=0V$			100	μA
Gate-to-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 30V, V_{DS}=0V$			± 100	nA
Cutoff Voltage	$V_{GS(off)}$	$V_{DS}=10V, I_D=1mA$	3		5	V
Forward Transfer Admittance	$ y_{fs} $	$V_{DS}=10V, I_D=2.75A$	1.5	2.9		S
Static Drain-to-Source On-State Resistance	$R_{DS(on)}$	$I_D=2.75A, V_{GS}=10V$		1.55	2.0	Ω
Input Capacitance	C_{iss}	$V_{DS}=30V, f=1MHz$		350		pF
Output Capacitance	C_{oss}			68		pF
Reverse Transfer Capacitance	C_{rss}			15		pF
Turn-ON Delay Time	$t_{d(on)}$	See Fig.2		14.2		ns
Rise Time	t_r			46		ns
Turn-OFF Delay Time	$t_{d(off)}$			37.6		ns
Fall Time	t_f			20.4		ns
Total Gate Charge	Q_g	$V_{DS}=200V, V_{GS}=10V, I_D=5.5A$		13.8		nC
Gate-to-Source Charge	Q_{gs}			3.2		nC
Gate-to-Drain "Miller" Charge	Q_{gd}			7.6		nC
Diode Forward Voltage	V_{SD}	$I_S=5.5A, V_{GS}=0V$		1.1	1.5	V
Reverse Recovery Time	t_{rr}	See Fig.3		60		ns
Reverse Recovery Charge	Q_{rr}			120		nC

Fig.1 Unclamped Inductive Switching Test Circuit




Fig.2 Switching Time Test Circuit

















Fig.3 Reverse Recovery Time Test Circuit



Ordering Information

Device	Package	Shipping	memo
ATP613-TL-H	ATPAK	3,000pcs./reel	Pb Free and Halogen Free






ATP613

Outline Drawing

ATP613-TL-H




Pin2 is idle pin with electrical designation only carried

*]:Lot indication

Mass (g)	Unit
0.266 * For reference	mm

Land Pattern Example



Unit: mm

Note on usage : Since the ATP613 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com