

DC to AC Inverters

Conformity to RoHS Directive

Connector type, Dimming, 5W, for 2 Bulbs

CXA Series CXA-M1212-RJL


FEATURES

- The CXA-M1212-RJL is an inverter for cold cathode fluorescent lamps and features a built-in dimmer.
- Because they employ advanced output current control, fluctuations in input voltage, load, and distributed capacitance have virtually no effect on brightness.
- Output open and short circuit conditions result in no damage, heat generation, or other difficulties.
- Safe design that includes a built-in overcurrent protection element.
- Insulation is simplified due to flat backside surface of board.
- It is a product conforming to RoHS directive.

TEMPERATURE AND HUMIDITY RANGES

Temperature range (°C)	Operating	0 to +60
	Storage	−30 to +85
Humidity range(%)RH		95max.
		[Maximum wet-bulb temperature 38°C]

SHAPES AND DIMENSIONS



- *1 Substrate (PWB: Printed wiring board): Flame retardant material UL94V-0 (FR-4 or CEM-3) $t=1\text{mm}$
- *2 : High-voltage generator (The entire surface within a range of 75mm away from the end of the base in the output)

Weight: 15.5g typ.

Dimensions in mm

Connector manufacturer's company and type				Symbol
1	Input connector	Molex Japan Co., Ltd.	53261-0571	CN1
2	Output connector	Japan Solderless Terminal Co., Ltd.	SM02(8.0)B-BHS-1	CN2
3	Output connector	Japan Solderless Terminal Co., Ltd.	SM02(8.0)B-BHS-1	CN3

TERMINAL NUMBERS AND FUNCTIONS

No. CN1

Terminal No.	Functions	Symbol
CN1-1	Input voltage Edc: 9.6 to 14.4V 12V[nom.]	Vin
CN1-2	0V	GND
CN1-3	Remote voltage Edc 0V: off/5 to 14.4V: on	Vrmt
CN1-4	Brightness dimmer voltage* Edc: 0 to 50k Ω	VR
CN1-5	(Maximum brightness on 50k Ω)	

* Brightness can be controlled by adjusting VR within a range of 0 to 50k Ω .

CN2

Terminal No.	Functions	Symbol
CN3-1	Output 1[High voltage] I _{rms} 2 to 6mA	V _{HIGH1}
CN3-2	—	N.C.
CN3-3	Output 1[Low voltage] (2V)	V _{LOW1}

CN3

Terminal No.	Functions	Symbol
CN3-1	Output 2[High voltage] I _{rms} 2 to 6mA	V _{HIGH2}
CN3-2	—	N.C.
CN3-3	Output 2[Low voltage] (2V)	V _{LOW2}

- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

- All specifications are subject to change without notice.


CXA-M1212-RJL

ELECTRICAL CHARACTERISTICS


Items	Unit	Symbol	Specifications			Conditions				Brightness
			min.	typ.	max.	Vin(V)	VR(k Ω)	Ta(°C)	RL(k Ω)	
Output current I _{rms}	mA	lout1	5.3	6	6.7	9.6 to 14.4	50	0 to +60	50 to 70	Maximum
		lout2	5.3	6	6.7	9.6 to 14.4	50	0 to +60	50 to 70	Maximum
		lout1	5.5	6	6.5	12	50	23±5	60	Maximum
		lout2	5.5	6	6.5	12	50	23±5	60	Maximum
		lout1	1.7	2	2.3	12	0	23±5	180	Minimum
		lout2	1.7	2	2.3	12	0	23±5	180	Minimum
Input current I _{dc}	A	I _{in}	—	0.47	0.75	9.6 to 14.4	0 to 50	0 to +60	50 to 70	
Oscillation frequency	kHz	F _L	33	39	45	9.6 to 14.4	50	0 to +60	50 to 70	
Open circuit output voltage E _{rms}	V	V _{open}	1400	1500	—	9.6 to 14.4	0 to 50	0 to +60	∞	

TYPICAL CONNECTIONS

EXAMPLE OF POTENTIOMETER DIMMER CONTROL





NO DIMMER CONTROL



*1 V_{rmr} (remote voltage) shall be ON after V_{in} was ON.

*2 SW a: on, b: off

BRIGHTNESS DIMMER RESISTANCE-OUTPUT CURRENT CHARACTERISTICS



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com