

ZXMC3A17DN8

COMPLEMENTARY 30V ENHANCEMENT MODE MOSFET


SUMMARY

N-Channel : $V_{(BR)DSS} = 30V$; $R_{DS(on)} = 0.050\Omega$; $I_D = 5.4A$

P-Channel : $V_{(BR)DSS} = -30V$; $R_{DS(on)} = 0.070\Omega$; $I_D = -4.4A$

DESCRIPTION

This new generation of trench MOSFETs from Zetex utilizes a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.




SO8

FEATURES


- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- Low profile SOIC package

APPLICATIONS

- Motor drive
- LCD backlighting



Q1 = N-channel




Q2 = P-channel

ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZXMC3A17DN8TA	7"	12mm	500 units
ZXMC3A17DN8TC	13"	12mm	2500 units

PINOUT



Top View

DEVICE MARKING

- ZXMC
3A17

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	N-channel	P-channel	UNIT
Drain-Source Voltage	V_{DSS}	30	-30	V
Gate-Source Voltage	V_{GS}	± 20	± 20	V
Continuous Drain Current ($V_{GS} = 10V$; $T_A = 25^\circ C$) ^{(b)(d)} ($V_{GS} = 10V$; $T_A = 70^\circ C$) ^{(b)(d)} ($V_{GS} = 10V$; $T_A = 25^\circ C$) ^{(a)(d)}	I_D	5.4 4.3 4.1	-4.4 -3.6 -3.4	A
Pulsed Drain Current ^(c)	I_{DM}	23	-20	A
Continuous Source Current (Body Diode) ^(b)	I_S	2.6	-2.5	A
Pulsed Source Current (Body Diode) ^(c)	I_{SM}	23	-20	A
Power Dissipation at $T_A = 25^\circ C$ ^{(a) (d)} Linear Derating Factor	P_D	1.25 10		W mW/ $^\circ C$
Power Dissipation at $T_A = 25^\circ C$ ^{(a) (e)} Linear Derating Factor	P_D	1.8 14		W mW/ $^\circ C$
Power Dissipation at $T_A = 25^\circ C$ ^{(b) (d)} Linear Derating Factor	P_D	2.1 17		W mW/ $^\circ C$
Operating and Storage Temperature Range	T_j, T_{stg}	-55 to +150		$^\circ C$

THERMAL RESISTANCE

PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient ^{(a) (d)}	$R_{\theta JA}$	100	$^\circ C/W$
Junction to Ambient ^{(a) (e)}	$R_{\theta JA}$	70	$^\circ C/W$
Junction to Ambient ^{(b) (d)}	$R_{\theta JA}$	60	$^\circ C/W$

NOTES:

(a) For a dual device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.

(b) For a dual device surface mounted on FR4 PCB measured at $t \leq 10$ sec.

(c) Repetitive rating 25mm x 25mm FR4 PCB, $D = 0.02$, pulse width = 300 μs - pulse width limited by maximum junction temperature.


(d) For a dual device with one active die.

(e) For dual device with two active die running at equal power.

ADVANCE INFORMATION

ZXMC3A17DN8

CHARACTERISTICS



ZXMC3A17DN8

ADVANCE INFORMATION

N-CHANNEL

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	30			V	I _D = 250μA, V _{GS} =0V
Zero Gate Voltage Drain Current	I _{DSS}			0.5	μA	V _{DS} =30V, V _{GS} =0V
Gate-Body Leakage	I _{GSS}			100	nA	V _{GS} =±20V, V _{DS} =0V
Gate-Source Threshold Voltage	V _{GS(th)}	1.0			V	I _D = 250μA, V _{DS} =V _{GS}
Static Drain-Source On-State Resistance ⁽¹⁾	R _{DS(on)}			0.050	Ω	V _{GS} = 10V, I _D = 7.8A
				0.065	Ω	V _{GS} = 4.5V, I _D = 6.8A
Forward Transconductance ⁽¹⁾ (3)	g _{fs}		10		S	V _{DS} = 10V, I _D = 7.8A
DYNAMIC ⁽³⁾						
Input Capacitance	C _{iss}		600		pF	V _{DS} = 25V, V _{GS} =0V f=1MHz
Output Capacitance	C _{oss}		104		pF	
Reverse Transfer Capacitance	C _{rss}		58.5		pF	
SWITCHING ⁽²⁾ (3)						
Turn-On-Delay Time	t _{d(on)}		2.9		ns	V _{DD} = 15V, I _D =3.5A R _G ≅ 6.0Ω, V _{GS} = 10V
Rise Time	t _r		6.4		ns	
Turn-Off Delay Time	t _{d(off)}		16		ns	
Fall Time	t _f		11.2		ns	
Gate Charge	Q _g		6.9		nC	V _{DS} = 15V, V _{GS} = 5V I _D = 3.5A
Total Gate Charge	Q _g		12.2		nC	V _{DS} = 15V, V _{GS} = 10V I _D = 3.5A
Gate-Source Charge	Q _{gs}		1.7		nC	
Gate-Drain Charge	Q _{gd}		2.4		nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage ⁽¹⁾	V _{SD}		0.85	0.95	V	T _j =25°C, I _S = 3.2A, V _{GS} =0V
Reverse Recovery Time ⁽³⁾	t _{rr}		18.8		ns	T _j =25°C, I _F = 3.5A, di/dt=100A/μs
Reverse Recovery Charge ⁽³⁾	Q _{rr}		14.1		nC	

(1) Measured under pulsed conditions. Pulse width $\leq 300\text{ms}$; Duty cycle $\leq 2\%$.

(2) Switching characteristics are independent of operating junction temperature.

(3) For design aid only, not subject to production testing.

ZXMC3A17DN8

ADVANCE INFORMATION

P-CHANNEL

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	-30			V	$I_D = -250\mu A$, $V_{GS}=0V$
Zero Gate Voltage Drain Current	I_{DSS}			-1.0	μA	$V_{DS} = -30V$, $V_{GS}=0V$
Gate-Body Leakage	I_{GSS}			100	nA	$V_{GS}=\pm 20V$, $V_{DS}=0V$
Gate-Source Threshold Voltage	$V_{GS(th)}$	-1.0			V	$I_D = -250\mu A$, $V_{DS}=V_{GS}$
Static Drain-Source On-State Resistance ⁽¹⁾	$R_{DS(on)}$			0.070 0.110	Ω Ω	$V_{GS} = -10V$, $I_D = -3.2A$ $V_{GS} = -4.5V$, $I_D = -2.5A$
Forward Transconductance ^{(1) (3)}	g_{fs}		6.4		S	$V_{DS} = -15V$, $I_D = -3.2A$
DYNAMIC ⁽³⁾						
Input Capacitance	C_{iss}		630		pF	$V_{DS} = -15V$, $V_{GS}=0V$ $f=1MHz$
Output Capacitance	C_{oss}		113		pF	
Reverse Transfer Capacitance	C_{rss}		78		pF	
SWITCHING ^{(2) (3)}						
Turn-On-Delay Time	$t_{d(on)}$		1.7		ns	$V_{DD} = -15V$, $I_D = -1A$ $R_G \cong 6.0\Omega$, $V_{GS} = -10V$
Rise Time	t_r		2.9		ns	
Turn-Off Delay Time	$t_{d(off)}$		29.2		ns	
Fall Time	t_f		8.7		ns	
Gate Charge	Q_g		8.3		nC	$V_{DS} = -15V$, $V_{GS} = -5V$ $I_D = -3.2A$
Total Gate Charge	Q_g		15.8		nC	$V_{DS} = -15V$, $V_{GS} = -10V$ $I_D = -3.2A$
Gate-Source Charge	Q_{gs}		1.8		nC	
Gate Drain Charge	Q_{gd}		2.8		nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage ⁽¹⁾	V_{SD}		-0.85	-0.95	V	$T_j=25^{\circ}C$, $I_S = -2.5A$, $V_{GS}=0V$
Reverse Recovery Time ⁽³⁾	t_{rr}		19.5		ns	$T_j=25^{\circ}C$, $I_S = -1.7A$, $di/dt=100A/\mu s$
Reverse Recovery Charge ⁽³⁾	Q_{rr}		16.3		nC	


NOTES:

- (1) Measured under pulsed conditions. Pulse width $\leq 300\text{ms}$; Duty cycle $\leq 2\%$.
(2) Switching characteristics are independent of operating junction temperature.
(3) For design aid only, not subject to production testing.

ZXMC3A17DN8

ADVANCE INFORMATION


N-CHANNEL TYPICAL CHARACTERISTICS




ADVANCE INFORMATION

ZXMC3A17DN8


N-CHANNEL TYPICAL CHARACTERISTICS



P-CHANNEL TYPICAL CHARACTERISTICS




P-CHANNEL TYPICAL CHARACTERISTICS



ZXMC3A17DN8

SO8 PACKAGE OUTLINE (Conforms to JEDEC MS-012AA Iss. C)



Controlling dimensions are in millimeters. Approximate conversions are given in inches

PACKAGE DIMENSIONS

DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min	Max	Min	Max		Min	Max	Min	Max
A	1.35	1.75	0.053	0.069	e	1.27 BSC		0.050 BSC	
A1	0.10	0.25	0.004	0.010	b	0.33	0.51	0.013	0.020
D	4.80	5.00	0.189	0.197	c	0.19	0.25	0.008	0.010
H	5.80	6.20	0.228	0.244	θ	0°	8°	0°	8°
E	3.80	4.00	0.150	0.157	h	0.25	0.50	0.010	0.020
L	0.40	1.27	0.016	0.050	-	-	-	-	-

© Zetex Semiconductors plc 2005

Europe	Americas	Asia Pacific	Corporate Headquarters
Zetex GmbH Streitfeldstraße 19 D-81673 München Germany	Zetex Inc 700 Veterans Memorial Hwy Hauppauge, NY 11788 USA	Zetex (Asia) Ltd 3701-04 Metroplaza Tower 1 Hing Fong Road, Kwai Fong Hong Kong	Zetex Semiconductors plc Zetex Technology Park Chadderton, Oldham, OL9 9LL United Kingdom
Telefon: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 europa.sales@zetex.com	Telephone: (1) 631 360 2222 Fax: (1) 631 360 8222 usa.sales@zetex.com	Telephone: (852) 26100 611 Fax: (852) 24250 494 asia.sales@zetex.com	Telephone (44) 161 622 4444 Fax: (44) 161 622 4446 hq@zetex.com

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to www.zetex.com



ISSUE 1 - OCTOBER 2005

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com