Data Sheet

Switching DC Power Supply with USB Charger Output 1-36 V, 0-3 A

Model 1550



The model 1550 is a compact 108 watt power supply delivering $1\text{-}36\ V$ and 0-3 A from its main isolated output. A unique feature of the 1550 supply is the USB charging port located on the front panel allowing the user to charge a cell phone or MP3 player. Clean power and quiet operation make this power supply ideal for any bench in laboratories, work shops and schools where bench space is limited.

Features:

- USB charging port on front panel
- Rear panel security loop
- Compact design
- Output On/Off control
- Large bright easy to read LCD display
- Constant voltage and constant current operation
- Overvoltage protection
- 230 VAC version with banana style outputs (model 1550-220V)



Charge your cell phone or MP3 player while you work	USB Charging Port	
	or MP3 player while	F5D V

Specifications	1550		
MAIN OUTPUT			
Output Voltage Adjustable Range	1.0 – 36 VDC		
Output Current Adjustable Range	0 – 3 A		
Voltage Regulation			
Load (10 % to 100 %)	±50 mV		
Line (min to max)	±20 mV		
Ripple	±5 mV rms		
Noise (Peak to Peak)	±50 mV		
Current Regulation			
Load (10 % to 100 %)	±20 mA		
Line (min to max)	±20 mA		
USB OUTPUT			
Output Voltage	5 V (±10 %)		
Output Current	400 mA (±10 %)		
Load Voltage Regulation	80 mV (±10 %)		
Ripple & Noise (no load rms)	8 mV (±10 %)		
OTHER			
AC Input	100 − 120 Vac (50~60 Hz)*		
Efficiency at Max Power	83 % (±10 %)		
Voltmeter and Ammeter Display	3 Digit		
Voltmeter Accuracy	± 1 % of rdg. ± 5 digits		
Switching Operation Frequency	80 kHz to 120 kHz		
Ammeter Accuracy	\pm 1 % of rdg. \pm 5 digits		
Full Load Input Current at 120 Vac	1.8 A (±10 %)		
LCD Indication	CC, CV, Amp, Volt, Output ON-OFF		
GENERAL			
Protection	Short Circuit, Overload, Over Temperature, Over Voltage		
Dimensions (W x H x D)	2.8" x 6.0" x 9.8" (70 x 150 x 250 mm)		
Weight	4.4 Lbs. (2 kgs)		
	One-Year Warranty		
Supplied Accessories	User manual and power cord		
+F 220V: -			

^{*}For 230V input, order model number 1550-220V.





AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com