

NP0080TA Series

Low Capacitance Protector

The NP series of low voltage/low capacitance overvoltage protection devices protect high speed xDSL line drivers and chipsets from both Lightning Surge and ESD events. The devices are designed with a low nominal capacitance as well as extremely low differential capacitance across frequency and voltage. The inherent low off-state leakage current provides superior performance in low voltage high speed applications. These characteristics allow protection of the system without distortion of the high speed data signal.

With it's advanced silicon structure the NP product is able to clamp very fast ESD events, and crowbar high energy surge events to help protect sensitive IC's all in a small footprint. The convenient flow thru design minimizes trace routing while maximizing circuit performance.

The NP series of low voltage/low capacitance devices helps designers to comply with the various regulatory standards and recommendations including: GR-1089-CORE, IEC 61000-4-5, ITU K.20/K.21/K.45, IEC 60950, TIA-968-A, FCC Part 68, EN 60950, UL 1950.

Features

- Low Nominal Capacitance
- Extremely Low Differential Capacitance
- Low Leakage (Transparent)
- High Surge Capability
- Precise Clamping Voltage
- Small Package Size
- Bi-directional Operation
- Flow Thru Layout
- IEC 61000-4-2 Level 4 ESD protection
- These are Pb-Free Devices

Typical Applications

- VDSL, ADSL, Access, Central Office, and Customer Premise modems and gateway IC side line driver chipset protection
- 10/100/1000 Ethernet Protection
- RS-232, RS-485 Transceiver Protection

ELECTRICAL CHARACTERISTICS

Device	V_{RWM}	V_{BR}	$I_R@$ $V_R = V_{RWM}$	$C@$ $V_R = 2\text{ V}$	$\Delta^\circ\text{C}$ $0\text{ V} - V_{RWM}$
	(V)	(V)	(μA)	(pF)	(pF)
NP0080TAT1G	8	9.5	0.5	13	4
NP0120TAT1G	12	12.5	0.5	13	3

SURGE/ESD RATINGS

Waveform	8x20 μs	ESD Air	ESD Contact
Value	50 A	15 kV	6 kV




ON Semiconductor®

<http://onsemi.com>



TSOP-5
TA SUFFIX
CASE 483


MARKING DIAGRAM



xxx = Specific Device Code
(NPxxx0TAT1G)
M = Date Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

PIN CONNECTIONS



(Top View)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

NP0080TA Series

ELECTRICAL CHARACTERISTICS TABLE ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Rating	Min	Typ	Max	Unit
V_{RWM}	Repetitive peak off-state voltage: Rated maximum (peak) continuous voltage that may be applied in the off-state condition	NP0080TAT1G		± 8	V
		NP0120TAT1G		± 12	
V_{BR1}	Breakdown Voltage: The minimum voltage across the device in or at the breakdown region. Measured at $I_{BR} = 1 \text{ mA}$	NP0080TAT1G	9.5		V
		NP0120TAT1G	12.5		
$V_{(BO)}$	Breakover Voltage: The maximum voltage across the device in or at the breakover region. Measured at $I_{(BO)} = 800 \text{ mA}$	NP0080TAT1G		20	V
		NP0120TAT1G		30	
I_R	Off-state Current: The dc value of current that results from the application of the off-state voltage			0.5	μA
I_H	Holding Current: The minimum current required to maintain the device in the on-state.		50		mA
C_o	Off-State Capacitance: $f = 1.0 \text{ MHz}$, $V_d = 1.0 \text{ Vrms}$, $V_D = -2 \text{ Vdc}$	NP0080TAT1G		13	pF
		NP0120TAT1G		13	
ΔC_1	Δ Capacitance: $f = 1.0 \text{ MHz}$, $V_d = 1.0 \text{ Vrms}$, $V_D = 0 \text{ V} - V_{rwm} $	NP0080TAT1G	4		pF
		NP0120TAT1G	3		
IPPS	Peak Pulse Current: Rated maximum value of peak impulse pulse current that may be applied. $8 \times 20 \mu\text{s}$, IEC-61000-4-5		50		A
ESD	Electrostatic Discharge (CONTACT): Rated maximum value of ESD per IEC-61000-4-2	NP0080TAT1G	8		kV
		NP0120TAT1G	6		
	Electrostatic Discharge (AIR): Rated maximum value of ESD per IEC-61000-4-2		15		
T_{STG}	Storage Temperature Range		-55	+150	$^\circ\text{C}$
T_J	Operating Junction Temperature Range		-40	+125	$^\circ\text{C}$

NP0080TA Series

Symbol	Parameter
V_{RWM}	Repetitive peak off-state voltage
V_{BR}	Breakdown voltage
$V_{(BO)}$	Breakover voltage
I_R	Off-state current
I_H	Holding current




Figure 1.

Application Information

The NPXXXXTAT can be used after the isolation transformer as protection for the xDSL line driver. The devices can be configured to protect against both differential and common mode surges and ESD.




Figure 2.




Figure 3.





Figure 4.



1. Connect pin 1 to pin 5 on PCB
2. Connect pin 3 to pin 4 on PCB
3. Pin 2 is no connection

Figure 5. PCB Layout

NP0080TA Series

DEVICE ORDERING INFORMATION

Device	Package	Shipping†
NP0080TAT1G	TSOP-5 (Pb-Free)	3000 / Tape & Reel
NP0120TAT1G	TSOP-5 (Pb-Free)	3000 / Tape & Reel

†For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com