ConnectCore® 7U

Universal ARM7 Core Module

Embedded ARM core processor module offers a wide range of connectivity options and integrated networking support in a compact DIP form factor.



Overview


The ConnectCore 7U core processor module utilizes Digi's high-performance NS7520 NET+ARM microprocessor, providing the ideal core processor platform for product designs demanding an additional level of performance, connectivity and flexibility. Combining core processing capabilities with long-term product availability, it is suited for applications including transportation, security/access control, building and industrial automation, retail, warehousing and others.

The module offers 16 MB of SDRAM and up to 8 MB of on-board Flash memory, an integrated 10/100 Mbit Ethernet MAC/PHY, up to two configurable UART/SPI ports, an I2C bus interface option, 16 shared GPIO ports for application-specific use, and an external 10-bit address/8-bit data bus interface for component integration flexibility.

The Digi JumpStart Kit® for NET+OS® delivers a ThreadX-based, IPv6-ready, royalty-free turnkey solution with all of the integrated building blocks needed for secure network-enabled embedded software development.



Block Diagram



Features/Benefits

- · Compact and versatile 48-pin DIP form factor
- Powerful 32-bit Digi NS7520 (ARM7) processor
- Integrated on-chip 10/100 Ethernet networking
- · Peripheral interface flexibility
- Digi processor technology for true long-term product availability
- Complete IPv6-ready NET+OS development platform
- Seamless migration path to fully integrated Digi NET+ARM system-on-chip solution



Digi JumpStart Kit® Overview





This royalty-free turnkey solution for embedded software development is based on the ThreadX Real-Time Operating System (RTOS), one of the most reliable and field-proven RTOS solutions available. In addition to ThreadX, NET+OS provides the integrated building blocks needed to create product solutions with leading network security using Digi embedded modules and microprocessors.

For professional NET+OS software development, the Eclipse based Digi ESP™ Integrated Development Environment (IDE) with graphical user interface and high-speed USB 2.0 hardware debugger is provided out-of-the-box.


- Royalty-free turn-key solution for embedded development
- Built on field-proven and compact ThreadX RTOS
- Fully integrated support for secure, IPv4/IPv6 networking applications
- Professional software development using Windows-based Digi ESP IDE

Please refer to the feature specs on our website for detailed information about the specific software platform capabilities.

Digi JumpStart Kit® Contents	Digi JumpStart Kit® Contents	
Software Platform	NET+OS°	
Module	ConnectCore 7U w/ 8 MB Flash, 16 MB SDRAM, Ethernet MAC/PHY	
Development Board	2 serial ports (RS-232, TTL), 2 user push-buttons, 2 user LEDs, Prototyping area, User/Application header, Status LEDs, Character display connector, Reset button, JTAG connector, 5VDC power supply	
CD/DVD	Digi NET+OS CD: NET+OS 7.x, Digi ESP IDE, BSP Source code, Sample code, Support, Documentation	
Documentation	Quick start guide, Digi ESP tutorial, NET+OS porting guide, NET+OS API documentation, Advanced Web Server, Hardware reference manual, Development board schematics	
Power Supplies and Accessories	External wall power supply (110/240VAC) with interchangeable outlet adapters (North America, EU, UK and Australia), JTAG adapter, Ethernet cable, Serial cable	
Other	Digi JTAG Link USB 2.0 hardware debugger	
Part Numbers (worldwide)	CC-7U-NET	

ConnectCore™ 7U		
Hardware		
Processor Type	32-bit NS7520 processor	
ARM Core	ARM7TDMI	
Processor Speed	55 MHz	
Memory Base Population	2/8 MB NOR flash	
Memory base ropulation	16 MB SDRAM	
Serial EEPROM	8 KB	
UART	Up to 230 Kbps	
GPIO GPIO	Up to 16 shared GPIO ports	
SPI	Master mode	
I ² C	Standard mode (100 kHz)	
External Memory Bus	10-bit address / 8-bit data; 2 external chip selects	

Hardware (continued)		
Timers/PWM	2 independent 27-bit timers; IRQ/FIQ, 2 microseconds to 20 hours	
JTAG	•	
Form Factor	48-Pin Dual In-Line Package (DIP)	
Dimensions (L x W x H)	2.475 in (62.87 mm) x 0.728 in (18.50 mm)	
Network Interface		
Standard	IEEE 802.3	
Physical Layer	10/100Base-T	
Data Rate	10/100 Mbps (auto-sensing)	
Mode	Full or Half duplex (auto-sensing)	
Integrated MAC/PHY	•	
Environmental		
Operating Temperature	0° C to +70° C (+32° F to +158° F)	
Storage Temperature	-50° C to +125° C (-58° F to +257° F)	
Relative Humidity	5% to 90% (non-condensing)	
Altitude	12,000 feet (3,658 meters)	
Power Requirements (3.3V)		
Maximum	280 mA	
Regulatory Approvals		
EN55022:2005, Class B	•	
IEC/CISPR 24:1997, modified + A1:2001+ A2:2002	•	



PCB Board Socket Components max 1.6mm

Side View

Visit www.digiembedded.com for part numbers.



DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. www.digi.com/support $\,$

91001350 C1/509

Digi International

877-912-3444 952-912-3444 info@digi.com **Digi International** France

+33-1-55-61-98-98 www.digi.fr

Digi International KK

+81-3-5428-0261 www.digi-intl.co.jp **Digi International** (HK) Limited

+852-2833-1008 www.digi.cn

BUY ONLINE • www.digiembedded.com



AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com