

GEN 2

GLOBAL STANDARD

Reader/Writer, Antenna

Unmatched Performance
Highest Quality
Best Delivered Value





Reader/Writer

GENERAL SPECIFICATIONS

BI/MONO-STATIC

Item	V740-BA50C22A (Bi-Static)	V740-BA50C04A (Mono-Static)
Operating Frequency	902 to 928MHz	902 to 928MHz
Supported Protocols	EPC Class0/0+, Class1, Gen2	EPC Class1, Gen2
Number of Antenna Ports	4	4
Interface Port	Ethernet	Ethernet
I/O Interface: Input	2 Photo coupler Input 20mA Max, 5 to 10mA typical	2 Photo coupler Input 20mA Max, 5 to 10mA typical
I/O Interface: Output	3 open collector outputs 24VDC Max, 20mA Max Internal resistance 360 ohm	3 open collector outputs 24VDC Max, 20mA Max Internal resistance 360 ohm
Supplied Voltage by AC Adapter	24Vdc, 2.0A	24Vdc, 2.0A
Power Supply	Normal 100-240Vac, 50/60Hz	Normal 100-240Vac, 50/60Hz
Operating Temperature	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)
Storage Temperature	-4 to 149°F (-20 to 65°C)	-4 to 149°F (-20 to 65°C)
Operating Humidity	25% to 85% RH (non condensing)	25% to 85% RH (non condensing)
Protective Rating	IP40	IP40
Regulatory Compliance	FCC Part 15, CSA	FCC Part 15, CSA
Dimension (LxWxD)	12.1 x 11.3 x 1.6 in (308 x 286 x 40mm)	12.1 x 11.3 x 1.6 in (308 x 286 x 40mm)
Weight	3.4 lbs. (1.5Kg)	3.4 lbs. (1.5Kg)



Antenna

GENERAL SPECIFICATIONS

BI-STATIC

MONO-STATIC

Item	V740-HS02CA (Bi-Static)	V740-HS01CA (Mono-Static)
Operating Frequency	902 to 928MHz	902 to 928MHz
Impedance	50ohm	50ohm
Polarization	Circular	Circular
Gain	6dBi max	6dBi max
Operating Temperature	14 to 122°F (-10 to 55°C)	14 to 122°F (-10 to 55°C)
Storage Temperature	-13 to 149°F (-25 to 65°C)	-13 to 149°F (-25 to 65°C)
Operating Humidity	25 to 85% RH non condensing	25 to 85% RH non condensing
Protective Rating	IP50	IP50
Dimension (LxWxD)	19.5 x 5.6 x 2.7 in (496 x 221 x 70mm)	10.1 x 10.1 x 2.3 in (256 x 256 x 2.3 in)
Weight	3.4 lbs (1.5Kg)	2.3 lbs (1.0Kg)

Omron RFID Division

JAPAN

1-11-1 Osaki,
Gate City Osaki West 14F
Shinagawa-ku,
Tokyo 141-0032 Japan
Phone: +81-5435-2016
Fax: +81-5435-2017

NORTH AMERICA

1920 Thoreau Dr
Suite 165
Schaumburg, IL 60173 USA
Phone: 888-303-RFID (7343)
Fax : 847-925-1260

EUROPE

Wegalaan 57
2132 JD Hoofddorp
The Netherlands
Phone : +31-235681200
Fax : +31-235681222

CHINA

Rm. 302, AZIA center,
1233 Lujiazui Ring Road
Pudong New Area, Shanghai
200120, PRC.
Phone: +86-21-5888-1666
Fax: +86-21-5888-7633/7933

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com