

SPECIFICATION


Part No. : **CAB.916**

Product Name : Taoglas Cable Assembly
N type Male Straight to
N type Male Straight
with 1M CFD-200 cable

Photo :




1. Cable Insertion Loss




2. CFD-200 Cable Specification

2.1 Drawing – Cross Section



2.2 Structure and Dimensions





2.3 Electrical & Physical Specification

Insulation Resistance:		1000 MΩ-Km (Min)				
Capacitance		80.4 ± 3 pF/m				
Nom. Impedance		50 ± 3 Ω				
Attenuation	150MHZ	450MHZ	900MHZ	1500MHZ	1800MHZ	2500MHZ
(dB/100M)	12.1	21.6	31.2	41.1	45.3	54.4


3. Technical Drawing

3.1 CAB.916



	Name	Part No.	Material	Finish	QTY
1	N Type(M)	N.TYPE.M.ST.PLUG.CFD200.J	Brass	Ni Plated	2
2	CFD-200	CFD.200.J	PVC Jacket	Black	1
3	Heat Shrink Tube	001311F0100XXA	PE	Black	2

3.2 Connector



	Name	Material	Finish	QTY
1	Body	Brass	Nickel	1
2	PIN	Brass	Gold Plated	1
3	Ferrule	Brass	Nickel	1

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com