



IGBT Modules

Short Circuit SOA Capability

Square RBSOA

$$\begin{aligned} I_{C25} &= 670 \text{ A} \\ V_{CES} &= 1200 \text{ V} \\ V_{CE(sat) \text{ typ.}} &= 2.3 \text{ V} \end{aligned}$$



E 72873

Symbol	Conditions	Maximum Ratings	
V_{CES}	$T_J = 25^\circ\text{C to } 150^\circ\text{C}$	1200	V
V_{CGR}	$T_J = 25^\circ\text{C to } 150^\circ\text{C}; R_{GE} = 20 \text{ k}\Omega$	1200	V
V_{GES}	Continuous	± 20	V
V_{GEM}	Transient	± 30	V
I_{C25}	$T_C = 25^\circ\text{C}$	670	A
I_{C80}	$T_C = 80^\circ\text{C}$	460	A
I_{CM}	$T_C = 80^\circ\text{C}, t_p = 1 \text{ ms}$ ①	920	A
t_{SC} (SCSOA)	$V_{GE} = \pm 15 \text{ V}, V_{CE} = V_{CES}, T_J = 125^\circ\text{C}$ $R_G = 1.8 \Omega$, non repetitive	10	μs
RBSOA	$V_{GE} = \pm 15 \text{ V}, T_J = 125^\circ\text{C}, R_G = 1.8 \Omega$ Clamped inductive load, $L = 100 \mu\text{H}$	$I_{CM} = 800$ $V_{CEK} \leq V_{CES}$	A
$P_{tot \text{ IGBT}}$	$T_C = 25^\circ\text{C}$	2750	W
T_J		150	$^\circ\text{C}$
T_{stg}		-40 ... +150	$^\circ\text{C}$
V_{ISOL}	50/60 Hz, RMS $t = 1 \text{ min}$ $I_{ISOL} \leq 1 \text{ mA}$ $t = 1 \text{ s}$ Insulating material: Al_2O_3	4000 4800	V~ V~
M_d	Mounting torque (module) (terminals)	2.25-2.75 20-25 2.5-3.7 22-33	Nm lb.in. Nm lb.in.
d_s	Creepage distance on surface	14	mm
d_A	Strike distance through air	9.6	mm
a	Max. allowable acceleration	50	m/s^2
Weight	Typical	250 8.8	g oz.

Data according to a single IGBT/FRED unless otherwise stated.

① Additional current limitation by external leads

Features

- NPT IGBT technology
- low saturation voltage
- low switching losses
- switching frequency up to 30 kHz
- square RBSOA, no latch up
- high short circuit capability
- positive temperature coefficient for easy paralleling
- MOS input, voltage controlled
- ultra fast free wheeling diodes
- package with DCB ceramic base plate
- isolation voltage 4800 V
- UL registered E72873


Advantages

- space and weight savings
- reduced protection circuits

Typical Applications

- AC and DC motor control
- power supplies
- welding inverters

Symbol	Conditions	Characteristic Values ($T_J = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
$V_{(BR)CES}$	$V_{GE} = 0\text{ V}$	1200		V
$V_{GE(th)}$	$I_C = 16\text{ mA}$, $V_{CE} = V_{GE}$	4.5		6.5 V
I_{CES}	$V_{CE} = V_{CES}$ $T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$		30	21 mA mA
I_{GES}	$V_{CE} = 0\text{ V}$, $V_{GE} = \pm 20\text{ V}$			1.6 μA
$V_{CE(sat)}$	$I_C = 400\text{ A}$, $V_{GE} = 15\text{ V}$		2.3	2.8 V
C_{ies}	$V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$, $f = 1\text{ MHz}$		26	nF
C_{oes}			4	nF
C_{res}			2	nF
$t_{d(on)}$	Inductive load, $T_J = 125^\circ\text{C}$ $I_C = 400\text{ A}$, $V_{GE} = \pm 15\text{ V}$ $V_{CE} = 600\text{ V}$, $R_G = 1.8\ \Omega$		100	ns
t_r			60	ns
$t_{d(off)}$			600	ns
t_f			90	ns
E_{on}			64	mJ
E_{off}			59	mJ
R_{thJC}	with heatsink compound			0.05 K/W
R_{thJS}			0.09	K/W




Free Wheeling Diode (FRED)		Characteristic Values ($T_J = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
V_F	$I_F = 400\text{ A}$, $V_{GE} = 0\text{ V}$		2.4	2.6 V
	$I_F = 400\text{ A}$, $V_{GE} = 0\text{ V}$, $T_J = 125^\circ\text{C}$		1.9	2.0 V
I_F	$T_C = 25^\circ\text{C}$ ①			750 A
	$T_C = 80^\circ\text{C}$			460 A
I_{RM}	$I_F = 400\text{ A}$, $V_{GE} = 0\text{ V}$, $-di_F/dt = 3000\text{ A}/\mu\text{s}$		300	A
t_{rr}	$T_J = 125^\circ\text{C}$, $V_R = 600\text{ V}$		200	ns
R_{thJC}				0.09 K/W
R_{thJS}			0.18	K/W

Anti Parallel Diode (FRED)		Characteristic Values ($T_J = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
V_F	$I_F = 100\text{ A}$, $V_{GE} = 0\text{ V}$		2.4	2.6 V
	$I_F = 100\text{ A}$, $V_{GE} = 0\text{ V}$, $T_J = 125^\circ\text{C}$		1.9	2.0 V
I_F	$T_C = 25^\circ\text{C}$			150 A
	$T_C = 80^\circ\text{C}$			95 A
I_{RM}	$I_F = 100\text{ A}$, $V_{GE} = 0\text{ V}$, $-di_F/dt = 600\text{ A}/\mu\text{s}$		62	A
t_{rr}	$T_J = 125^\circ\text{C}$, $V_R = 600\text{ V}$		200	ns
R_{thJC}				0.45 K/W
R_{thJS}			0.9	K/W

① Additional current limitation by external leads

Equivalent Circuits for Simulation


Conduction



IGBT (typ. at $V_{GE} = 15\text{ V}$; $T_J = 125^\circ\text{C}$)
 $V_0 = 1.3\text{ V}$; $R_0 = 3.2\text{ m}\Omega$

Free Wheeling Diode (typ. at $T_J = 125^\circ\text{C}$)
 $V_0 = 1.3\text{ V}$; $R_0 = 1.5\text{ m}\Omega$

Thermal Response



IGBT (typ.)
 $C_{th1} = 0.90\text{ J/K}$; $R_{th1} = 0.049\text{ K/W}$
 $C_{th2} = 2.07\text{ J/K}$; $R_{th2} = 0.001\text{ K/W}$

Free Wheeling Diode (typ.)
 $C_{th1} = 0.71\text{ J/K}$; $R_{th1} = 0.090\text{ K/W}$
 $C_{th2} = 1.30\text{ J/K}$; $R_{th2} = 0.002\text{ K/W}$




Fig. 1 Typ. output characteristics




Fig. 2 Typ. output characteristics




Fig. 3 Typ. transfer characteristics




Fig. 4 Typ. forward characteristics of free wheeling diode




Fig. 5 Typ. turn on gate charge




Fig. 6 Typ. turn off characteristics of free wheeling diode




Fig. 7 Typ. turn on energy and switching times versus collector current




Fig. 8 Typ. turn off energy and switching times versus collector current




Fig. 9 Typ. turn on energy and switching times versus gate resistor




Fig. 10 Typ. turn off energy and switching times versus gate resistor




Fig. 11 Reverse biased safe operating area RBSOA




Fig. 12 Typ. transient thermal impedance

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com