

Cx (pF)		WORKING VOLTAGE -40°C TO +125°C	I _{DC}	I.R. MIN. @ 100 (VDC.)	DWV (VAC)	TYPICAL NO LOAD INSERTION LOSS (dB) @ 25°C PER MIL-STD-220			
						10 MHz	100 MHz	1 GHz	10 GHz
2000 MIN.		250 VAC	20 Amps	10 G Ω	1500	5	50	60	65

REVISION RECORD	Original Release	0	REVISED BLOCK & NOTE 3. ADDED NOTE 5. S.M. 01-28-00	1	ADDED DWV & I.R. REVISED NOTES & METRIC. S.M. 06-15-04	2	NOTES 2 & 3 REVISED L.E. 06-29-04	3	ADDED NOTES 1-4 & RENUMBERED. S.M. 10-12-05	4	NOTES REVISED. L.E. 10-25-05	5	NOTES 4 & 6 REVISED. ADDED INK DOT. REVISED TORQUE. S.M. 01-20-06	6	TOLERANCES unless otherwise specified	Title FILTERED TERMINAL BLOCK 2 POSITION, UL RECOGNIZED							
	C.O. 19990607-1-06																						
															ANGLES ± N/A	Drawn S.M. 06-08-99	Scale FULL						
															TUSONIX TUCSON, ARIZONA	Approved T.C. 06-08-99							
																A	7602-501						

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com