

LEVER SWITCHES

POS. 2

POS. 1

VARIABLE ON SPECIFIC CIRCUITS - SEE CHART

CONTACTS

NON-LOCKING THUMB

LOCKING THUMB

NYLON ROLLER

MAX. PANEL .290 (8.33)

OPERATES ON 5 POS. SWITCH ONLY

3.000 (76.80)

1.830 (46.80)

1.219 (30.96)

1.937 (49.30)

2-HOLES FOR 4-40 SCREWS

4-HOLES FOR 3-48 TAPPED HOLES

MOUNTING CENTERS

531 inch (13.49mm) x 1.188 inch (30.18mm)

WITH ENCLINATION PLATE

WITH ENCLINATION PLATE

SEE CHART - VARIABLE CO. ON SPECIAL CIRCUITS

CONTACTS (SEE TEXT)

NYLON ROLLERS

NON-LOCKING THROW

LOCKING THROW

STOP PLATE

OPERATES ON POSITION SWITCH ONLY

KEYWAY - THIS SIDE

MAXIMUM PANEL THICKNESS .250 inch (6.35mm)

PANEL LAYOUT

USING NON TURN WASHER P-1063

USE OF BUSHING FOR NON-TURN

NON-TURN DEVICE

"TELEVER" SWITCH
SERIES 16000
(SINGLE HOLE
MOUNTING)

Inch

(mm)

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com