


## Overview

KEMET's MPLCG Series of metal composite inductors is ideal for use in DC to DC switching power supplies. The MPLCG's small size makes it ideal in applications with tight space requirements. The combination of composite core material and round wire allows these inductors to be used in applications with high switching frequencies and where efficiency is important.

## Applications

- Switching DC-DC power supplies
- Notebook computers
- Tablets
- Embedded computer systems
- HDTVs
- DVD and BluRay players



## Part Number System



MPLCG	0530	L	R22
Series	Size Code	Inductor	Inductance Code $\mu\text{H}$
MPLCG	0530 0630		R = decimal point Examples: R22 = .22 $\mu\text{H}$ 1R0 = 1.0 $\mu\text{H}$

**Table 1 – Ratings & Part Number Reference**



Part Number	Inductance (μH) @ 100 kHz	Inductance Tolerance	DC Resistance (mΩ) ±10%	Rated Current (A)	
				I <sub>rms</sub> <sup>1</sup> (Ref.)	I <sub>sat</sub> <sup>2</sup> (Ref.)
MPLCG0530LR22	0.22	±20%	3.7	14.1	10.2
MPLCG0530LR33	0.33	±20%	7.3	10.3	8.9
MPLCG0530LR47	0.47	±20%	9.0	9.3	8.7
MPLCG0530LR0	1.0	±20%	14.6	7.4	5.6
MPLCG0530LR5	1.5	±20%	21.7	5.9	5.6
MPLCG0530LR2	2.2	±20%	36.4	4.5	5.0
MPLCG0530LR3	3.3	±20%	58.0	3.6	3.1
MPLCG0530LR7	4.7	±20%	74.0	3.1	3.0
MPLCG0630LR22	0.22	±20%	2.7	21.4	17.9
MPLCG0630LR33	0.33	±20%	4.3	16.9	17.3
MPLCG0630LR47	0.47	±20%	5.0	15.8	15.6
MPLCG0630LR68	0.68	±20%	6.0	14.2	12.6
MPLCG0630LR82	0.82	±20%	7.0	13.1	11.8
MPLCG0630LR0	1.0	±20%	9.0	11.9	11.3
MPLCG0630LR5	1.5	±20%	15.0	9.9	8.3
MPLCG0630LR2	2.2	±20%	19.0	8.2	7.8
MPLCG0630LR3	3.3	±20%	30.0	6.5	6.3
MPLCG0630LR7	4.7	±20%	41.0	5.5	5.4

<sup>1</sup> T = 40 K rise at rated current.<sup>2</sup> Inductance drop 20% at rated current.

## DC-Superposed Characteristics



## DC-Superposed Characteristics




## Specifications

Part Number	Dimensions (mm)	Land Pattern
MPLCG0530	<p>Top view: 5.5 Maximum, 3.0 Maximum, 1.1, 1.1, 2.5 ±0.2, 5.0 ±0.2, (0.1)</p> <p>Side view: 2.5 ±0.2, (3.2)</p>	<p>2.8, 1.7, 2.3, 1.7</p>
MPLCG0630	<p>Top view: 7.5 Maximum, 3.0 Maximum, 1.4, 1.4, 3.2 ±0.2, 6.7 ±0.2, (0.1)</p> <p>Side view: 3.2 ±0.2, (3.2)</p>	<p>3.5, 2.0, 3.7, 2.0</p>

Operating temperature range: -20°C to +120°C (Include self temperature rise)

## Taping Specification


### Dimensions of indented square hole plastic tape



Series	Reel Qty		Dimensions (mm)							
			W	F	E <sub>1</sub>	P <sub>1</sub>	P <sub>2</sub>	P <sub>0</sub>	øD <sub>0</sub>	T
MPLCG0530	3,500	Tolerance	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	±0.05	±0.05
		Nominal	12.0	5.5	1.75	8.0	2.0	4.0	1.55	0.4
MPLCG0630	2,000	Tolerance	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	±0.05	±0.05
		Nominal	16.0	7.5	1.75	12.0	2.0	4.0	1.55	0.4

## Reel Specifications

### Reel dimensions



Series		Dimensions (mm)							
		A	B	C	D	A <sub>0</sub>	r	W <sub>1</sub>	W <sub>2</sub>
MPLCG0530	Tolerance	±5.0	±10.0	±1.0	±0.8	±0.5		±1.5	±2.0
	Nominal	ø380	ø95	ø13.5	ø21.0	2.0	R1.0	14.5	18.5
MPLCG0630	Tolerance	±5.0	±10.0	±1.0	±0.8	±0.5		±1.0	±1.5
	Nominal	ø380	ø95	ø13.5	ø21.0	2.0	R1.0	18.0	21.6

**KEMET Corporation  
World Headquarters**

2835 KEMET Way  
Simpsonville, SC 29681

Mailing Address:  
P.O. Box 5928  
Greenville, SC 29606

www.kemet.com  
Tel: 864-963-6300  
Fax: 864-963-6521

**Corporate Offices**  
Fort Lauderdale, FL  
Tel: 954-766-2800

**North America****Southeast**

Lake Mary, FL  
Tel: 407-855-8886

**Northeast**

Wilmington, MA  
Tel: 978-658-1663

**Central**

Novi, MI  
Tel: 248-306-9353

**West**

Milpitas, CA  
Tel: 408-433-9950

**Mexico**

Guadalajara, Jalisco  
Tel: 52-33-3123-2141

**Europe****Southern Europe**

Paris, France  
Tel: 33-1-4646-1006

Sasso Marconi, Italy  
Tel: 39-051-939111

**Central Europe**

Landsberg, Germany  
Tel: 49-8191-3350800

Kamen, Germany  
Tel: 49-2307-438110

**Northern Europe**

Bishop's Stortford, United Kingdom  
Tel: 44-1279-460122

Espoo, Finland  
Tel: 358-9-5406-5000

**Asia****Northeast Asia**

Hong Kong  
Tel: 852-2305-1168

Shenzhen, China  
Tel: 86-755-2518-1306

Beijing, China  
Tel: 86-10-5829-1711

Shanghai, China  
Tel: 86-21-6447-0707

Taipei, Taiwan  
Tel: 886-2-27528585

**Southeast Asia**

Singapore  
Tel: 65-6586-1900

Penang, Malaysia  
Tel: 60-4-6430200

Bangalore, India  
Tel: 91-806-53-76817

*Note: KEMET reserves the right to modify minor details of internal and external construction at any time in the interest of product improvement. KEMET does not assume any responsibility for infringement that might result from the use of KEMET Capacitors in potential circuit designs. KEMET is a registered trademark of KEMET Electronics Corporation.*

## Disclaimer

This product has been made available through a Private Label Agreement and a Development and Cross-Licensing Agreement between KEMET and NEC TOKIN to expand market and product offerings for both companies and their respective customers. For more information, please visit <http://www.kemet.com/nectokin>.

All product specifications, statements, information and data (collectively, the "Information") in this datasheet are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed.

All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Statements of suitability for certain applications are based on KEMET Electronics Corporation's ("KEMET") knowledge of typical operating conditions for such applications, but are not intended to constitute – and KEMET specifically disclaims – any warranty concerning suitability for a specific customer application or use. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by KEMET with reference to the use of KEMET's products is given gratis, and KEMET assumes no obligation or liability for the advice given or results obtained.

Although KEMET designs and manufactures its products to the most stringent quality and safety standards, given the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required.

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct    +86 (21) 6401-6692  
Email     amall@ameya360.com  
QQ        800077892  
Skype     ameyasales1 ameyasales2

➤ Customer Service :

Email     service@ameya360.com

➤ Partnership :

Tel        +86 (21) 64016692-8333  
Email     mkt@ameya360.com